Note: This datasheet may be out of date

Please download the latest datasheet of BLM03PG330SN1# from the official website of Murata Manufacturing

https://www.murata.com/en-us/products/productdetail?partno=BLM03PG330SN1%23

### BLM03PG330SN1#

"#" indicates a package specification code.








< List of part numbers with package codes >

BLM03PG330SN1B BLM03PG330SN1D BLM03PG330SN1J



### Appearance & Shape









- 1. The chip ferrite beads BLM series is designed to function nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted. BLM series is effective in circuits without stable ground lines because BLM series does not need a connection to ground.
- 2. The nickel barrier structure of the external electrodes provides excellent solder heat resistance.
- 3.BLM P series can be used in high current circuits due to its low DC resistance. It can match power lines to a maximum of 6ADC.

# **Applications**

Other Usage

For general



## **Packaging Information**

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	1000
D	180mm Paper Tape	15000
J	330mm Paper Tape	50000

1 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/03/09



Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=BLM03PG330SN1%23

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ BLM03PG330SN1\# \ from \ the \ official \ website \ of \ Murata \ Manufacturing} }$ 

## BLM03PG330SN1#

"#" indicates a package specification code.

Note: This datasheet may be out of date



Shape	SMD
Size Code (in mm)	0603
Size Code (in inch)	0201
Length	0.6mm
Length Tolerance	±0.03mm
Width	0.3mm
Width Tolerance	±0.03mm
Thickness	0.3mm
Thickness Tolerance	±0.03mm
Impedance (at 100MHz)	33Ω
Impedance (at 100MHz) Tolerance	±25%
Rated Current (at 85°C)	750mA
Rated Current (at 125°C)	750mA
DC Resistance(max.)	0.09Ω
Operating Temperature Range	-55°C to 125°C
Mass(typ.)	0.0003g
Number of Circuit	1

2 of 3

### Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2018/03/09

<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Note: This datasheet may be out of date.  $\underline{ Please \ download \ the \ latest \ data sheet \ of \ BLM03PG330SN1\# \ from \ the \ official \ website \ of \ Murata \ Manufacturing} }$ 


 $\begin{tabular}{ll} \hline $Co., Ltd. \\ $https://www.murata.com/en-us/products/productdetail?partno=BLM03PG330SN1\%23 \\ \end{tabular}$ 

## BLM03PG330SN1#

"#" indicates a package specification code.







Impedance-Frequency Characteristics

**Equivalent Circuit** 

3 of 3

### Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.