Note: This datasheet may be out of date

Please download the latest datasheet of DSS6NC52A102Q55# from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=DSS6NC52A102Q55%23

DSS6NC52A102Q55#

"#" indicates a package specification code.








< List of part numbers with package codes >

DSS6NC52A102Q55B



Appearance & Shape





- GND

 1 The bottom of the ferrite beads may not be level with each other.
 2 There may be a hole on the top of ferrite beads,
- which causes no characteristics deterioration



Features

DS_6 is a compact, high performance lead type EMI suppression filter which can be mounted 2.54mm pitch. Its three terminal structure enables precise high frequency performance.



Applications

Other Usage

For general



Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	250

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2018/03/12



Note: This datasheet may be out of date

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ DSS6NC52A102Q55\# from \ the \ official \ website \ of \ Murata \ Manufacturing} }$ Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=DSS6NC52A102Q55%23

DSS6NC52A102Q55#

"#" indicates a package specification code.



Shape	Lead
Length	8.0mm
Length Tolerance	max.
Width	2.54mm
Width Tolerance	max.
Thickness	7.0mm
Thickness Tolerance	max.
Rated Current	6A
Operating Temperature Range	-25℃ to 85℃
Mass(typ.)	0.42g
Number of Circuit	1
Insulation Resistance(min.)	5000ΜΩ
Rated Voltage	100Vdc
Withstanding Voltage	250Vdc
Capacitance	1000pF
Capacitance Tolerance	±20%
Structure/Shape	Small type beads inside(straight)

2 of 3

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2018/03/12

^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Note: This datasheet may be out of date $\underline{ \text{Please download the latest datasheet of DSS6NC52A102Q55\# from the official website of Murata Manufacturing} \\$ Co., Ltd.


https://www.murata.com/en-us/products/productdetail?partno=DSS6NC52A102Q55%23

DSS6NC52A102Q55#

"#" indicates a package specification code.








Insertion Loss Characteristics

Insertion Loss Characteristics (Main Items)



Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2018/03/12