

GLASS PASSIVATED BRIDGE RECTIFIERS

**REVERSE VOLTAGE – 400 to 1000 Volts
FORWARD CURRENT – 10 Amperes**


FEATURES

- Rating to 1000V PRV.
- Ideal for printed circuit board
- Reliable low cost construction utilizing molded plastic technique.
- UL recognition file # E95060

MECHANICAL DATA

- Case: GBU
- Case Material: Plastic material, UL flammability classification 94V-0
- Polarity Indicator: Symbol molded on body
- Weight: 3.72 grams (Approximate)

GBU



GBU		
DIM	MIN	MAX
A	21.80	22.30
B	18.30	18.80
C	3.30	3.56
D	17.50	18.00
E	0.76	1.00
F	0.46	0.56
G	7.40	7.90
H	3.50	4.10
I	1.65	2.16
J	2.25	2.75
K	1.95	2.35
L	1.02	1.27
M	4.83	5.33
N	7.0° TYPICAL	
O	(3.2) x 45°	
P	1.90 PADIUS	
All dimension in millimeter		

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

ABSOLUTE RATINGS

PARAMETER	SYMBOL	GBU1004	GBU1006	GBU1008	GBU1010	UNIT
Maximum repetitive peak reverse voltage	V_{RRM}	400	600	800	1000	V
Maximum DC blocking voltage	V_{DC}	400	600	800	1000	V
Average rectified output current per device with heatsink (Note 2) without heatsink @ $T_C = 100^\circ\text{C}$	$I_{(AV)}$	10 3.2				A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load @ $T_A = 25^\circ\text{C}$ @ $T_A = 125^\circ\text{C}$	I_{FSM}	240 220				A
Peak forward surge current 1ms single half sine-wave superimposed on rated load @ $T_A = 25^\circ\text{C}$ @ $T_A = 125^\circ\text{C}$	I_{FSM}	480 440				A
$I^2 t$ rating for fusing ($t = 8.3 \text{ ms}$) @ $T_A = 25^\circ\text{C}$	$I^2 t$	239				A^2S
Mounting Torque (recommended torque: 0.5 N.m)	TOR	0.8				N.m
Operating and storage temperature range	T_J, T_{STG}	-55 to +150				$^\circ\text{C}$

STATIC ELECTRICAL CHARACTERISTICS

PARAMETER	TEST CONDITION	SYMBOL	MAX	UNIT
Forward voltage	$I_F = 5.0\text{A}$ $T_J = 25^\circ\text{C}$	V_F	1.0	V
	$I_F = 10\text{A}$ $T_J = 25^\circ\text{C}$		1.2	
Leakage current	V_R at rated $T_J = 25^\circ\text{C}$ $T_J = 125^\circ\text{C}$	I_R	5 500	μA
Typical junction capacitance (Note 1)		C_J	60	pF

THERMAL CHARACTERISTICS

PARAMETER	SYMBOL	TYP.	UNIT
Typical thermal resistance	R_{thJC} (Note 2)	2.0	$^\circ\text{C/W}$
	R_{thJC} (without heatsink)	5.6	
	R_{thJA} (without heatsink)	22	

Note :

- (1) Measured at 1.0MHz and applied reverse voltage of 4.0V DC
- (2) Thermal resistance junction to case and ambient in accordance with JESD-51. Device mounted on 150mm * 150mm * 1.6mm Cu plate heatsink.

RATING AND CHARACTERISTIC CURVES GBU1004 thru GBU1010



FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL JUNCTION CAPACITANCE




FIG.5- TYPICAL REVERSE CHARACTERISTICS





FIG.6- NON-REPETITIVE SURGE CURRENT



Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.