

SK12-A THRU SK120-A

1.0A Surface Mount Schottky Barrier Rectifiers - 20V-200V


Features

- ▶ The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- ▶ For surface mounted applications
- ▶ Metal silicon junction, majority carrier conduction
- ▶ Low power loss, high efficiency
- ▶ Built-in strain relief, ideal for automated placement
- ▶ High forward surge current capability
- ▶ High temperature soldering guaranteed: 250°C/10 seconds at terminals
- ▶ Compliant to RoHS Directive 2011/65/EU

Mechanical data

- ▶ **Case:** JEDEC DO-214AC molded plastic body
- ▶ **Terminals:** Solder plated, solderable per MIL-STD-750, Method 2026
- ▶ **Polarity:** Color band denotes cathode end
- ▶ **Mounting Position:** Any
- ▶ **Weight:** 0.002 ounce, 0.07 grams

Package outline



Maximum ratings and Electrical Characteristics (AT T_A=25°C unless otherwise noted)

PARAMETER	CONDITIONS	Symbol	MIN.	TYP.	MAX.	UNIT
Forward rectified current	See Fig.2	I _O			1.0	A
Forward surge current	8.3ms single half sine-wave (JEDEC methode)	I _{FSM}			30	A
Reverse current	V _R = V _{RRM} T _A = 25°C	I _R			0.5	mA
	V _R = V _{RRM} T _A = 100°C				10	
Thermal resistance	Junction to ambient NOTE 1	R _{θJA}		88		°C/W
Diode junction capacitance	f=1MHz and applied 4V DC reverse voltage	C _J		110		pF
Storage temperature		T _{STG}	-65		+150	°C

Note: 1.P.C.B. mounted with 0.2x0.2" (5.0x5.0mm) copper pad areas

SYMBOLS	V _{RRM} ^{*1} (V)	V _{RMS} ^{*2} (V)	V _R ^{*3} (V)	V _F ^{*4} (V)	Operating temperature T _J (°C)
SK12-A	20	14	20	0.45	-55 to +125
SK13-A	30	21	30	0.55	
SK14-A	40	28	40		
SK15-A	50	35	50	0.70	-55 to +150
SK16-A	60	42	60		
SK18-A	80	56	80	0.85	
SK110-A	100	70	100		
SK115-A	150	105	150		
SK120-A	200	140	200		

*1 Repetitive peak reverse voltage







*2 RMS voltage

*3 Continuous reverse voltage

*4 Maximum forward voltage@I_F=1.0A



SK12-A THRU SK120-A

Rating and characteristic curves



SK12-A THRU SK120-A

Pinning information

Pin	Simplified outline	Symbol
Pin1 cathode Pin2 anode		

Marking

Type number	Marking code
SK12-A	SK12
SK13-A	SK13
SK14-A	SK14
SK15-A	SK15
SK16-A	SK16
SK18-A	SK18
SK110-A	SK110
SK115-A	SK115
SK120-A	SK120

Suggested solder pad layout



Dimensions in inches and (millimeters)

PACKAGE	A	B	C
SMA	0.110 (2.80)	0.063 (1.60)	0.087 (2.20)