



Ordering code

A0800 WR-S-XP XXX
 ① ② ③ ④ ⑤

- ① Series No.
- ② Connector type: WR=Right angle
- ③ Mounting type: S=SMT without boss
- ④ No. of circuits
- ⑤ Option code:
 Blank=Contacts/Matte Tin-plated and Solder tabs/Matte Tin-plated
 D01=Contacts/Gold-flash and Solder tabs/Gold-flash
 D02=Contacts/Gold-plated 3u" and Solder tabs/Gold-flash

SPECIFICATIONS

Current Rating: 0.5A AC,DC
 Voltage Rating: 30V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 200V AC/minute
 Pin Material: Phosphor Bronze/
 Matte Tin-plated or Gold-flash or
 Gold-plated 3u"
 Solder Tabs: Phosphor Bronze/
 Matte Tin-plated or Gold-flash
 Material: Nylon 6T,UL94V-0
 Color: Natural(Beige)

Circuit No.	Dimensions			
	A	B	C	D
02P	0.80	3.80	1.90	2.38
03P	1.60	4.60	2.70	3.18
04P	2.40	5.40	3.50	3.98
05P	3.20	6.20	4.30	4.78
06P	4.00	7.00	5.10	5.58
07P	4.80	7.80	5.90	6.38
08P	5.60	8.60	6.70	7.18
10P	7.20	10.20	8.30	8.78
12P	8.80	11.80	9.90	10.38
14P	10.40	13.40	11.50	11.98
15P	11.20	14.20	12.30	12.78
16P	12.00	15.00	13.10	13.58
17P	12.80	15.80	13.90	14.38
20P	15.20	18.20	16.30	16.78

B2	ECN NO. EN1001040002	2010. 01. 04					
B1	REVISE	2009. 04. 01	UNIT	SCALE	SHEET	TITLE:	
B0	REVISE	2009. 03. 19	mm		1 of 2	<p>0.80mm PITCH 90° WAFER-SMT TYPE</p>	
A5	REVISE	2008. 11. 26	DRAWN BY		APPROVED BY		
A4	REVISE	2008. 04. 08	李勤		董正一		
A3	REVISE	2007. 10. 12	2006. 02. 07		2006. 02. 07		
A2	REVISE	2007. 07. 26	GENERAL TOLERANCE				
A1	REVISE	2006. 04. 15	X. X±0. 25	ANGLE±			
A0	NEW RELEASE	2006. 02. 07	X. XX±0. 15	DRAW NO. :			
REV.	DESCRIPTION	DATE	X. XXX±0. 05	A0800WR-S-XP		REV. B2	



燦達電子工業股份有限公司
 JOINT TECH ELECTRONIC IND. CO., LTD.