
## KEMET Part Number: PME261KA5100KR19T0

(P561HE103K220L)



## PME261/P561, Film, Metallized Paper, General Purpose, 0.01 uF, 10%, 400 VDC, 85°C, Lead Spacing = 10.2mm



General Information	
Series:	PME261/P561
Dielectric:	Metallized Paper
Style:	Radial
Features:	Pulse in DC and low frequency applications
RoHS:	Yes
Lead:	Wire Leads
AEC-Q200:	No
Construction:	Molded
Miscellaneous:	AC Operation: 70C MAX.

Dimensions	
L	13.5mm +0/-0.5mm
Н	7.5mm +0/-0.5mm
Т	3.9mm +0/-0.5mm
S	10.2mm +0.6/-0.1mm
HO	18.5mm +/-0.5mm
F	0.6mm +/-0.05mm

Packaging Specifications	
Packaging:	T&R
Packaging Quantity:	700

Specifications	
Capacitance:	0.01 uF
Capacitance Tolerance:	10%
Voltage AC:	220 VAC
Voltage DC:	400 VDC
Temperature Range:	-40/+100°C
Rated Temperature:	85°C
Dissipation Factor:	1.3% 1kHz
Insulation Resistance:	12 GOhms
Max dV/dt:	2000 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

