
KEMET Part Number: PHE850EB5220MB06R17

(F850BL223M300A)



PHE850/F850, Film, Metallized Polypropylene, Safety, 0.022 uF, 20%, 300 VAC (Y2), 1250 VDC, 110°C, Lead Spacing = 15mm



| Series: | PHE850/F850 |
|-----------------|--|
| Dielectric: | Metallized Polypropylene |
| Style: | Radial |
| Features: | EMI Safety |
| RoHS: | Yes |
| Lead: | Wire Leads |
| Qualifications: | ENEC, UL, cUL |
| AEC-Q200: | No |
| Notes: | Not For New Design, Please Check Possible Alternative Parts (AltPart). |

General Information

| Dimensions | | |
|------------|---------------|--|
| L | 18mm MAX | |
| Н | 14.5mm MAX | |
| Т | 7.5mm MAX | |
| S | 15mm +/-0.4mm | |
| LL | 17mm NOM | |
| F | 0.8mm NOM | |

| Packaging Specifications | |
|--------------------------|-----------|
| Packaging: | Bulk, Bag |
| Packaging Quantity: | 400 |

| Specifications | |
|------------------------|--|
| Capacitance: | 0.022 uF |
| Capacitance Tolerance: | 20% |
| Voltage AC: | 300 VAC (Y2) |
| Voltage DC: | 1250 VDC |
| Temperature Range: | -55/+110°C |
| Rated Temperature: | 110°C |
| Dissipation Factor: | 0.15% 1kHz, 0.2% 10kHz, 0.6% 100kHz |
| Insulation Resistance: | 30 GOhms |
| Max dV/dt: | 100 V/us |
| Safety Class: | Y2 |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.



© 2006 - 2020 KEMET