






REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD
1	△	Part No. Change:FR-050FSS-DXX-HXX To FBB05002-FXXS1XX3XXM-HXX	29/OCT/13	JACOB	CHERRY
2	△	Structure Change	26/DEC/18	CHERRY	KATE
3		Add packaging specification	05/DEC/19	KATE	CHERRY

**Electrical**  
 Current Rating: 0.5A AC(rms)/DC  
 Voltage Rating: 50V AC(rms)/DC  
 Contact Resistance: 40 mΩ Max  
 Insulation Resistance: 100 MΩ MIN  
 Withstanding Voltage: 250V AC r.m.s  
 Temperature Range-Operating: -25°C~+85°C

**Material and Plating**  
 Housing: LCP( UL 94V-0)  
 Contact Pin: Phosphor Bronze  
 Plating: Gold Plated

Height H(in/mm)	Female H1(in/mm)	Male H2(in/mm)
.118(3.00)	.087(2.20)	.031(0.80)
.138(3.50)	.087(2.20)	.051(1.30)
.157(4.00)	.118(3.00)	.039(1.00)
.177(4.50)	.138(3.50)	.039(1.00)
.197(5.00)	.157(4.00)	.118(3.00)
.217(5.50)	.177(4.50)	.039(1.00)
.236(6.00)	.157(4.00)	.079(2.00)
.256(6.50)	.177(4.50)	.079(2.00)




Recommended P.C.Board Layout

Ordering Information

FBB 050 02 - F XX S 1 XX 3 XX M HXX  
 1 2 3 4 5 6 7 8 9 10 11 12

1   Category FBB-Board To Board	2   Series Number 050-Pitch0.5mm	3   Distinction No. 02	4   Type F-Female	5   Circuits XX	6   Entry Angle S-180° Vertical
7   Plating 1-Gold Plated	8   Thickness of Plating 00-Gold Flash 03-3μ"	9   Material-Resin 3-LCP	10   Color-Resin K6-Black W5-White	11   Packaging M-Reel	12   Female Height H22-2.2mm H30-3.0mm .....

THIRD ANGLE PROJECTION		GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY	DATE	PART NO.	TEM NO.	 Leader Of Industry
DESIGN UNITS Inch (metric)	X±.012(0.30)	X'±5'		FRANK	26/SEPT/13	FBB05002-FXXS1XX3XXMHXX	FBB05002-F	
SCALE	X.X±.008(0.20)	X'±2'		CHECKED BY	DATE	TITLE		REV 3
5:1	X.XX±.006(0.15)	.XX±1'		CHERRY	26/SEPT/13	Board to Board Pitch 0.5mm 180° Vertical (SMT)		SHEET NO. 1/3
SIZE	X.XXX±.004(0.10)	.XXX±0.5'		DRAWN BY	DATE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
A4				JACOB	26/SEPT/13			

1 2 3 4 5 6 7 8

REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

A

A

B

B

C

C

D



D



E

E

F


F

Circuits (n)	Part No. 	Dimensions(in/mm)				Circuits (n)	Part No. 	Dimensions(in/mm)			
		A	B	C	D			A	B	C	D
8	FBB05002-F08S1XX3XXMHXX	.185(4.70)	.059(1.50)	.134(3.40)	.079(2.00)	34	FBB05002-F34S1XX3XXMHXX	.441(11.20)	.315(8.00)	.390(9.90)	.335(8.50)
10	FBB05002-F10S1XX3XXMHXX	.205(5.20)	.079(2.00)	.154(3.90)	.098(2.50)	36	FBB05002-F36S1XX3XXMHXX	.461(11.70)	.335(8.50)	.409(10.40)	.354(9.00)
12	FBB05002-F12S1XX3XXMHXX	.224(5.70)	.098(2.50)	.173(4.40)	.118(3.00)	38	FBB05002-F38S1XX3XXMHXX	.480(12.20)	.354(9.00)	.429(10.90)	.374(9.50)
14	FBB05002-F14S1XX3XXMHXX	.244(6.20)	.118(3.00)	.193(4.90)	.138(3.50)	40	FBB05002-F40S1XX3XXMHXX	.500(12.70)	.374(9.50)	.449(11.40)	.394(10.00)
16	FBB05002-F16S1XX3XXMHXX	.264(6.70)	.138(3.50)	.213(5.40)	.157(4.00)	42	FBB05002-F42S1XX3XXMHXX	.520(13.20)	.394(10.00)	.469(11.90)	.413(10.50)
18	FBB05002-F18S1XX3XXMHXX	.283(7.20)	.157(4.00)	.232(5.90)	.177(4.50)	44	FBB05002-F44S1XX3XXMHXX	.539(13.70)	.413(10.50)	.488(12.40)	.433(11.00)
20	FBB05002-F20S1XX3XXMHXX	.303(7.70)	.177(4.50)	.252(6.40)	.197(5.00)	46	FBB05002-F46S1XX3XXMHXX	.559(14.20)	.433(11.00)	.508(12.90)	.453(11.50)
22	FBB05002-F22S1XX3XXMHXX	.323(8.20)	.197(5.00)	.272(6.90)	.217(5.50)	50	FBB05002-F50S1XX3XXMHXX	.598(15.20)	.472(12.00)	.547(13.90)	.492(12.50)
24	FBB05002-F24S1XX3XXMHXX	.343(8.70)	.217(5.50)	.291(7.40)	.236(6.00)	60	FBB05002-F60S1XX3XXMHXX	.697(17.70)	.571(14.50)	.646(16.40)	.591(15.00)
26	FBB05002-F26S1XX3XXMHXX	.362(9.20)	.236(6.00)	.311(7.90)	.256(6.50)	70	FBB05002-F70S1XX3XXMHXX	.795(20.20)	.669(17.00)	.744(18.90)	.689(17.50)
28	FBB05002-F28S1XX3XXMHXX	.382(9.70)	.256(6.50)	.331(8.40)	.276(7.00)	80	FBB05002-F80S1XX3XXMHXX	.894(22.70)	.768(19.50)	.843(21.40)	.787(20.00)
30	FBB05002-F30S1XX3XXMHXX	.402(10.20)	.276(7.00)	.350(8.90)	.295(7.50)	90	FBB05002-F90S1XX3XXMHXX	.992(25.20)	.866(22.00)	.941(23.90)	.886(22.50)
32	FBB05002-F32S1XX3XXMHXX	.421(10.70)	.295(7.50)	.370(9.40)	.315(8.00)	100	FBB05002-F100S1XX3XXMHXX	1.091(27.70)	.965(24.50)	1.039(26.40)	.984(25.00)

 THIRD ANGLE PROJECTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY FRANK	DATE 26/SEPT/13	PART NO. FBB05002-FXXS1XX3XXMHXX	TEM NO. FBB05002-F	 Leader Of Industry
	X.±.012(0.30)	X.±5'	CHECKED BY CHERRY	DATE 26/SEPT/13	TITLE Board to Board Pitch 0.5mm 180° Vertical (SMT)	REV 3	
	DESIGN UNITS Inch (metric)	X.X±.008(0.20)	X.±2'	DRAWN BY JACOB	DATE 26/SEPT/13	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
SCALE 5:1	SIZE A4	X.XX±.006(0.15)	X.X±1'				
		X.XXX±.004(0.10)	.XXX±0.5'				






1 2 3 4 5 6 7 8

REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD



- Note:
- 10 sprocket hole cumulative tolerance  $\pm 0.2$
  - Carrier camber is within 1.0mm in 100mm
  - Material: Black Conductive polystyrene Alloy 100% recyclable
  - All dimensions meet EIA-481-B requirements
  - Peel off force of cover tape & carrier tape: 20g~130g(0.2N~1.3N)
  - Component load per 13" reel: 1,000 pcs

Circuits (n)	Dimensions(in/mm)		
	A	B	C
4~20	.630(16.0)	.295(7.50)	—
22~52	.945(24.0)	.453(11.50)	—
54~70	1.260(32.0)	.561(14.25)	1.122(28.50)
72~100	1.732(44.0)	.797(20.25)	1.594(40.50)



 THIRD ANGLE PROJECTION DESIGN UNITS Inch (metric) SCALE 5:1 SIZE A4	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY FRANK	DATE 05/DEC/19	PART NO. FBB05002-FXXS1XX3XXMHXX	ITEM NO. FBB05002-F	 Leader of Industry
	X.±.012(0.30)	X.'±5'	CHECKED BY CHERRY	DATE 05/DEC/19	TITLE Board to Board Pitch 0.5mm 180° Vertical (SMT)		
	X.XX±.008(0.20)	.X'±2'	DRAWN BY KATE	DATE 05/DEC/19	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TXGA INDUSTRIAL ELECTRONICS(S.Z)CO.,LTD AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		SHEET NO. 3/3
	X.XX±.006(0.15)	.XX'±1'					
	X.XXX±.004(0.10)	.XXX'±0.5'					