



# TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,  
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: [tstsales@mail.taisaw.com](mailto:tstsales@mail.taisaw.com) Web: [www.taisaw.com](http://www.taisaw.com)


## Product Specifications Approval Sheet

Product Name: SAW Filter 465MHz

TST Parts No.:TA0266A

Customer Parts No.:\_\_\_\_\_

Customer signature required
Company:_____
Division:_____
Approved by :_____
Date:_____

Checked by:\_\_\_\_\_ Anne Chen 

Approval by:\_\_\_\_\_ Andy Yu 

Date:\_\_\_\_\_ 2019/07/22

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.

## SAW Filter 465 MHz

MODEL NO.: TA0266A

REV. NO.:3.0

### A. MAXIMUM RATING:

1. Input Power Level: 0 dB<sub>m</sub>
2. DC voltage: 10 V
3. Operating Temperature: -10°C to +50°C
4. Storage Temperature: -40°C to +85°C
5. Moisture Sensitivity Level: Level 1(MSL1)

RoHS Compliant  
Lead free  
Lead-free soldering


Electrostatic Sensitive Device

### B. ELECTRICAL CHARACTERISTICS:



Item	Min.	Typical	Max.
<b>Center frequency</b> $F_c$ (dB)	-	465.1375	-
<b>Insertion loss</b> ( $F_c \pm 2.5875$ MHz) <b>IL</b> (dB)	-	-	4.0
<b>Amplitude ripple</b> ( $F_c \pm 2.5875$ MHz) (dB)	-	-	2.0
<b>Attenuation</b> (Reference level from 0 dB)			
365.1375 ~ 424.3375 MHz (dB)	50	-	-
451.5 ~ 457.0 MHz (dB)	15	-	-
495.1375 ~ 565.1375 MHz (dB)	50	-	-
<b>Source impedance</b> $Z_s$ ( $\Omega$ )	-	81.5-j87	-
<b>Load impedance</b> $Z_L$ ( $\Omega$ )	-	81.5-j87	-

Note1. The standard definitions is in JIS C 6703



Note2.



### C. Frequency Characteristics :



**D.OUTLINE DRAWING:**



#2 : Input  
 #6 : Output  
 #1、3、4、5、7、8 : Ground  
 △ : Year code  
 □ : Date code  
 Unit : mm

**Product / Year Code- 4year cycle**


Year	2017 2021	2018 2022	2019 2023	2020 2024
Product Code	A	a	<u>A</u>	<u>a</u>

**Week Code Table**


WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z

### E. MEASUREMENT CIRCUIT:

HP Network analyzer




### F. PCB FOOTPRINT:




**G. PACKING:**

1. REEL DIMENSION (Please refer to FR-75D10 for packing quantity)



**2. TAPE DIMENSION**



### H. RECOMMENDED REFLOW PROFILE:

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 260°C +0/-5°C peak (20~40sec).
4. Time: 2 times.

