



**Micro Commercial Components** 

Micro Commercial Components 20736 Marilla Street Chatsworth

CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

# Features


- Halogen free available upon request by adding suffix "-HF" Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information) Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Small package saves board space
- Protects four(4) I/O lines
- Low clamping voltage
- Low capacitance: 1.5pF
- ESD protection to over 8kV contact discharge
- Can handle multiple ESD strikes

### **Maximum Ratings**

Operating Junction &StorageTemperature: -55°C to +150°C

Parameter		Symbol	Limits	unit
IEC61000-4-2(ESD)	Air		$\pm 15$	ΚV
	Contact		$\pm 8$	ΚV
IEC61000-4-4 (EFT): @ 5/50ns			40	Α
Peak Pulse Power: @ 8/20us		Ppk	350	W
Peak Pulse Current: @ 8/20us		lpp	12	Α

# **PinConfiguration**




Marking: V05

### **SRV05-4L**

## 5 Volts **ESD Protection Device**

### **SOT23-6L**



DIMENSIONS					
	INCHES		MM		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.013	.020	0.35	0.50	
В	.060	.066	1.52	1.68	
С	.106	.114	2.70	2.90	
D	.03	7	0.95B	SC	
G	.07	4	1.90B	SC	
Н	.111	.117	2.82	2.98	
J	.002	.006	0.05	0.15	
K	.035	.051	0.90	1.30	
L	.013	.021	0.35	0.55	
M	.003	.008	0.08	0.22	



#### **Micro Commercial Components**

Electrical characteristics per line@25°C(unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Тур.	Max.	Units
Reverse stand-off voltage	$V_{RWM}$				5	V
Reverse Breakdown voltage	$V_{BR}$	I <sub>t</sub> = 1mA	6			V
Reverse Leakage Current	I <sub>R</sub>	V <sub>RWM</sub> = 5V T=25°C			1	μΑ
Junction Capacitance	C <sub>j</sub>	V <sub>R</sub> =0V f = 1MHz		1.5		pF
Clamping voltage	Vc	Ipp=1A			12.5	<b>V</b>
Clamping voltage	Vc	Ipp=5A			17.5	V



#### **Micro Commercial Components**

#### **Ordering Information:**

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.