

Features

- Zener Voltages from 2.7V-39V
- Planar Die Construction
- Ideally Suited for Automated Assembly Processes
- Halogen Free. "Green" Device (Note 1)
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

200 mW Zener Diodes 2.7 to 39 Volts

Maximum Ratings

- Operating Junction Temperature Range: -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance : 625°C/W Junction to Ambient


| Parameter | Symbol | Rating | Conditions |
|-------------------------|--------|--------|----------------------|
| Power Dissipation | P_D | 200mW | Note 2 |
| Maximum Forward Voltage | V_F | 0.9V | $I_F=10mA$ Note 3 |

Note: 1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

Note: 2. Device Mounted on Ceramic PCB: 7.6mm x 9.4mm x 0.87mm With Pad Areas 25 mm²


Note:3. Tested With Pulses, $T_p < 1.0ms$

SOD-323



| DIM | INCHES | | MM | | NOTE |
|-----|--------|-------|-------|------|------|
| | MIN | MAX | MIN | MAX | |
| A | 0.090 | 0.107 | 2.30 | 2.70 | |
| B | 0.063 | 0.071 | 1.60 | 1.80 | |
| C | 0.045 | 0.053 | 1.15 | 1.35 | |
| D | 0.031 | 0.045 | 0.80 | 1.15 | |
| E | 0.010 | 0.016 | 0.25 | 0.40 | |
| G | 0.004 | 0.018 | 0.10 | 0.45 | |
| H | 0.004 | 0.010 | 0.10 | 0.25 | |
| J | ----- | 0.006 | ----- | 0.15 | |

Suggested Solder Pad Layout



Electrical Characteristics @ 25°C Unless Otherwise Specified

| MCC Part Number | Nominal Zener Voltage ^(4,5) | | Maximum Zener Impedance ⁽⁶⁾ | | | Leakage Current | | Maximum Zener Voltage Temp Coefficient 'B' Suffix Only | Marking Code |
|--------------------|--|----------|--|-------------------|----------|----------------------|-------|---|--------------|
| | $V_Z @ I_{ZT}$ | I_{ZT} | $Z_{ZT} @ I_{ZT}$ | $Z_{Zk} @ I_{Zk}$ | I_{Zk} | I_R | V_R | | |
| | V | mA | Ω | Ω | mA | $\mu A(\text{Max.})$ | V | %/°C | |
| MMXZ5223B | 2.7 | 20 | 30 | 1300 | 0.25 | 75 | 1.0 | -0.080 | C3 |
| MMXZ5225B | 3.0 | 20 | 29 | 1600 | 0.25 | 50 | 1.0 | -0.075 | C5 |
| MMXZ5226B | 3.3 | 20 | 28 | 1600 | 0.25 | 25 | 1.0 | -0.070 | G1 |
| MMXZ5227B | 3.6 | 20 | 24 | 1700 | 0.25 | 15 | 1.0 | -0.065 | G2 |
| MMXZ5228B | 3.9 | 20 | 23 | 1900 | 0.25 | 10 | 1.0 | -0.060 | G3 |
| MMXZ5229B | 4.3 | 20 | 22 | 2000 | 0.25 | 5.0 | 1.0 | ± 0.055 | G4 |
| MMXZ5230B | 4.7 | 20 | 19 | 1900 | 0.25 | 5.0 | 2.0 | ± 0.030 | G5 |
| MMXZ5231B | 5.1 | 20 | 17 | 1600 | 0.25 | 5.0 | 2.0 | ± 0.030 | E1 |
| MMXZ5232B | 5.6 | 20 | 11 | 1600 | 0.25 | 5.0 | 3.0 | +0.038 | E2 |
| MMXZ5234B | 6.2 | 20 | 7.0 | 1000 | 0.25 | 5.0 | 4.0 | +0.045 | E4 |
| MMXZ5235B | 6.8 | 20 | 5.0 | 750 | 0.25 | 3.0 | 5.0 | +0.050 | E5 |
| MMXZ5236B | 7.5 | 20 | 6.0 | 500 | 0.25 | 3.0 | 6.0 | +0.058 | F1 |
| MMXZ5237B | 8.2 | 20 | 8.0 | 500 | 0.25 | 3.0 | 6.5 | +0.062 | F2 |
| MMXZ5239B | 9.1 | 20 | 10 | 600 | 0.25 | 3.0 | 7.0 | +0.068 | F4 |
| MMXZ5240B | 10 | 20 | 17 | 600 | 0.25 | 3.0 | 8.0 | +0.075 | F5 |
| MMXZ5241B | 11 | 20 | 22 | 600 | 0.25 | 2.0 | 8.4 | +0.076 | H1 |
| MMXZ5242B | 12 | 20 | 30 | 600 | 0.25 | 1.0 | 9.1 | +0.077 | H2 |
| MMXZ5243B | 13 | 9.5 | 13 | 600 | 0.25 | 0.5 | 9.9 | +0.079 | H3 |
| MMXZ5245B | 15 | 8.5 | 16 | 600 | 0.25 | 0.1 | 11 | +0.082 | H5 |
| MMXZ5246B | 16 | 7.8 | 17 | 600 | 0.25 | 0.1 | 12 | +0.083 | J1 |
| MMXZ5248B | 18 | 7.0 | 21 | 600 | 0.25 | 0.1 | 14 | +0.085 | J3 |
| MMXZ5250B | 20 | 6.2 | 25 | 600 | 0.25 | 0.1 | 15 | +0.086 | J5 |
| MMXZ5251B | 22 | 5.6 | 29 | 600 | 0.25 | 0.1 | 17 | +0.087 | K1 |
| MMXZ5252B | 24 | 5.2 | 33 | 600 | 0.25 | 0.1 | 18 | +0.088 | K2 |
| MMXZ5254B | 27 | 4.6 | 41 | 600 | 0.25 | 0.1 | 21 | +0.090 | K4 |
| MMXZ5255B | 28 | 4.5 | 44 | 600 | 0.25 | 0.1 | 21 | +0.091 | K5 |
| MMXZ5256B | 30 | 4.2 | 49 | 600 | 0.25 | 0.1 | 23 | +0.091 | M1 |
| MMXZ5257B | 33 | 3.8 | 58 | 700 | 0.25 | 0.1 | 25 | +0.092 | M2 |
| MMXZ5258B | 36 | 3.4 | 70 | 700 | 0.25 | 0.1 | 27 | +0.093 | M3 |
| MMXZ5259B | 39 | 3.2 | 80 | 800 | 0.25 | 0.1 | 30 | +0.094 | M4 |

NOTE:

 4. Tolerance and Type Number Designation. The Type Numbers Listed Have a Standard Tolerance on The Nominal Zener Voltage of $\pm 5\%$.

 5. Zener Voltage (V_Z) Measurement. Guarantees The Zener Voltage When Measured at 90 Seconds While Maintaining The Lead Temperature (T_L) at 25°C, from The Diode Body.

 6. Zener Impedance (Z_Z) Derivation. The zener Impedance is Derived from The 60 Cycle AC Voltage, Which Results When an AC Current Having an rms Value Equal to 10% of the DC Zener Current (I_{ZT} or I_{Zk}) is Superimposed on I_{ZT} or I_{Zk} .

Curve Characteristics

Fig. 1 - Power Derating Curve




Fig. 2 - Typical Zener Breakdown Characteristics





Fig. 3 - Typical Zener Breakdown Characteristics



Ordering Information

| Device | Packing |
|----------------|----------------------|
| Part Number-TP | Tape&Reel:3Kpcs/Reel |

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.