SMD Power Inductor

HPC5040NF-Series


| | ECN HISTORY LIST | | | | | |
|-----|------------------|-------------|----------|---------|-------|--|
| REV | DATE | DESCRIPTION | APPROVED | CHECKED | DRAWN | |
| 1.0 | 16/03/25 | 新發行 | 楊祥忠 | 詹偉特 | 何秦芝 | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| 備 | | | | | | |
| 注 | | | | | | |


SMD Power Inductor

1. Features

- 1. This specification applies Low Profile Power Inductors.
- 2. 100% Lead(Pb) & Halogen-Free and RoHS compliant.


2. Dimension





Halogen-free Pb-free

Recommended Land pattern




| HPC5040NF ≤10 uH >10 uH >10 uH 4.95±0.2 4.95±0.2 3.9±0.2 1.3±0.3 4.2±0.2 3.7ref | Series | Inductance | A(mm) | B(mm) | C(mm) | D(mm) | E (mm) | F(mm) | |
|--|------------|------------|----------------|----------|---------|---------|---------|--------|--|
| | | ≪10 uH | 4 05 ± 0.2 | 4.95±0.2 | 3.9±0.2 | 1.3±0.3 | 4.2±0.2 | 3.7ref | |
| | HPC5040INF | >10 uH | 4.95 ± 0.2 | | 3.8±0.2 | | | | |

| G(mm) | H(mm) | l(mm) | | | |
|-------------------------------|-------|-------|--|--|--|
| 2.1 4.2 1.5 | | | | | |
| Note · Recommend solder naste | | | | | |

thickness at 0.12mm and above

3. Part Numbering



P2

HPC5040NF-Series

4. Specification

| | | | | | Rated | | | |
|---------------|-------------------------------|------|-------|------|-------------|----------------------|---------------------------|---------|
| Part Number | Inductance Tolerar L0 (uH) | | rance | | Temperature | Saturation | DCR (mΩ) @25℃ ±20%. | |
| | @ 0 A | к | L | м | Y | current I rms (A) | current I sat (A) | ± 20 %. |
| HPC5040NF-1R0 | 1.00 | 1 | 1 | ±20% | ±30% | 5.00 | 7.50 | 12 |
| HPC5040NF-1R5 | 1.50 | 1 | 1 | ±20% | ±30% | 4.50 | 6.50 | 15 |
| HPC5040NF-2R2 | 2.20 | 1 | 1 | ±20% | ±30% | 3.80 | 5.70 | 21 |
| HPC5040NF-3R3 | 3.30 | 1 | 1 | ±20% | ±30% | 3.50 | 4.40 | 24 |
| HPC5040NF-4R7 | 4.70 | 1 | 1 | ±20% | ±30% | 3.20 | 3.90 | 32 |
| HPC5040NF-6R8 | 6.80 | 1 | 1 | ±20% | ±30% | 2.50 | 3.30 | 43 |
| HPC5040NF-100 | 10.0 | 1 | 1 | ±20% | ±30% | 2.20 | 2.52 | 56 |
| HPC5040NF-150 | 15.0 | 1 | ±15% | ±20% | ±30% | 1.80 | 2.00 | 80 |
| HPC5040NF-220 | 22.0 | 1 | ±15% | ±20% | ±30% | 1.50 | 1.62 | 123 |
| HPC5040NF-330 | 33.0 | 1 | ±15% | ±20% | ±30% | 1.20 | 1.30 | 180 |
| HPC5040NF-470 | 47.0 | ±10% | ±15% | ±20% | ±30% | 1.00 | 1.10 | 270 |
| HPC5040NF-680 | 68.0 | ±10% | ±15% | ±20% | ±30% | 0.80 | 0.90 | 400 |
| HPC5040NF-101 | 100 | ±10% | ±15% | ±20% | ±30% | 0.72 | 0.75 | 560 |

Note:

1. All test data referenced to 25°C ambient , Ls:100KHz/1V.

2. Testing Instrument : HP4284A,CH11025,CH3302,CH1320 ,CH1320S LCR METER / Rdc:CH502BC MICRO OHMMETER.


3. Heat Rated Current (Irms) will cause the coil temperature rise approximately Δt of 40°C (keep 1min.).

4. Saturation Current (Isat) will cause L0 $\,$ to drop $\,$ 30% typical. (keep quickly).

5. The part temperature (ambient + temp rise) should not exceed 125°C under worst case operating conditions. Circuit design, component, PCB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.

6. Special inquiries besides the above common used types can be met on your requirement.

5. Material List



| NO | Items | Materials |
|----|-------------|---------------------|
| а | Core | Ferrite Core |
| b | Wire | Copper Wire |
| С | Glue | Magnetic Resin |
| d | Solder | Lead free-Sn Cu |
| е | Adhesive | Ероху |
| f | Copper foil | Pure Copper |
| g | ink | Halogen-free ketone |

6. Reliability and Test Condition

| ltem | Performance | Test Condition |
|---------------------------|--|---|
| Operating temperature | -40~+125°C (Including self - temperature rise) | |
| Storage temperature | 110~+40℃ ,50~60%RH (Product without taping) 240~+125℃ (on board) | |
| Electrical Performance T | est | |
| Inductance | | HP4284A,CH11025,CH3302,CH1320,CH1320S LCR Meter. |
| DCR | Refer to standard electrical characteristics list. | CH16502,Agilent33420A Micro-Ohm Meter. |
| Saturation Current (Isat) | ∆L30% typical. | Saturation DC Current (Isat) will cause L0 to drop $\triangle L(\%)$ (keep quickly). |
| Heat Rated Current (Irms) | Approximately △T40℃ | Heat Rated Current (Irms) will cause the coil temperature rise △T(℃) without core loss. 1.Applied the allowed DC current(keep 1 min.). 2.Temperature measured by digital surface thermometer |
| Reliability Test | | |
| Life Test | | Preconditioning: Run through IR reflow for 2 times.(IPC/JEDEC J-STD-020DClassification Reflow Profiles) Temperature : 125±2°C(Inductor) Applied current : rated current Duration : 1000±12hrs Measured at room temperature after placing for 24±2 hrs |
| Load Humidity | | Preconditioning: Run through IR reflow for 2 times.(IPC/JEDEC J-STD-020DClassification Reflow Profiles Humidity: 85±2% R.H, Temperature: 85°C±2°C Duration: 1000hrs Min. with 100% rated current |
| Moisture Resistance | Appearance : No damage. Inductance : within±10% of initial value Q : Shall not exceed the specification value. RDC : within ±15% of initial value and shall not exceed the specification value | Measured at room temperature after placing for 24±2 hrs Preconditioning: Run through IR reflow for 2 times. (IPC/JEDEC J-STD-020DClassification Reflow Profiles 1. Baked at50°C for 25hrs, measured at room temperature after placing for 4 hrs. 2. Raise temperature to 65±2°C 90-100%RH in 2.5hrs, and keep 3 hours, cool down to 25°C in 2.5hrs. 3. Raise temperature to 65±2°C 90-100%RH in 2.5hrs, and keep 3 hours, cool down to 25°C in 2.5hrs. 3. Raise temperature to 65±2°C 90-100%RH in 2.5hrs, and keep 3 hours, cool down to 25°C in 2.5hrs, keep at 25°C 60-100%RH for 15min and vibrate at the frequency of 10 to 55 Hz to 10 Hz, measure at room temperature after placing for 1~2 hrs. |
| Thermal shock | | Preconditioning: Run through IR reflow for 2 times.(IPC/JEDEC J-STD-020DClassification Reflow Profiles Condition for 1 cycle Step1 : -40±2℃ 30±5min Step2 : 25±2℃ ≤0.5min Step3 : 125±2℃ 30±5min Number of cycles : 500 Measured at room temperature after placing for 24±2 hrs |
| Vibration | | Oscillation Frequency: 10 ~ 2K ~ 10Hz for 20 minutes Equipment : Vibration checker Total Amplitude:1.52mm±10% Testing Time : 12 hours(20 minutes, 12 cycles each of 3 orientations)。 |

TAI-TECH

| Item | Performance | | | Test Cor | dition | |
|------------------------------------|--|---|--|--------------------------------------|---|----------------------------------|
| Shock | Appearance : No damage. | Тур | Peak e value (g's) | Normal duration (D) (ms) | Wave form | Velocity change (Vi)ft/sec |
| | Inductance : within±10% of initial value | SM | D 1500 | 0.5 | Half-sine | 15.4 |
| | Q : Shall not exceed the specification value. RDC : within ±15% of initial value and shall not | Lea | d 100 | 6 | Half-sine | 12.3 |
| Bending | exceed the specification value | Shall be mounted on a FR4 substrate of the following dimensions: >=0805:40x100x1.2mm <0805:40x100x0.8mm Bending depth: >=0805:1.2mm <0805:0.8mm duration of 10 sec. | | | | |
| Solderability | More than 95% of the terminal electrode should be covered with solder。 | Solo Terr Flux Dip | perature: 245 for lead free: ime: 4±1sec | Ag3% Cu0.5% 5±5℃。 Rosin. 9.5%。 | | |
| Resistance to Soldering Heat | | (| emperature °C) °C) emp) | Time(s) | Temperature ramp/immers and emersion 25mm/s ±6 n | ion n rate |
| Terminal Strength | Appearance : No damage. Inductance : within±10% of initial value Q : Shall not exceed the specification value. RDC : within ±15% of initial value and shall not exceed the specification value | Preconditioning: Run through IR reflow for times.(IPC/JEDEC J-STD-020DClassification Reflow Profiles With the component mounted on a PCB with the device t be tested, apply a force (>0805:1kg, <=0805:0.5kg)to the side of a device bein tested. This force shall be applied for 60 +1 seconds. Also the force shall be applie gradually as not to apply a shock to the component being tested. | | | | |
| | | | substrate | | press tool | thick |

Note : When there are questions concerning measurement result : measurement shall be made after 48 ± 2 hours of recovery under the standard condition.

7. Soldering and Mounting

(1) Soldering

Mildly activated rosin fluxes are preferred. The minimum amount of solder can lead to damage from the stresses caused by the difference in coefficients of expansion between solder, chip and substrate. TAI-TECH terminations are suitable for re-flow soldering systems. If hand soldering cannot be avoided, the preferred technique is the utilization of hot air soldering tools.

(2) Solder re-flow:


Recommended temperature profiles for re-flow soldering in Figure 1.

(3) Soldering Iron:

Products attachment with a soldering iron is discouraged due to the inherent process control limitations. In the event that a soldering iron must be employed the following precautions are recommended.


- \cdot Preheat circuit and products to 150 $^\circ\!\!\!\!\!^\circ$ \cdot Never contact the ceramic with the iron tip
- 355°C tip temperature (max) 1.0mm tip diameter (max)
 - ax)

Use a 20 watt soldering iron with tip diameter of 1.0mm
Limit soldering time to 4~5sec.




8. Packaging Information


(1) Reel Dimension



| Туре | A(mm) | B(mm) | C(mm) | D(mm) |
|----------|-----------|--------|----------|---------|
| 13"x12mm | 12.4+2/-0 | 80±2.0 | 13.5±0.5 | 330±3.0 |

(2) Tape Dimension






| Series | Size | Bo(mm) | Ao(mm) | Ko(mm) | P(mm) | w(mm) | t(mm) | E(mm) | F(mm) | D(mm) | Po(mm) | P2(mm) |
|--------|------|---------|---------|---------|---------|--------|---------|----------|---------|---------|---------|----------|
| HPC | 5040 | 5.4±0.1 | 5.4±0.1 | 4.3±0.1 | 8.0±0.1 | 12±0.3 | 0.4±0.1 | 1.75±0.1 | 7.5±0.1 | 1.5±0.1 | 4.0±0.1 | 2.00±0.1 |

(3) Packaging Quantity

| HPC | 5040 |
|-----------|-------|
| Reel | 1500 |
| Inner box | 3000 |
| Carton | 12000 |

(4) Tearing Off Force




The force for tearing off cover tape is 10 to 130 grams in the arrow direction under the following conditions (referenced ANSI/EIA-481-C-2003 of 4.11 standards).

| Room Temp. | Room Humidity | Room atm | Tearing Speed |
|------------|---------------|----------|---------------|
| (℃) | (%) | (hPa) | mm/min |
| 5~35 | 45~85 | 860~1060 | |

Application Notice


- Storage Conditions(component level) To maintain the solderability of terminal electrodes:
 1. TAI-TECH products meet IPC/JEDEC J-STD-020D standard-MSL, level 1.
- 2. Temperature and humidity conditions: Less than 40 $^\circ\!\mathrm{C}$ $\,$ and 60% RH.
- 3. Recommended products should be used within 12 months form the time of delivery.
- 4. The packaging material should be kept where no chlorine or sulfur exists in the air.
- Transportation
- 1. Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- 2. The use of tweezers or vacuum pick up is strongly recommended for individual components.
- 3. Bulk handling should ensure that abrasion and mechanical shock are minimized.

9. Typical Performance Curves



Core chipping


The appearance standard of the chipping size on top side, and bottom side ferrite core is listed below.



| L | w |
|------------|------------|
| 0.8mm Max. | 0.8mm Max. |

Void appearance tolerance Limit

Size of voids occurring to coating resin is specified below.




Exposed wire tolerance limit of coating resin part on product side. Size of exposed wire occurring to coating resin is specified below. 1. Width direction (dimension a): Acceptable when $a \leq w/2$.

- 1. With direction (dimension a). Acceptable when $a \ge w_A$
- Length direction (dimension b): Dimension b is not specified.
 The total area of exposed wire occurring to each sides is
 - not greater than 50% of coating resin area, and is acceptable.

External appearance criterion for exposed wire


Exposed end of the winding wire at the secondary side should be 3mm and below.



0.8mm Max

0.8mm Max

Electrode appearance criterion for exposed wire



Foreign materials (dirt) will not affect the coplanarity of PAD, below the example of foreign materials (dirt) quantity ≤2PCS on single PAD. dimension range as below.





測試報告 號碼(No.) : CE/2015/B1564 日期(Date) : 2015/11/16 頁數(Page): 1 of 15 **Test Report** 西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD. (臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.) (耀鑽科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.) (慶邦電子元器件(泗洪)有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.) 桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中壢區中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省電市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU) 以下测試樣品係由申請廠商所提供及確認 (The following sample(s) was/were submitted and identified by/on behalf of the applicant as): SMD POWER INDUCTOR 樣品名稱(Sample Description) HPC(YHC 、 DR) 、 MDC 、 FPC(YPC) 、 FWP(YWP) 、 SPC 、 AHP 、 UHP 、 DFP 、 DHP 、 TLPC 、 樣品型號(Style/Item No.) : TLPH . TLI SERIES -收件日期(Sample Receiving Date) 2015/11/10 • 測試期間(Testing Period) 2015/11/10 TO 2015/11/16

测试结果(Test Results) :

請見下一頁 (Please refer to next pages).

Trov Chang/Manage Signed for and on Dehalf o SGS TAIWAN LTD. Chemical Laboratory - Taipei

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.asp. and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.asp. drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereion reflects the Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, foregory or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.



測試報告 Test Report ^{號碼(No}

號碼(No.): CE/2015/B1564

日期(Date): 2015/11/16

頁數(Page): 2 of 15

西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD.

NICS CO., LTD.

(臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.) (耀鑽科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.) (慶邦電子元器件 (泗洪) 有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.) 桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中壢區中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿還市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)

测试结果(Test Results)

测试部位(PART NAME)No.1 : 整體混測(MIXED ALL PARTS)

| 测試項目 (Test Items) | 單位 (Unit) | 测試方法 (Method) | 方法偵測 極限値 (MDL) | 結果 (Result) No.1 |
|--|--------------|--|----------------------|------------------------|
| 鎘 / Cadmium (Cd) | mg/kg | 参考IEC 62321-5: 2013方法, 以感應耦合 電漿原子發射光譜儀檢測. / With reference to IEC 62321-5: 2013 and performed by ICP-AES. | 2 | n. d. |
| 鉛 / Lead (Pb) | mg/kg | 参考IEC 62321-5: 2013方法,以感應耦合 電漿原子發射光譜儀檢測. / ₩ith reference to IEC 62321-5: 2013 and performed by ICP-AES. | 2 | n. d. |
| 汞 / Mercury (Hg) | mg/kg | 參考IEC 62321-4: 2013方法, 以感應耦合 電漿原子發射光譜儀檢測. / With reference to IEC 62321-4: 2013 and performed by ICP-AES. | 2 | n. d. |
| 六價鉻 / Hexavalent Chromium Cr(VI) | mg/kg | 参考IEC 62321: 2008方法,以UV-VIS檢测. / With reference to IEC 62321: 2008 and performed by UV-VIS. | 2 | n. d. |
| 六溴環十二烷及所有主要被辨別出的異構 物 / Hexabromocyclododecane (HBCDD) and all major diastereoisomers identified (α - HBCDD, β - HBCDD, γ - HBCDD) (CAS No.: 25637-99-4 and 3194-55-6 (134237-51-7, 134237-50-6, 134237-52-8)) | mg/kg | 参考IEC 62321: 2008方法, 以氣相層析/質 譜儀檢測. / With reference to IEC 62321: 2008 method. Analysis was performed by GC/MS. | 5 | n. d. |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ega.com/en/Terms-and-Conditions appx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.ega.com/en/Terms-and-Conditions drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

SGS Taivvan Ltd. 台湾検验科技股份有限公司 🕴 25, Wu Chyuan 7th Road, New Taipei Industrial Park, Wu Ku District, New Taipei City, Taiwan 麻北市和聖新北產業園區五權七路25號



测試報告 號碼(No.): CE/2015/B1564 **Test Report**

西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD.

(臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.)

(耀鑽科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.)

(慶邦電子元器件(泗洪)有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.)

桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD,KUNJIA HI-TECH INDUSTRIAL PARK,KUN-SHAN,JIANG-SU,CHINA) (桃園市中壢區中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿邊市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)

日期(Date): 2015/11/16

| 測試項目 (Test Items) | 單位 (Unit) | 测試方法 (Method) | 方法偵測 極限値 (MDL) | 結果 (Result) No.1 |
|----------------------------------|--------------|---|----------------------|------------------------|
| 聚氯乙烯 / PVC | ** | 以紅外光譜分析及焰色法檢測. / Analysis was performed by FTIR and FLAME Test. | | Negative |
| 多溴聯苯總和 / Sum of PBBs | mg/kg | | - | n.d. |
| 一溴聯苯 / Monobromobiphenyl | mg/kg | · · · | 5 | n.d. |
| 二溴聯苯 / Dibromobiphenyl | mg/kg | | 5 | n.d. |
| 三溴聯苯 / Tribromobiphenyl | mg/kg | | 5 | n. d. |
| 四溴聯苯 / Tetrabromobiphenyl | mg/kg | | 5 | • n.d. |
| 五溴聯苯 / Pentabromobiphenyl | mg/kg | | 5 | n. d. |
| 六溴聯苯 / Hexabromobiphenyl | mg/kg | | 5 | n. d. |
| 七溴聯苯 / Heptabromobiphenyl | mg/kg | | 5 | n. d. |
| 八溴聯苯 / Octabromobiphenyl | mg/kg | | 5 | n. d. |
| 九溴聯苯 / Nonabromobiphenyl | mg/kg | | 5 | n. d. |
| 十溴聯苯 / Decabromobiphenyl | mg/kg | 参考IEC 62321-6: 2015方法,以氣相層析/ 質譜儀檢測. / With reference to IEC | 5 | n. d. |
| 多溴聯苯醚總和 / Sum of PBDEs | mg/kg | 資替稅檢測,/ With reference to Inc. 62321-6: 2015 and performed by GC/MS. | | n. d. |
| 一溴聯苯醚 / Monobromodiphenyl ether | mg/kg | | 5 | n.d. |
| 二溴聯苯醚 / Dibromodiphenyl ether | mg/kg | | 5 | n.d. |
| 三溴聯苯醚 / Tribromodiphenyl ether | mg/kg | | 5 | n. d. |
| 四溴聯苯醚 / Tetrabromodiphenyl ether | mg/kg | | 5 | n. d. |
| 五溴聯苯醚 / Pentabromodiphenyl ether | mg/kg | | 5 | n. d. |
| 六溴聯苯醚 / Hexabromodiphenyl ether | mg/kg | | 5 | n. d. |
| 七溴聯苯醚 / Heptabromodiphenyl ether | mg/kg | | 5 | n. d. |
| 八溴聯苯醚 / Octabromodiphenyl ether | mg/kg | | 5 | n, d. |
| 九溴聯苯醚 / Nonabromodiphenyl ether | ng/kg | | 5 | n. d. |
| 十溴聯苯醚 / Decabromodiphenyl ether | mg/kg | · · · · · · · · · · · · · · · · · · · | 5 | n.d. |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions aspx drewn to the limitation of liability, indemnification and jurisdiction issues defined there of this document is advised that information contained here on reflects the Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is advised, scrept in full, without pilor written approval of the Company's company, any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extern of the sample(s) tested.

SGS Taiwan Ltd. 台灣換验科技股份有限公司 125, Wu Chyuan 7th Road, New Taipei Industrial Park, Wu Ku District, New Taipei City, Taiwan 新北市五股區新北產業團區五級七路25號

頁數(Page): 3 of 15



測試報告 Test Report ^{號碼(No.)}:

號碼(No.): CE/2015/B1564 - 6

日期(Date): 2015/11/16

頁數(Page): 4 of 15

西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD.

(臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.)

(耀鑽科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.)

(慶邦電子元器件(泗洪)有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.)

桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中壢區中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿遷市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)

| 測試項目 (Test Itens) | 單位 (Unit) | 測試方法 (Method) | 方法偵測 極限值 (MDL) | 結果 (Result) No.1 |
|--|--------------|---|----------------------|------------------------|
| 绨 / Antimony (Sb) | mg/kg | 参考US EPA 3052方法,以感應耦合電浆原 子發射光譜儀檢測. / With reference to US EPA Method 3052. Analysis was performed by ICP-AES. | 2 | n. d. |
| 鈹 / Beryllium (Be) | mg/kg | 参考US EPA 3052方法,以感應耦合電漿原 子發射光譜儀檢測. / With reference to US EPA Method 3052. Analysis was performed by ICP-AES. | 2 | n. d. |
| 全氣辛烷磺酸 / Perfluorooctane sulfonates (PFOS-Acid, Metal Salt, Amide) | mg/kg | 參考US EPA 3550C: 2007方法, 以液相層析 /質譜儀檢測. / With reference to US EPA 3550C: 2007. Analysis was performed by LC/MS. | 10 | n. d. |
| 全氟辛酸 / PFOA (CAS No.: 335-67-1) | mg/kg | 参考US EPA 3550C: 2007方法, 以液相層析 /質譜儀檢測. / With reference to US EPA 3550C: 2007. Analysis was performed by LC/MS. | 10 | n. d. |
| 鹵素 / Halogen | | | *** | |
| 鹵素 (氟) / Halogen-Fluorine (F) (CAS No.: 14762-94-8) | mg/kg | | 50 | n.d. |
| 鹵素(氣) / Halogen-Chlorine(C1) (CAS No.: 22537-15-1) | mg/kg | 参考BS EN 14582:2007,以離子層析儀分 析. / With reference to BS EN | 50 | n. d. |
| 鹵素 (溴) / Halogen-Bromine (Br) (CAS No.: 10097-32-2) | mg/kg | 14582:2007. Analysis was performed by IC. | 50 | n. d. |
| 鹵素 (碘) / Halogen-Iodine (I) (CAS No.: 14362-44-8) | mg/kg | · · · · · · · · · · · · · · · · · · · | 50 | n. d. |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sga.com/en/Terms-and-Conditions.sga and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sga.com/en/Terms-and-Conditions drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereinon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the sample(s) tested. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

SGS Taivvari Ltd. 台湾 徐駿井技殿 份有限公司 125, Wu Chyuan 7th Road, New Taipei Industrial Park, Wu Ku District, New Taipei City, Taiwan 衛北市正殿區新北產樂園區五優七路25號



測試報告 Test Report^號

號碼(No.): CE/2015/B1564

日期(Date): 2015/11/16

西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD.

(臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.)

(耀鑽科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.)

(慶邦電子元器件(泗洪)有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.)

桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中壢區中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿邊市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)

| 測試項目 (Test Items) | 單位 (Unit) | 測試方法 (Method) | 方法偵測 極限值 (MDL) | 結果 (Result) No.1 |
|--|--------------|---|----------------------|------------------------|
| 鄰苯二甲酸丁苯甲酯 / BBP (Butyl Benzyl phthalate) (CAS No.: 85-68-7) | mg/kg | | 50 | n. d. |
| 鄰苯二甲酸二丁酯 / DBP (Dibutyl phthalate) (CAS No.: 84-74-2) | mg/kg | | 50 | n. d. |
| 鄰苯二甲酸二(2-乙基己基)酯 / DEHP (Di- (2-ethylhexyl) phthalate) (CAS No.: 117-81-7) | mg/kg | | 50 | n. d. |
| 鄰苯二甲酸二異丁酯 / DIBP (Di- isobutyl phthalate) (CAS No.: 84-69- 5) | mg/kg | 參考IEC 62321-8 (111/321/CD),以氣相層 析儀/質譜儀檢測之. / With reference to | 50 | n.d. |
| 鄰苯二甲酸二異癸酯 / DIDP (Di- isodecyl phthalate) (CAS No.: 26761- 40-0; 68515-49-1) | mg/kg | IEC 62321-8 (111/321/CD). Analysis was performed by GC/MS. | 50 | n. d. |
| 鄰苯二甲酸二異壬酯 / DINP (Di- isononyl phthalate) (CAS No.: 28553- 12-0; 68515-48-0) | mg/kg | | 50 | n, d, |
| 鄰苯二甲酸二正辛酯 / DNOP (Di-n- octyl phthalate) (CAS No.: 117-84-0) | mg/kg | | 50 | n. d. |
| 鄰苯二甲酸二正己酯 / DNHP (Di-n- hexyl phthalate) (CAS No.: 84-75-3) | mg/kg | | 50 | n. d. |

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions sept and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/

SGS Taiwan Ltd. 台灣檢验科技股份有限公司 | 25, Wu Chyuan 7th Road, New Taipei Industrial Park, Wu Ku District, New Taipei City, Taiwan 新北市五般區新北產樂園医五撮七路25號

Member of the SGS Group

號碼(No.); CE/2015/B1564

日期(Date): 2015/11/16

頁數(Page): 6 of 15

西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD.

(臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.)

(耀鐟科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.)

(慶邦電子元器件(泗洪)有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.)

桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中壢區中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿還市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)

備註(Note):

- 1. mg/kg = ppm; 0.1wt% = 1000ppm
- 2. n.d. = Not Detected (未檢出)
- 3. MDL = Method Detection Limit (方法偵測極限值)
- 4. "-" = Not Regulated (無規格值)
- 5. **= Qualitative analysis (No Unit) 定性分析(無單位)
- 6. Negative = Undetectable 陰性(未偵測到); Positive = Detectable 陽性(已偵測到)
- 7. 樣品的測試是基於申請人要求混合測試,報告中的混合測試結果不代表其中個別單一材質的含量. (The samples was/were analyzed on behalf of the applicant as mixing sample in one testing. The above results was/were only given as the informality value.)

PFOS參考資訊(Reference Information): 持久性有機污染物 POPs - (EU) 757/2010

PFOS濃度在物質或製備中不得超過0.001%(10ppm),在半成品、成品或零部件中不得超過0.1%(1000ppm),在紡織品或塗 層材料中不得超過1µg/m²。

(Outlawing PFOS as substances or preparations in concentrations above 0.001% (10ppm), in semi-finished products or articles or parts at a level above 0.1%(1000ppm), in textiles or other coated materials above lug/m^2 .)

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Temis-and-Con This document is issued by the Company subject to its General Conditions of Service printed overlear, avaliable on request on accessible at <u>Intro Avavor spectra and the service service</u> and, for electronic format documents, subject to terms and Conditions for Electronic Documents at <u>Intro Avavor sector</u> and <u>Conditions</u>. The Company subject to the service at <u>Intro Avavor sector</u> and <u>Conditions</u> and <u>Conditions</u> for Electronic Documents at <u>Intro Avavor sector</u> and <u>Conditions</u> and <u>Conditio</u> int or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law

號碼(No.): CE/2015/B1564


日期(Date) : 2015/11/16

頁數(Page): 7 of 15

西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD. (臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (RUN-SHAN) CO. LTD.) (耀鑽科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.) (慶邦電子元器件(泗洪)有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.) 桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中壢區中壢工業區長春六路15號 / NO. 15、CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿遷市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)

1) 根據以下的流程圖之條件,樣品已完全溶解。(六價鋒測試方法除外) / These samples were dissolved totally by pre-conditioning method according to below flow chart. (Cr6+ test method excluded) 2)

- 测试人員:楊登偉 / Name of the person who made measurement: Climbgreat Yang
- 测試負責人:張啟興 / Name of the person in charge of measurement: Troy Chang 3)



Note** (For IEC 62321)

- (1) 針對非金屬材料加入鹼性消化液,加熱至 90~95℃萃取. / For non-metallic material, add alkaline digestion reagent and heat to 90~95°C.
- (2) 針對金屬材料加入純水,加熱至沸腾萃取. / For metallic material, add pure water and heat to boiling.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sga.com/en/Terms-and-Conditions appx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sga.com/en/Terms-and-Conditions appx drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law, Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司 125.Wu Chyuan 7th Road, New Taipei Industrial Park, Wu Ku District, New Taipei City, Taiwan 廣北市近照區新北產業網區五撮七路25號

號碼(No.) : CE/2015/B1564

日期(Date) : 2015/11/16

頁數(Page): 8 of 15

西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD.


(臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.) (耀鑽科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.) (慶邦電子元器件 (泗洪) 有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.) 桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C.

(江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中壢區中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿遷市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)

全氟辛酸/全氟辛烷磺酸分析流程圖 / PFOA/PFOS analytical flow chart

■ 测試人員:翁賜彬 / Name of the person who made measurement: Roman Wong

■ 測試負責人:張啟興 / Name of the person in charge of measurement: Troy Chang



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.aga.com/en/Terms-and-Conditions app. and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.aga.com/en/Terms-and-Conditions.app. drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not excende a private to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

SGS Taiwan Ltd. 台灣 檢驗科 技殿份有限公司 🕴 55, Wu Chyuan 7th Road, New Taipei Industrial Park, Wu Ku District, New Taipei City, Taiwan 顧北市五戰區新北產型欄區五權七路25號

測試報告 ^{號碼(No.)}: CE/2015/B1564 日期(Date): 2015/11/16 **Test Report**

頁數(Page): 9 of 15

西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD.

(臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.)

(耀鑽科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.)

(慶邦電子元器件 (泗洪) 有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.)

桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中堀區中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿還市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)

- 根據以下的流程圖之條件,樣品已完全溶解。 / These samples were dissolved totally by pre-conditioning method according to below flow chart.
- 测試入員:楊登偉 / Name of the person who made measurement: Climbgreat Yang
- 测試負責人:張啟興 / Name of the person in charge of measurement: Troy Chang

元素以 ICP-AES 分析的消化流程圖 (Flow Chart of digestion for the elements analysis performed by ICP-AES) 剪裁、製備樣品 / Cutting、Preparation T 測試樣品重量 / Sample Measurement 依據不同樣品的材質而以適當的酸進行消化(如下表所示)/Acid digestion by suitable acid depended on different sample material (as below table) 過濾 / Filtration T 殘渣 / Residue 溶液 / Solution 1) 鹼熔融法 / Alkali Fusion 2) 鹽酸溶解 / HCI to dissolve 感應耦合電漿原子發射光譜儀 / ICP-AES 王水,硝酸,鹽酸,氫氟酸,雙氧水 / 鋼,銅,鋁,焊錫 / Steel, copper, aluminum, solder Aqua regia, HNO₃, HCl, HF, H₂O₂ 硝酸,氫氟酸 / HNO₃/HF 玻璃 / Glass 金,鉑,鉅,陶瓷 / Gold, platinum, palladium, ceramic 王水 / Aqua regia 硝酸 / HNO3 銀 / Silver 硫酸,雙氧水,硝酸,鹽酸 / H2SO4, H2O2, HNO3, HCI 塑膠 / Plastic 加入適當的試劑至完全溶解 / Added appropriate 其他 / Others reagent to total digestion

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.ega.com/en/Terms-and-Conditions.sepx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.ega.com/en/Terms-and-Conditions sepx drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information entered the Company's indings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their nghts and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forger or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fulles: when of the leaves of the subject is the results shown in this test report refer only to the sample(s) tested.

SGS Taiwan Lid. 台湾 读验科技服台有限公司 15, Wu Chyuan 7th Road, New Taipei Industrial Park, Wu Ku District, New Taipei City, Taiwan 前北市五股區新北產業園區五檔七路25號

測試報告 Test Report 號碼(No.): CE/2015/B1564

西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD.

(臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.) (耀鎖科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.) (慶邦電子元器件 (泗洪) 有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.) 桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中壢區中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿遷市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)


日期(Date): 2015/11/16

聚氯乙烯物質判定分析流程圖 1

Analysis flow chart for determination of PVC in material

■ 測試人員:林建宇 / Name of the person who made measurement: Roy Lin

■ 测试負責人:張啟興 / Name of the person in charge of measurement: Troy Chang



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions apx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-

SGS Taiwan Ltd, 台灣校验科技戰份有限公司

頁數(Page): 10 of 15



號碼(No.): CE/2015/B1564


日期(Date) : 2015/11/16

西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD. (臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.) (耀鑽科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.) (慶邦電子元器件 (泗洪) 有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.) 桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中壢區 中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿還市泗洪縣經濟開發區金沙南路-高新技術產業園 / HICH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)

鹵素分析流程圖 / Analytical flow chart of halogen content

■ 測試人員:陳恩臻 / Name of the person who made measurement: Rita Chen

■ 測試負責人:張啟興 / Name of the person in charge of measurement: Troy Chang



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sg.com/en/Terms-and-Conditions aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www ags.com/en/Terms-and-Conditions/Terms-and-Conditi

SGS Taiwan Ltd. 台湾徐瑜科技股份有限公司 <u>25, Wu Chyuan 7th Road, New Taipei Industrial Park, Wu Ku District, New Taipei City, Taiwan 新北市五股區新北產業園區工程上路25號 + 886 10212299 3939 1+886 10212299 3939 1+886 10212299 3237 www.sgs.tw</u>



號碼(No.): CE/2015/B1564

日期(Date): 2015/11/16

頁數(Page): 12 of 15


西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD.

(臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.) (耀鑽科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.) (慶邦電子元器件 (泗洪) 有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.) 桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中壢區中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿還市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)

六溴環十二烷分析流程圖 / HBCDD analytical flow chart

■ 測試人員:翁賜彬 / Name of the person who made measurement: Roman Wong

■ 測試負責人:張啟興 / Name of the person in charge of measurement: Troy Chang



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-Document.aspx, Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's propeny's soliton is to estimate the indication from exercising all their rights and obligations under the transaction document to reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or italification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

SGS Taiwan Ltd. 台湾 檢驗科技股份有账公司 25, Wu Chyuan 7th Road, New Taipei Industrial Park, Wu Ku District, New Taipei City, Taiwan /新北市近股區新北產業園區五種七路25號

號碼(No.): CE/2015/B1564

日期(Date): 2015/11/16

頁數(Page): 13 of 15

西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD. (臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.) (耀鎖科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.)

(慶邦電子元器件 (泗洪) 有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.)


桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中壢區中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿遷市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)

可塑劑分析流程圖 / Analytical flow chart of phthalate content

■ 测試人員:徐毓明 / Name of the person who made measurement: Andy Shu

■ 測試負責人:張啟興 / Name of the person in charge of measurement: Troy Chang

【测試方法/Test method: IEC 62321-8】



This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/on/Terms-and-Conditions.sepw and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/on/Terms-and-Conditions.sepw drawn to the limitation of lability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parities to a transaction from exercising all their rights and obligations under the transaction document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or fastilication of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

SGS Taiwyan Ltd. 台湾 検強料技度份有 11公司 25, Wu Chyuan 7th Road, New Taipei Industrial Park, Wu Ku District, New Taipei City, Taiwan 新北市五股區新北產業園區近羅七路25號



測試報告 Test Report ^{號碼(No.)}: CE/2015/B1564

西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD.

頁數(Page): 14 of 15

(臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.)

(耀鑽科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.)

(慶邦電子元器件(泗洪)有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.)

桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中壢區中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿還市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)


日期(Date): 2015/11/16


多溴聯苯/多溴聯苯醚分析流程圖 / PBB/PBDE analytical FLOW CHART

■ 測試人員:翁賜彬 / Name of the person who made measurement: Roman Wong

■ 測試負責人:張啟興 / Name of the person in charge of measurement: Troy Chang

初次测试程序 / First testing process →→ 選擇性篩檢程序 / Optional screen process =======





This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/art/Terms-and-Conditions aspx. and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/art/Terms-and-Conditions/Terms-Bocument.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document document as advised there in the first order at a http://www.sgs.com/art/Terms-and-Conditions/ and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

SGS Taiwan Ltd. 台灣檢驗科技股份有账公司 125, Wu Chyuan 7th Road, New Taipei Industrial Park, Wu Ku District, New Taipei City, Taiwan /新北市五聚區新北產業園區五曜上路25號



測試報告

號碼(No.): CE/2015/B1564

日期(Date): 2015/11/16

頁數(Page): 15 of 15

Test Report

西北臺慶科技股份有限公司 / TAI-TECH ADVANCED ELECTRONICS CO., LTD.

(臺慶精密電子(昆山)有限公司 / TAI-TECH ADVANCED ELECTRONICS (KUN-SHAN) CO. LTD.)


(耀鑚科技股份有限公司 / YOSONIC TECHNOLOGY CO., LTD.)

(慶邦電子元器件 (泗洪) 有限公司 / TAIPAQ ELECTRONICS (SI-HONG) CO., LTD.)


桃園市楊梅區幼獅工業區幼四路1號 / NO. 1, YOU 4TH ROAD, YOUTH INDUSTRIAL DISTRICT, YANG-MEI, TAO-YUAN CITY, TAIWAN, R.O.C. (江蘇省昆山市篷朗昆嘉高科技工業區郭澤路 / GUO-ZE ROAD, KUNJIA HI-TECH INDUSTRIAL PARK, KUN-SHAN, JIANG-SU, CHINA) (桃園市中壢區中壢工業區長春六路15號 / NO. 15, CHANGCHUN 6TH RD., JHONGLI CITY, TAOYUAN COUNTY 320, TAIWAN) (江蘇省宿遷市泗洪縣經濟開發區金沙南路-高新技術產業園 / HIGH-TECH INDUSTRIAL DISTRICT, JINSHAJIANG ROAD, SIHONG COUNTY ECONOMIC, SUQIAN CITY, JIANGSU)

> * 照片中如有箭頭標示,則表示為實際檢測之樣品/部位. * (The tested sample / part is marked by an arrow if it's shown on the photo.)

CE/2015/B1564



CE/2015/B1564



** 報告結尾 (End of Report) **

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.seg.com/en/Terms-and-Conditions aspk</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.seg.com/en/Terms-and-Conditions aspk</u> drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its Intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in tull, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwises stated the results shown in this test report refer only to the sample(s) tested.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司 25. Wu Chyuan 7th Road, New Taipei Industrial Park, Wu Ku District, New Taipei City, Taiwan 麻北市五般區和進業園區五層上路25號