




Surface Mount Schottky Rectifier

Features

- Low profile package
- Ideal for automated placement
- Guardring for overvoltage protection
- Low power losses, high efficiency
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

DO-214AC (SMA)



Typical Applications

For use in low voltage high frequency inverters, freewheeling, DC/DC converters, and polarity protection applications.

Mechanical Data

- **Package:** DO-214AC (SMA)
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■ Maximum Ratings (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	SS									
			32	33	34	35	36	38A	310	315	320	
Repetitive peak reverse voltage	V _{RRM}	V	20	30	40	50	60	80	100	150	200	
Average rectified output current @60Hz sine wave, resistance load, TL (FIG.1)	I _O	A	3.0									
Surge(non-repetitive)forward current @60Hz half-sine wave, 1 cycle, T _a =25°C	I _{FSM}	A	70									
Storage temperature	T _{stg}	°C	-55 ~+150									
Junction temperature	T _J	°C	-55 ~+150					-55 ~+175				

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	SS									
				32	33	34	35	36	38	310	315	320	
Maximum instantaneous forward voltage drop per diode	V _F	V	I _{FM} =3.0A	0.55			0.70		0.85		0.95		
Maximum DC reverse current at rated DC blocking voltage per diode@ V _{RM} =V _{RRM}	I _{RRM}	mA	T _a =25°C	0.50					0.10				
			T _a =100°C	10					5.0				

■ Thermal Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	SS								
			32	33	34	35	36	38	310	315	320
Thermal resistance	R _{θJA}	°C/W	55 ¹⁾								
	R _{θJL}		17 ¹⁾								

Note

(1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

■ Characteristics (Typical)

FIG1: I_o -TL Curve




FIG2: Surge Forward Current Capability




FIG.3: TYPICAL FORWARD CHARACTERISTICS




FIG4: Typical Reverse Characteristics

