


#### **Features**

- 70Watts peak pulse power (tp = 8/20µs)
- Tiny DFN0603 package
- Bidirectional configurations
- Solid-state silicon-avalanche technology
- Low clamping voltage
- Low leakage current
- Medium capacitance (CJ=12pF typ.)
- Protection one data/power line to: IEC 61000-4-2 ±30kV contact ±30kV air IEC 61000-4-4 (EFT) 40A (5/50ns) IEC 61000-4-5 (Lightning) 9A (8/20 µs)
- RoHS compliant


### **Applications**

- Audio Line, Speaker, Headset, Microphone Protection
- Human Interface Devices (Keyboard, Touchpad, Buttons)

#### SES3V3D0603SY-2B



**DFN0603** 



**Schematic Diagram** 

### **Absolute Maximum Ratings**

 $(T_A=25^{\circ}C, Unless otherwise specified.)$ 

Parameter	Symbol	Value	Unit
Peak Pulse Power (T <sub>P</sub> =8/20μS)	P <sub>PP</sub>	70	W
ESD contact/air discharge (IEC-61000-4-2)	V <sub>ESD</sub>	30	kV
Peak Pulse Current ( t₂ = 8/20µS )	I <sub>PP</sub>	9	Α
Junction Temperature	TJ	-55 to +125	$^{\circ}$
Storage temperature	T <sub>STG</sub>	-55 to +150	${\mathbb C}$

#### **Electrical Characteristics**

(T<sub>A</sub>=25  $^{\circ}$ C, Unless otherwise specified.)

Parameter	Symbol	Condition	Min	Тур	Max	Unit
Reverse stand-off Voltage	$V_{RWM}$				3.3	V
Reverse Breakdown Voltage	$V_{BR}$	I <sub>T</sub> =1mA	3.4			V
Reverse Leakage Current	I <sub>R</sub>	V <sub>R</sub> =3.3V			0.2	uA
Clamping Voltage (IEC 61000-4-5)	V <sub>C</sub>	I <sub>PP</sub> =9A			8	V
Junction Capacitance	CJ	V <sub>R</sub> =0V, f=1MHz		12		pF



## **Typical Characteristic Curves**

Fig.1 Peak Pulse Power Rating Curve




Fig.2 Pulse Derating Curve




Fig.3 Pulse Waveform-8/20µs






Fig.4 Pulse Waveform-ESD(IEC61000-4-2)



### **Product Dimensions**



Cumbal	Dimensions in millimeter			
Symbol	Min Nom		Max	
Α	0.23	-	0.33	
A1	0.00	-	0.05	
A3	0.102 REF			
D	0.55	0.60	0.65	
Е	0.25	0.30	0.35	
b	0.215	0.245	0.275	
L	0.13	0.18	0.23	
L1	0.13	0.18	0.23	
е	0.355 BSC			



# Marking



## **Order Information**

Device	Package	Carrier	Quantity	HSF Status
SES3V3D0603SY-2B	DFN0603	Tape & Reel	10000pcs / Reel	RoHS compliant

## **Revision history**

Date	Revision	Description of changes
20-October-2020	A2	Update



#### **CAUTION / WARNING**

- Information in this document is believed to be accurate and reliable. However, SEMITEL does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.
- Users should independently evaluate the suitability of and test each product selected for their own applications, and SEMITEL assumes no liability whatsoever relating to the choice, selection or use of the SEMITEL products and services described herein.
- SEMITEL reserves the right to change or update, without notice, any information contained in this publication; to change, without notice, the design, construction, processing, or specification of any product; and to discontinue or limit production or distribution of any product.
- · Information in this document supersedes and replaces all information previously supplied.
- Products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in
  applications where failure or malfunction of an SEMITEL product can reasonably be expected to result in personal injury, death or severe property or
  environmental damage. SEMITEL accepts no liability for inclusion and/or use of SEMITEL products in such equipment or applications and therefore
  such inclusion and/or use is at the customer's own risk.
- This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.
- Resale of SEMITEL products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by SEMITEL for the SEMITEL product or service described herein and shall not create or extend in any manner whatsoever, any liability of SEMITEL.
- SEMITEL expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. SEMITEL only obligations are those in the SEMITEL Standard Terms and Conditions of Sale and in no case will SEMITEL be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products.

Specifications are subject to change without notice
© Copyright 2005, Semitel Electronics
Semitel

. ® is a registered trademark of Semitel Electronics
All rights reserved