



BBL4001

N-Channel Power MOSFET 60V, 74A, 6.1mΩ, TO-220F-3SG

ON Semiconductor®

<http://onsemi.com>

Features

- ON-resistance $R_{DS(on)1}=4.7\text{m}\Omega(\text{typ.})$
- Input capacitance $C_{iss}=6,900\text{pF}(\text{typ.})$
- 4V drive

Specifications

Absolute Maximum Ratings at $T_a=25^\circ\text{C}$

Parameter	Symbol	Conditions	Ratings	Unit
Drain to Source Voltage	V_{DSS}		60	V
Gate to Source Voltage	V_{GSS}		± 20	V
Drain Current (DC)	I_D		74	A
Drain Current (Pulse)	I_{DP}	$PW \leq 10\mu\text{s}$, duty cycle $\leq 1\%$	296	A
Allowable Power Dissipation	PD		2.0	W
		$T_c=25^\circ\text{C}$	35	W
Junction Temperature	T_j		150	$^\circ\text{C}$
Storage Temperature	T_{stg}		-55 to +150	$^\circ\text{C}$
Avalanche Energy (Single Pulse) *1	E_{AS}		370	mJ
Avalanche Current *2	I_{AV}		65	A

Note : *1 $V_{DD}=30\text{V}$, $L=100\mu\text{H}$, $I_{AV}=65\text{A}(\text{Fig.1})$ *2 $L \leq 100\mu\text{H}$, Single pulse

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.









Electrical Characteristics at $T_a=25^\circ\text{C}$







Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain to Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D=1\text{mA}$, $V_{GS}=0\text{V}$	60			V
Zero-Gate Voltage Drain Current	I_{DSS}	$V_{DS}=60\text{V}$, $V_{GS}=0\text{V}$			1	μA
Gate to Source Leakage Current	I_{GSS}	$V_{GS}=\pm 16\text{V}$, $V_{DS}=0\text{V}$			± 10	μA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=10\text{V}$, $I_D=1\text{mA}$	1.2		2.6	V
Forward Transconductance	g_{FS}	$V_{DS}=10\text{V}$, $I_D=37\text{A}$	32	53		S
Static Drain to Source On-State Resistance	$R_{DS(on)1}$	$I_D=37\text{A}$, $V_{GS}=10\text{V}$		4.7	6.1	$\text{m}\Omega$
	$R_{DS(on)2}$	$I_D=37\text{A}$, $V_{GS}=4\text{V}$		7.0	9.8	$\text{m}\Omega$
Input Capacitance	C_{iss}			6900		pF
Output Capacitance	C_{oss}	$V_{DS}=20\text{V}$, $f=1\text{MHz}$		740		pF
Reverse Transfer Capacitance	C_{rss}			540		pF
Turn-ON Delay Time	$t_d(on)$	See specified Test Circuit.		48		ns
Rise Time	t_r			300		ns
Turn-OFF Delay Time	$t_d(off)$			510		ns
Fall Time	t_f			340		ns
Total Gate Charge	Q_g				135	
Gate to Source Charge	Q_{gs}	$V_{DS}=30\text{V}$, $V_{GS}=10\text{V}$, $I_D=74\text{A}$		18		nC
Gate to Drain "Miller" Charge	Q_{gd}			32		nC
Diode Forward Voltage	V_{SD}	$I_S=74\text{A}$, $V_{GS}=0\text{V}$		1.0	1.2	V

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

ORDERING INFORMATION

See detailed ordering and shipping information on page 4 of this data sheet.





BBL4001

Package Dimensions

BBL4001-1E


TO-220 Fullpack, 3-Lead / TO-220F-3SG

CASE 221AT

ISSUE A

unit : mm

- 1: Gate
- 2: Drain
- 3: Source




*1 Lot indication

Ordering & Package Information

Device	Package	Shipping	memo
BBL4001-1E	TO-220F-3SG SC-67	50 pcs. / tube	Pb-Free

Marking



Electrical Connection




Fig.1 Unclamped Inductive Switching Test Circuit





Fig.2 Switching Time Test Circuit



Note on usage : Since the BBL4001 is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.