

# LXZ Series

- Adoption of innovative electrolyte and new technologies
- Very low impedance at high frequency
- Endurance with ripple current: 2,000 to 8,000 hours at 105°C
- Solvent resistant type (see PRECAUTIONS AND GUIDELINES)
- RoHS2 Compliant
- AEC-Q200 compliant : Please contact Chemi-Con for more details, test data, information.




## SPECIFICATIONS

| Items                             | Characteristics  |                                  |                             |                    |                                       |                    |                               |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
|-----------------------------------|--|----------------------------------|-----------------------------|--------------------|---------------------------------------|--------------------|-------------------------------|--------------------|-----------------------------|--------------|------|------|------|--------------|---------------------------------------|------|------|--|--|-----------------|-------------------------------|--|--|--|--|
| <b>Category</b>                   | -55 to +105°C  |                                  |                             |                    |                                       |                    |                               |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| <b>Temperature Range</b>          | -55 to +105°C  |                                  |                             |                    |                                       |                    |                               |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| <b>Rated Voltage Range</b>        | 6.3 to 63V <sub>dc</sub>   |                                  |                             |                    |                                       |                    |                               |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| <b>Capacitance Tolerance</b>      | ±20% (M) (at 20°C, 120Hz)  |                                  |                             |                    |                                       |                    |                               |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| <b>Leakage Current</b>            | I=0.01CV or 3μA, whichever is greater.<br>Where, I : Max. leakage current (μA), C : Nominal capacitance (μF), V : Rated voltage (V) (at 20°C after 2 minutes)  |                                  |                             |                    |                                       |                    |                               |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| <b>Dissipation Factor (tan δ)</b> | <table border="1"> <tr> <td>Rated voltage (V<sub>dc</sub>)</td> <td>6.3V</td> <td>10V</td> <td>16V</td> <td>25V</td> <td>35V</td> <td>50V</td> <td>63V</td> </tr> <tr> <td>tan δ (Max.)</td> <td>0.22</td> <td>0.19</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> <td>0.10</td> <td>0.08</td> </tr> </table> <p>When nominal capacitance exceeds 1,000μF, add 0.02 to the value above for each 1,000μF increase. (at 20°C, 120Hz)</p>   | Rated voltage (V <sub>dc</sub> ) | 6.3V                        | 10V                | 16V                                   | 25V                | 35V                           | 50V                | 63V                         | tan δ (Max.) | 0.22 | 0.19 | 0.16 | 0.14         | 0.12                                  | 0.10 | 0.08 |  |  |                 |                               |  |  |  |  |
| Rated voltage (V <sub>dc</sub> )  | 6.3V   | 10V                              | 16V                         | 25V                | 35V                                   | 50V                | 63V                           |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| tan δ (Max.)                      | 0.22   | 0.19                             | 0.16                        | 0.14               | 0.12                                  | 0.10               | 0.08                          |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| <b>Endurance</b>                  | <p>The following specifications shall be satisfied when the capacitors are restored to 20°C after subjected to DC voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) for the specified period of time at 105°C.</p> <table border="1"> <tr> <td>Time</td> <td>φ5 &amp; 6.3 : 2,000hours</td> <td>φ8 : 3,000hours</td> <td>φ10 : 5,000hours</td> <td>φ12.5 : 7,000hours</td> <td>φ16 &amp; 18 : 8,000hours</td> </tr> <tr> <td>Capacitance change</td> <td colspan="5">≤ ±20% of the initial value</td> </tr> <tr> <td>D.F. (tan δ)</td> <td colspan="5">≤ 200% of the initial specified value</td> </tr> <tr> <td>Leakage current</td> <td colspan="5">≤ The initial specified value</td> </tr> </table> | Time                             | φ5 & 6.3 : 2,000hours       | φ8 : 3,000hours    | φ10 : 5,000hours                      | φ12.5 : 7,000hours | φ16 & 18 : 8,000hours         | Capacitance change | ≤ ±20% of the initial value |              |      |      |      | D.F. (tan δ) | ≤ 200% of the initial specified value |      |      |  |  | Leakage current | ≤ The initial specified value |  |  |  |  |
| Time                              | φ5 & 6.3 : 2,000hours  | φ8 : 3,000hours                  | φ10 : 5,000hours            | φ12.5 : 7,000hours | φ16 & 18 : 8,000hours                 |                    |                               |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| Capacitance change                | ≤ ±20% of the initial value  |                                  |                             |                    |                                       |                    |                               |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| D.F. (tan δ)                      | ≤ 200% of the initial specified value  |                                  |                             |                    |                                       |                    |                               |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| Leakage current                   | ≤ The initial specified value  |                                  |                             |                    |                                       |                    |                               |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| <b>Shelf Life</b>                 | <p>The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 105°C without voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to Item 4.1 of JIS C 5101-4.</p> <table border="1"> <tr> <td>Capacitance change</td> <td>≤ ±20% of the initial value</td> </tr> <tr> <td>D.F. (tan δ)</td> <td>≤ 200% of the initial specified value</td> </tr> <tr> <td>Leakage current</td> <td>≤ The initial specified value</td> </tr> </table>  | Capacitance change               | ≤ ±20% of the initial value | D.F. (tan δ)       | ≤ 200% of the initial specified value | Leakage current    | ≤ The initial specified value |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| Capacitance change                | ≤ ±20% of the initial value  |                                  |                             |                    |                                       |                    |                               |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| D.F. (tan δ)                      | ≤ 200% of the initial specified value  |                                  |                             |                    |                                       |                    |                               |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |
| Leakage current                   | ≤ The initial specified value  |                                  |                             |                    |                                       |                    |                               |                    |                             |              |      |      |      |              |                                       |      |      |  |  |                 |                               |  |  |  |  |


## DIMENSIONS [mm]

### Terminal Code : E



| φD  | 5          | 6.3 | 8   | 10  | 12.5 | 16  | 18  |
|-----|------------|-----|-----|-----|------|-----|-----|
| φd  | 0.5        | 0.5 | 0.6 | 0.6 | 0.6  | 0.8 | 0.8 |
| F   | 2.0        | 2.5 | 3.5 | 5.0 | 5.0  | 7.5 | 7.5 |
| φD' | φD+0.5max. |     |     |     |      |     |     |
| L'  | L+1.5max.  |     |     |     |      |     |     |

## PART NUMBERING SYSTEM



Please refer to "Product code guide (radial lead type)"

◆ STANDARD RATINGS

| VV (V <sub>dc</sub> ) | Cap (μF) | Case size φD×L(mm) | Impedance (Ω max./100kHz) |       | Rated ripple current (mA rms/105°C, 100kHz) | Part No.           | VV (V <sub>dc</sub> ) | Cap (μF) | Case size φD×L(mm) | Impedance (Ω max./100kHz) |                    | Rated ripple current (mA rms/105°C, 100kHz) | Part No.           |
|-----------------------|----------|--------------------|---------------------------|-------|---|--------------------|-----------------------|----------|--------------------|---------------------------|--------------------|---|--------------------|
|                       |          |                    | 20°C                      | -10°C |   |                    |                       |          |                    | 20°C                      | -10°C              |   |                    |
| 6.3                   | 150      | 5×11.5             | 0.50                      | 1.0   | 175   | ELXZ6R3E□□151MEB5D | 16                    | 2,700    | 16×20              | 0.029                     | 0.058              | 2,210                                       | ELXZ160E□□272ML20S |
|                       | 330      | 6.3×11.5           | 0.25                      | 0.50  | 290   | ELXZ6R3E□□331MFB5D |                       | 3,300    | 12.5×35            | 0.022                     | 0.044              | 2,510                                       | ELXZ160E□□332MK35S |
|                       | 470      | 6.3×15             | 0.18                      | 0.36  | 400   | ELXZ6R3E□□471MF15D |                       | 3,900    | 12.5×40            | 0.017                     | 0.034              | 2,870                                       | ELXZ160E□□392MK40S |
|                       | 680      | 8×12               | 0.12                      | 0.24  | 555   | ELXZ6R3E□□681MH12D |                       | 3,900    | 16×25              | 0.022                     | 0.044              | 2,560                                       | ELXZ160E□□392ML25S |
|                       | 820      | 10×12.5            | 0.090                     | 0.18  | 760   | ELXZ6R3E□□821MJC5S |                       | 3,900    | 18×20              | 0.028                     | 0.056              | 2,490                                       | ELXZ160E□□392MM20S |
|                       | 1,000    | 8×15               | 0.090                     | 0.18  | 730   | ELXZ6R3E□□102MH15D |                       | 4,700    | 16×30              | 0.019                     | 0.038              | 3,010                                       | ELXZ160E□□472ML30S |
|                       | 1,200    | 8×20               | 0.080                     | 0.16  | 810   | ELXZ6R3E□□122MH20D |                       | 4,700    | 18×25              | 0.020                     | 0.040              | 2,740                                       | ELXZ160E□□472MM25S |
|                       | 1,200    | 10×16              | 0.068                     | 0.136 | 1,050                                       | ELXZ6R3E□□122MJ16S |                       | 5,600    | 16×35              | 0.017                     | 0.034              | 3,150                                       | ELXZ160E□□562ML35S |
|                       | 1,500    | 10×20              | 0.052                     | 0.104 | 1,220                                       | ELXZ6R3E□□152MJ20S |                       | 5,600    | 18×30              | 0.018                     | 0.036              | 3,330                                       | ELXZ160E□□562MM30S |
|                       | 2,200    | 10×25              | 0.045                     | 0.090 | 1,440                                       | ELXZ6R3E□□222MJ25S |                       | 6,800    | 16×40              | 0.015                     | 0.030              | 3,710                                       | ELXZ160E□□682ML40S |
|                       | 2,700    | 10×30              | 0.037                     | 0.074 | 1,690                                       | ELXZ6R3E□□272MJ30S |                       | 8,200    | 18×35              | 0.016                     | 0.032              | 3,680                                       | ELXZ160E□□822MM35S |
|                       | 3,300    | 12.5×20            | 0.038                     | 0.076 | 1,660                                       | ELXZ6R3E□□332MK20S |                       | 10,000   | 18×40              | 0.015                     | 0.030              | 3,800                                       | ELXZ160E□□103MM40S |
|                       | 3,900    | 12.5×25            | 0.030                     | 0.060 | 1,950                                       | ELXZ6R3E□□392MK25S |                       | 47       | 5×11.5             | 0.50                      | 1.0                | 175   | ELXZ250E□□470MEB5D |
|                       | 4,700    | 12.5×30            | 0.025                     | 0.050 | 2,310                                       | ELXZ6R3E□□472MK30S |                       | 100      | 6.3×11.5           | 0.25                      | 0.50               | 290   | ELXZ250E□□101MFB5D |
|                       | 5,600    | 12.5×35            | 0.022                     | 0.044 | 2,510                                       | ELXZ6R3E□□562MK35S |                       | 150      | 6.3×15             | 0.18                      | 0.36               | 400   | ELXZ250E□□151MF15D |
|                       | 5,600    | 16×20              | 0.029                     | 0.058 | 2,210                                       | ELXZ6R3E□□562ML20S |                       | 220      | 8×12               | 0.12                      | 0.24               | 555   | ELXZ250E□□221MH12D |
|                       | 6,800    | 12.5×40            | 0.017                     | 0.034 | 2,870                                       | ELXZ6R3E□□682MK40S |                       | 330      | 8×15               | 0.090                     | 0.18               | 730   | ELXZ250E□□331MH15D |
|                       | 6,800    | 16×25              | 0.022                     | 0.044 | 2,560                                       | ELXZ6R3E□□682ML25S |                       | 330      | 10×12.5            | 0.090                     | 0.18               | 760   | ELXZ250E□□331MJC5S |
|                       | 6,800    | 18×20              | 0.028                     | 0.056 | 2,490                                       | ELXZ6R3E□□682MM20S |                       | 390      | 8×20               | 0.080                     | 0.16               | 810   | ELXZ250E□□391MH20D |
|                       | 8,200    | 16×30              | 0.019                     | 0.038 | 3,010                                       | ELXZ6R3E□□822ML30S |                       | 470      | 10×16              | 0.068                     | 0.136              | 1,050                                       | ELXZ250E□□471MJ16S |
| 10,000                | 16×35    | 0.017              | 0.034                     | 3,150 | ELXZ6R3E□□103ML35S                          | 680                | 10×20                 | 0.052    | 0.104              | 1,220                     | ELXZ250E□□681MJ20S |   |                    |
| 10,000                | 18×25    | 0.020              | 0.040                     | 2,740 | ELXZ6R3E□□103MM25S                          | 820                | 10×25                 | 0.045    | 0.090              | 1,440                     | ELXZ250E□□821MJ25S |   |                    |
| 12,000                | 16×40    | 0.015              | 0.030                     | 3,710 | ELXZ6R3E□□123ML40S                          | 1,000              | 10×30                 | 0.037    | 0.074              | 1,690                     | ELXZ250E□□102MJ30S |   |                    |
| 12,000                | 18×30    | 0.018              | 0.036                     | 3,330 | ELXZ6R3E□□123MM30S                          | 1,000              | 12.5×20               | 0.038    | 0.076              | 1,660                     | ELXZ250E□□102MK20S |   |                    |
| 15,000                | 18×35    | 0.016              | 0.032                     | 3,680 | ELXZ6R3E□□153MM35S                          | 1,500              | 12.5×25               | 0.030    | 0.060              | 1,950                     | ELXZ250E□□152MK25S |   |                    |
| 18,000                | 18×40    | 0.015              | 0.030                     | 3,800 | ELXZ6R3E□□183MM40S                          | 1,800              | 12.5×30               | 0.025    | 0.050              | 2,310                     | ELXZ250E□□182MK30S |   |                    |
| 10                    | 100      | 5×11.5             | 0.50                      | 1.0   | 175   | ELXZ100E□□101MEB5D | 25                    | 1,800    | 16×20              | 0.029                     | 0.058              | 2,210                                       | ELXZ250E□□182ML20S |
|                       | 220      | 6.3×11.5           | 0.25                      | 0.50  | 290   | ELXZ100E□□221MFB5D |                       | 2,200    | 12.5×30            | 0.025                     | 0.050              | 2,310                                       | ELXZ250E□□222MK30S |
|                       | 330      | 6.3×15             | 0.18                      | 0.36  | 400   | ELXZ100E□□331MF15D |                       | 2,200    | 12.5×35            | 0.022                     | 0.044              | 2,510                                       | ELXZ250E□□222MK35S |
|                       | 470      | 8×12               | 0.12                      | 0.24  | 555   | ELXZ100E□□471MH12D |                       | 2,200    | 18×20              | 0.028                     | 0.056              | 2,490                                       | ELXZ250E□□222MM20S |
|                       | 680      | 8×15               | 0.090                     | 0.18  | 730   | ELXZ100E□□681MH15D |                       | 2,700    | 12.5×40            | 0.017                     | 0.034              | 2,870                                       | ELXZ250E□□272MK40S |
|                       | 680      | 10×12.5            | 0.090                     | 0.18  | 760   | ELXZ100E□□681MJC5S |                       | 2,700    | 16×25              | 0.022                     | 0.044              | 2,560                                       | ELXZ250E□□272ML25S |
|                       | 1,000    | 8×20               | 0.080                     | 0.16  | 810   | ELXZ100E□□102MH20D |                       | 3,300    | 16×25              | 0.022                     | 0.044              | 2,560                                       | ELXZ250E□□332ML25S |
|                       | 1,000    | 10×16              | 0.068                     | 0.136 | 1,050                                       | ELXZ100E□□102MJ16S |                       | 3,300    | 16×30              | 0.019                     | 0.038              | 3,010                                       | ELXZ250E□□332ML30S |
|                       | 1,200    | 10×20              | 0.052                     | 0.104 | 1,220                                       | ELXZ100E□□122MJ20S |                       | 3,300    | 18×20              | 0.028                     | 0.056              | 2,490                                       | ELXZ250E□□332MM20S |
|                       | 1,500    | 10×25              | 0.045                     | 0.090 | 1,440                                       | ELXZ100E□□152MJ25S |                       | 3,300    | 18×25              | 0.020                     | 0.040              | 2,740                                       | ELXZ250E□□332MM25S |
|                       | 1,800    | 10×30              | 0.037                     | 0.074 | 1,690                                       | ELXZ100E□□182MJ30S |                       | 3,900    | 16×35              | 0.017                     | 0.034              | 3,150                                       | ELXZ250E□□392ML35S |
|                       | 2,200    | 10×30              | 0.037                     | 0.074 | 1,690                                       | ELXZ100E□□222MJ30S |                       | 3,900    | 18×30              | 0.018                     | 0.036              | 3,330                                       | ELXZ250E□□392MM30S |
|                       | 2,200    | 12.5×20            | 0.038                     | 0.076 | 1,660                                       | ELXZ100E□□222MK20S |                       | 4,700    | 16×40              | 0.015                     | 0.030              | 3,710                                       | ELXZ250E□□472ML40S |
|                       | 3,300    | 12.5×25            | 0.030                     | 0.060 | 1,950                                       | ELXZ100E□□332MK25S |                       | 4,700    | 18×35              | 0.016                     | 0.032              | 3,680                                       | ELXZ250E□□472MM35S |
|                       | 3,900    | 12.5×30            | 0.025                     | 0.050 | 2,310                                       | ELXZ100E□□392MK30S |                       | 5,600    | 18×40              | 0.015                     | 0.030              | 3,800                                       | ELXZ250E□□562MM40S |
|                       | 3,900    | 16×20              | 0.029                     | 0.058 | 2,210                                       | ELXZ100E□□392ML20S |                       | 33       | 5×11.5             | 0.50                      | 1.0                | 175   | ELXZ350E□□330MEB5D |
|                       | 4,700    | 12.5×35            | 0.022                     | 0.044 | 2,510                                       | ELXZ100E□□472MK35S |                       | 56       | 6.3×11.5           | 0.25                      | 0.50               | 290   | ELXZ350E□□560MFB5D |
|                       | 5,600    | 12.5×40            | 0.017                     | 0.034 | 2,870                                       | ELXZ100E□□562MK40S |                       | 100      | 6.3×15             | 0.18                      | 0.36               | 400   | ELXZ350E□□101MF15D |
|                       | 5,600    | 16×25              | 0.022                     | 0.044 | 2,560                                       | ELXZ100E□□562ML25S |                       | 150      | 8×12               | 0.12                      | 0.24               | 555   | ELXZ350E□□151MH12D |
|                       | 5,600    | 18×20              | 0.028                     | 0.056 | 2,490                                       | ELXZ100E□□562MM20S |                       | 220      | 8×15               | 0.090                     | 0.18               | 730   | ELXZ350E□□221MH15D |
| 6,800                 | 16×30    | 0.019              | 0.038                     | 3,010 | ELXZ100E□□682ML30S                          | 220                | 10×12.5               | 0.090    | 0.18               | 760                       | ELXZ350E□□221MJC5S |   |                    |
| 6,800                 | 18×25    | 0.020              | 0.040                     | 2,740 | ELXZ100E□□682MM25S                          | 270                | 8×20                  | 0.080    | 0.16               | 810                       | ELXZ350E□□271MH20D |   |                    |
| 8,200                 | 16×35    | 0.017              | 0.034                     | 3,150 | ELXZ100E□□822ML35S                          | 330                | 10×16                 | 0.068    | 0.136              | 1,050                     | ELXZ350E□□331MJ16S |   |                    |
| 8,200                 | 18×30    | 0.018              | 0.036                     | 3,330 | ELXZ100E□□822MM30S                          | 470                | 10×20                 | 0.052    | 0.104              | 1,220                     | ELXZ350E□□471MJ20S |   |                    |
| 10,000                | 16×40    | 0.015              | 0.030                     | 3,710 | ELXZ100E□□103ML40S                          | 560                | 10×20                 | 0.052    | 0.104              | 1,220                     | ELXZ350E□□561MJ20S |   |                    |
| 10,000                | 18×35    | 0.016              | 0.032                     | 3,680 | ELXZ100E□□103MM35S                          | 560                | 10×25                 | 0.045    | 0.090              | 1,440                     | ELXZ350E□□561MJ25S |   |                    |
| 12,000                | 18×40    | 0.015              | 0.030                     | 3,800 | ELXZ100E□□123MM40S                          | 680                | 10×30                 | 0.037    | 0.074              | 1,690                     | ELXZ350E□□681MJ30S |   |                    |
| 16                    | 47       | 5×11.5             | 0.50                      | 1.0   | 175   | ELXZ160E□□470MEB5D | 35                    | 680      | 12.5×20            | 0.038                     | 0.076              | 1,660                                       | ELXZ350E□□681MK20S |
|                       | 100      | 6.3×11.5           | 0.25                      | 0.50  | 290   | ELXZ160E□□101MFB5D |                       | 1,000    | 12.5×20            | 0.038                     | 0.076              | 1,660                                       | ELXZ350E□□102MK20S |
|                       | 220      | 6.3×15             | 0.18                      | 0.36  | 400   | ELXZ160E□□221MF15D |                       | 1,000    | 12.5×25            | 0.030                     | 0.060              | 1,950                                       | ELXZ350E□□102MK25S |
|                       | 330      | 8×12               | 0.12                      | 0.24  | 555   | ELXZ160E□□331MH12D |                       | 1,200    | 12.5×30            | 0.025                     | 0.050              | 2,310                                       | ELXZ350E□□122MK30S |
|                       | 470      | 8×15               | 0.090                     | 0.18  | 730   | ELXZ160E□□471MH15D |                       | 1,200    | 16×20              | 0.029                     | 0.058              | 2,210                                       | ELXZ350E□□122ML20S |
|                       | 470      | 10×12.5            | 0.090                     | 0.18  | 760   | ELXZ160E□□471MJC5S |                       | 1,500    | 12.5×35            | 0.022                     | 0.044              | 2,510                                       | ELXZ350E□□152MK35S |
|                       | 560      | 8×20               | 0.080                     | 0.16  | 810   | ELXZ160E□□561MH20D |                       | 1,800    | 12.5×40            | 0.017                     | 0.034              | 2,870                                       | ELXZ350E□□182MK40S |
|                       | 680      | 10×16              | 0.068                     | 0.136 | 1,050                                       | ELXZ160E□□681MJ16S |                       | 1,800    | 16×25              | 0.022                     | 0.044              | 2,560                                       | ELXZ350E□□182ML25S |
|                       | 1,000    | 10×20              | 0.052                     | 0.104 | 1,220                                       | ELXZ160E□□102MJ20S |                       | 1,800    | 18×20              | 0.028                     | 0.056              | 2,490                                       | ELXZ350E□□182MM20S |
|                       | 1,200    | 10×25              | 0.045                     | 0.090 | 1,440                                       | ELXZ160E□□122MJ25S |                       | 2,200    | 16×25              | 0.022                     | 0.044              | 2,560                                       | ELXZ350E□□222ML25S |
|                       | 1,500    | 10×30              | 0.037                     | 0.074 | 1,690                                       | ELXZ160E□□152MJ30S |                       | 2,200    | 16×30              | 0.019                     | 0.038              | 3,010                                       | ELXZ350E□□222ML30S |
|                       | 1,500    | 12.5×20            | 0.038                     | 0.076 | 1,660                                       | ELXZ160E□□152MK20S |                       | 2,200    | 18×20              | 0.028                     | 0.056              | 2,490                                       | ELXZ350E□□222MM20S |
|                       | 2,200    | 12.5×25            | 0.030                     | 0.060 | 1,950                                       | ELXZ160E□□222MK25S |                       | 2,200    | 18×25              | 0.020                     | 0.040              | 2,740                                       | ELXZ350E□□222MM25S |
|                       | 2,700    | 12.5×30            | 0.025                     | 0.050 | 2,310                                       | ELXZ160E□□272MK30S |                       | 2,700    | 16×35              | 0.017                     | 0.034              | 3,150                                       | ELXZ350E□□272ML35S |

□□ : Enter the appropriate lead forming or taping code.

◆STANDARD RATINGS

| VV<br>(V <sub>dc</sub> ) | Cap<br>(μF) | Case size<br>φD×L(mm) | Impedance<br>(Ω max./100kHz) |       | Rated<br>ripple<br>current<br>(mA <sub>rms</sub> /105°C,<br>100kHz) | Part No.           | VV<br>(V <sub>dc</sub> ) | Cap<br>(μF) | Case size<br>φD×L(mm) | Impedance<br>(Ω max./100kHz) |                    | Rated<br>ripple<br>current<br>(mA <sub>rms</sub> /105°C,<br>100kHz) | Part No.           |
|--------------------------|-------------|-----------------------|------------------------------|-------|---|--------------------|--------------------------|-------------|-----------------------|------------------------------|--------------------|---|--------------------|
|                          |             |                       | 20°C                         | -10°C |   |                    |                          |             |                       | 20°C                         | -10°C              |   |                    |
| 35                       | 2,700       | 18×30                 | 0.018                        | 0.036 | 3,330   | ELXZ350E□□272MM30S | 50                       | 2,200       | 18×35                 | 0.023                        | 0.046              | 3,100   | ELXZ500E□□222MM35S |
|                          | 3,300       | 16×40                 | 0.015                        | 0.030 | 3,710   | ELXZ350E□□332ML40S |                          | 2,700       | 18×40                 | 0.020                        | 0.040              | 3,400   | ELXZ500E□□272MM40S |
|                          | 3,300       | 18×35                 | 0.016                        | 0.032 | 3,680   | ELXZ350E□□332MM35S |                          | 12          | 5×11.5                | 1.9                          | 4.0                | 145   | ELXZ630E□□120MEB5D |
|                          | 3,900       | 18×40                 | 0.015                        | 0.030 | 3,800   | ELXZ350E□□392MM40S |                          | 22          | 6.3×11.5              | 1.0                          | 2.0                | 240   | ELXZ630E□□220MFB5D |
|                          | 4,700       | 18×40                 | 0.015                        | 0.030 | 3,800   | ELXZ350E□□472MM40S |                          | 39          | 6.3×15                | 0.61                         | 1.4                | 330   | ELXZ630E□□390MF15D |
| 50                       | 22          | 5×11.5                | 0.90                         | 1.8   | 155   | ELXZ500E□□220MEB5D | 68                       | 8×12        | 0.34                  | 0.75                         | 405                | ELXZ630E□□680MH12D  |                    |
|                          | 47          | 6.3×11.5              | 0.45                         | 0.90  | 260   | ELXZ500E□□470MFB5D | 100                      | 8×15        | 0.27                  | 0.65                         | 535                | ELXZ630E□□101MH15D  |                    |
|                          | 68          | 6.3×15                | 0.31                         | 0.62  | 360   | ELXZ500E□□680MF15D | 100                      | 10×12.5     | 0.255                 | 0.51                         | 540                | ELXZ630E□□101MJC5S  |                    |
|                          | 100         | 8×12                  | 0.22                         | 0.44  | 485   | ELXZ500E□□101MH12D | 120                      | 10×16       | 0.19                  | 0.38                         | 600                | ELXZ630E□□121MJ16S  |                    |
|                          | 120         | 8×15                  | 0.16                         | 0.32  | 635   | ELXZ500E□□121MH15D | 150                      | 8×20        | 0.21                  | 0.52                         | 690                | ELXZ630E□□151MH20D  |                    |
|                          | 120         | 10×12.5               | 0.16                         | 0.32  | 620   | ELXZ500E□□121MJC5S | 180                      | 10×20       | 0.145                 | 0.29                         | 890                | ELXZ630E□□181MJ20S  |                    |
|                          | 180         | 8×20                  | 0.12                         | 0.24  | 730   | ELXZ500E□□181MH20D | 220                      | 10×25       | 0.13                  | 0.26                         | 1,050              | ELXZ630E□□221MJ25S  |                    |
|                          | 180         | 10×16                 | 0.13                         | 0.26  | 850   | ELXZ500E□□181MJ16S | 330                      | 10×30       | 0.090                 | 0.18                         | 1,300              | ELXZ630E□□331MJ30S  |                    |
|                          | 220         | 10×20                 | 0.088                        | 0.18  | 1,050   | ELXZ500E□□221MJ20S | 330                      | 12.5×20     | 0.085                 | 0.17                         | 1,290              | ELXZ630E□□331MK20S  |                    |
|                          | 330         | 10×25                 | 0.073                        | 0.15  | 1,250   | ELXZ500E□□331MJ25S | 390                      | 12.5×25     | 0.070                 | 0.14                         | 1,720              | ELXZ630E□□391MK25S  |                    |
|                          | 390         | 10×30                 | 0.054                        | 0.11  | 1,500   | ELXZ500E□□391MJ30S | 470                      | 12.5×30     | 0.055                 | 0.11                         | 2,090              | ELXZ630E□□471MK30S  |                    |
|                          | 390         | 12.5×20               | 0.059                        | 0.12  | 1,480   | ELXZ500E□□391MK20S | 470                      | 16×20       | 0.059                 | 0.12                         | 1,770              | ELXZ630E□□471ML20S  |                    |
|                          | 470         | 12.5×20               | 0.059                        | 0.12  | 1,480   | ELXZ500E□□471MK20S | 680                      | 12.5×35     | 0.047                 | 0.094                        | 2,270              | ELXZ630E□□681MK35S  |                    |
|                          | 560         | 12.5×25               | 0.044                        | 0.088 | 1,840   | ELXZ500E□□561MK25S | 680                      | 16×25       | 0.050                 | 0.10                         | 2,160              | ELXZ630E□□681ML25S  |                    |
|                          | 680         | 12.5×30               | 0.039                        | 0.078 | 2,220   | ELXZ500E□□681MK30S | 680                      | 18×20       | 0.055                 | 0.11                         | 2,290              | ELXZ630E□□681MM20S  |                    |
|                          | 680         | 16×20                 | 0.048                        | 0.096 | 1,840   | ELXZ500E□□681ML20S | 820                      | 12.5×40     | 0.042                 | 0.084                        | 2,560              | ELXZ630E□□821MK40S  |                    |
|                          | 820         | 12.5×35               | 0.033                        | 0.066 | 2,290   | ELXZ500E□□821MK35S | 820                      | 16×30       | 0.043                 | 0.086                        | 2,670              | ELXZ630E□□821ML30S  |                    |
|                          | 820         | 18×20                 | 0.042                        | 0.084 | 1,980   | ELXZ500E□□821MM20S | 820                      | 18×25       | 0.043                 | 0.086                        | 2,590              | ELXZ630E□□821MM25S  |                    |
|                          | 1,000       | 12.5×40               | 0.029                        | 0.058 | 2,500   | ELXZ500E□□102MK40S | 1,000                    | 16×30       | 0.043                 | 0.086                        | 2,670              | ELXZ630E□□102ML30S  |                    |
|                          | 1,000       | 16×25                 | 0.034                        | 0.068 | 2,240   | ELXZ500E□□102ML25S | 1,000                    | 16×35       | 0.036                 | 0.072                        | 2,770              | ELXZ630E□□102ML35S  |                    |
| 1,200                    | 16×30       | 0.028                 | 0.056                        | 2,700 | ELXZ500E□□122ML30S  | 1,200              | 16×40                    | 0.030       | 0.060                 | 2,850                        | ELXZ630E□□122ML40S |   |                    |
| 1,200                    | 18×25       | 0.029                 | 0.058                        | 2,610 | ELXZ500E□□122MM25S  | 1,200              | 18×30                    | 0.032       | 0.064                 | 2,950                        | ELXZ630E□□122MM30S |   |                    |
| 1,500                    | 16×35       | 0.025                 | 0.050                        | 2,800 | ELXZ500E□□152ML35S  | 1,500              | 18×35                    | 0.030       | 0.060                 | 3,100                        | ELXZ630E□□152MM35S |   |                    |
| 1,800                    | 16×40       | 0.021                 | 0.042                        | 3,200 | ELXZ500E□□182ML40S  | 1,800              | 18×40                    | 0.025       | 0.050                 | 3,210                        | ELXZ630E□□182MM40S |   |                    |
| 1,800                    | 18×30       | 0.025                 | 0.050                        | 3,000 | ELXZ500E□□182MM30S  | 2,200              | 18×40                    | 0.025       | 0.050                 | 3,210                        | ELXZ630E□□222MM40S |   |                    |

□□ : Enter the appropriate lead forming or taping code.

◆RATED RIPPLE CURRENT MULTIPLIERS

●Frequency Multipliers

| Capacitance(μF) | Frequency(Hz) | 120  | 1k   | 10k  | 100k |
|-----------------|---------------|------|------|------|------|
| 12 to 180       |               | 0.40 | 0.75 | 0.90 | 1.00 |
| 220 to 560      |               | 0.50 | 0.85 | 0.94 | 1.00 |
| 680 to 1,800    |               | 0.60 | 0.87 | 0.95 | 1.00 |
| 2,200 to 3,900  |               | 0.75 | 0.90 | 0.95 | 1.00 |
| 4,700 to 18,000 |               | 0.85 | 0.95 | 0.98 | 1.00 |

The endurance of capacitors is reduced with internal heating produced by ripple current at the rate of halving the lifetime with every 5°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced.