


RECOMMENDED PCB LAYOUT(T=0.80±0.05)  
COMPONENT SIDE(GENERAL TOLERANCE:±0.05)

NOTE:  
1.MATERIAL SPECIFICATION:  
1.HOUSING:LCP,UL94 V-0.  
2.TERMINAL: COPPER ALLOY  
3.MID PLATE: STAINLESS STEEL  
4.FRONT SHELL: STAINLESS STEEL  
5.EMI PLATE: STAINLESS STEEL  
2.PLATING SPECIFICATION:  
2-1.TERMINAL:  
Ni 50u" MIN. UNDER PLATED OVER ALL.  
Au PLATED ON THE FUNCTIONAL AREA OF CONTACT.  
(GOLD PLATING THICKNESS FOLLOW THE P/N)  
PLATING SPECIFICATIONS OF THE SOLDER AREA FOLLOW THE P/N  
2-2.FRONT SHELL:  
PLATING SPECIFICATIONS FOLLOW THE P/N  
2-3.MID PLATE&EMI PLATE:  
CLEAR ONLY  
3.MECHANICAL PERFORMANCE,  
3-1.INSERTION FORCE: 0.5~2.0kgf.  
3-2.REMOVAL FORCE: 0.8kgf~2.0kgf.  
3-3.DURABILITY: 10000 CYCLES.  
4.ELECTRICAL PERFORMANCE:  
4-1. VOLTAGE RATING:100V DC/AC (RMS. max)  
CURRENT RATING:3.0A MAX  
4-2. LLCR:  
VBUS & GND PINS AND OTHER PINS: 40mΩ/PIN MAX.  
SHIELD: 50mΩ/MAX.  
LLCR MAX. CHANGE OF ALL PINS: 10mΩ.  
4-3.INSULATION RESISTANCE: 100MΩ MIN  
4-4.DIELECTRIC WITHSTAND VOLTAGE,AC 100V FOR 1 MINUTE.  
5. ENVIRONMENTAL PERFORMANCE:  
OPERATING TEMPERATURE: -30°C~+85°C.  
6.IR REFLOW:  
THE PEAK TEMPERATURE ON THE BOARD SHALL  
BE MAINTAINED FOR 10 SECONDS AT 260°C.

A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

### U263-24XN-4BQC15



					DSND		DATE		SCALE: N/A	MODEL TYPE: 3.1 TYPE C		
					DWN		DATE		VIEW:	PART NO.:		
					CHKD		DATE		UNIT: mm/in	DWG NO.:		
					APPD		DATE		SIZE: A4	U263-24XN-4BQC15		
					UNSPECIFIED TOLERANCES					WEIGHT	SHEET	REVISION
					KKB INDUSTRIAL PRECISION CO.,LIMITED					1.0g	1/1	A0
Δx					ANGLAR		±5°					
Δx					L ≤ 4		±0.2					
Δx					4 < L ≤ 16		±0.3					
MARK	DESCRIPTION	DATE	REVISED	APPROVED	16 < L ≤ 63		±0.4					
					L > 63		±0.5					
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn												