


NPN Transistor



Features

- Epoxy meets UL-94 V-0 flammability rating
- Halogen free available upon request by adding suffix "HF"
- Moisture Sensitivity Level 1
- Surface mount package ideally Suited for Automatic Insertion
- NPN

Mechanical Data

- **Package:** SOT-23
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:**

BC849B	49B
BC849C	49C

■ Maximum Ratings (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Value
Collector-Base Voltage	V_{CBO}	V	$I_C=100\mu A, I_E=0$	50
Collector-Emitter Voltage	V_{CEO}	V	$I_C=0.1mA, I_B=0$	45
Emitter-Base Voltage	V_{EBO}	V	$I_E=100\mu A, I_C=0$	5
Collector Current	I_C	A		0.1
Collector Power Dissipation	P_C	mW		200
Operation Junction Temperature	T_j	°C		150
Storage Temperature	T_{stg}	°C		-55 to +150

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
BC849B	F2	Approximate 0.009	3000	30000	120000	7" reel
BC849C	F2	Approximate 0.009	3000	30000	120000	7" reel

**■ Electrical Characteristics** (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Min	Max
Collector-base breakdown voltage	V _{CB0}	V	IC=100μA,IE=0	50	
Collector-emitter breakdown voltage	V _{CEO}	V	IC =0.1mA,IB=0	45	
Emitter-base breakdown voltage	V _{EBO}	V	IE=100μA,IC=0	5	
Collector-Base cut-off current	I _{CB0}	uA	V _{CB} =50 V ,IE=0		0.1
Collector-emitter cut-off current	I _{CEO}	uA	VCE=35 V , IB=0		0.1
Emitter-base cut-off current	I _{EBO}	uA	V _{EB} =3 V , IC=0		0.1
DC current gain	h _{FE}		VCE=5V,IC=1mA	200	1000
Collector-emitter saturation voltage	V _{CE(sat)}	V	IC=100mA,IB=5mA		0.3
Base-emitter saturation voltage	V _{BE(sat)*}	V	IC=100mA,IB=5mA		1

■ Other Characteristics (Ta=25°C Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Max
Transition frequency	f _T	MHz	VCE= 5 V, IC= 10mA, f=30MHz	150	


■ Classification of h_{FE}

Rank	BC849B	BC849C
Range	200-450	420-1000




■ Characteristics(Typical)


Static Characteristic




DC Current Gain




Collector-Emitter Saturation Voltage




Base-Emitter Saturation Voltage




Base-Emitter On Voltage



Cob/Cib-Vcb/Veb




■SOT-23 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
ø	0°	8°	0°	8°

■SOT-23 Soldering Footprint





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.