KEMET Part Number: M3253505E1B103JZMB

(C1206K103J1EML)



SMD MIL COG PRF32535, Ceramic, 0.01 uF, 5%, 100 VDC, COG, SMD, Low ESR, MIL-PRF-32535, N/A, 1206



Dimensions		
Chip Size	1206	
L	3.2mm +/-0.25mm	
	(0.126 in +/-0.01 in)	
w	1.6mm +/-0.25mm	
	(0.063 in +/-0.01 in)	
Т	1.78mm MAX (0.07 in MAX)	
В	0.51mm +/-0.36mm	
	(0.02 in +/-0.014 in)	

Packaging Specifications		
Packaging:	Waffle	
Packaging Quantity:	126	

General Information	
Series:	SMD MIL COG PRF32535
Style:	SMD Chip
Description:	SMD, Low ESR, MIL-PRF-32535
RoHS:	No
Prop 65:	warning: Cancer and reproductive harm - www.p65warnings.ca.gov.
REACH:	SVHC (Pb – CAS 7439-92-1)
SCIP Number:	d66873f5-e54d-410c-a0cf- ebf6fcf635b5
Termination:	Solder Plated
Failure Rate:	N/A
Qualifications:	MIL-PRF-32535 M-Level
AEC-Q200:	No
Shelf Life:	78 Weeks
MSL:	1

Specifications		
Capacitance:	0.01 uF	
Capacitance Tolerance:	5%	
Voltage DC:	100 VDC	
Dielectric Withstanding Voltage:	250 VDC	
Temperature Range:	-55/+125°C	
Temperature Coefficient:	COG	
Dissipation Factor:	0.15% 1 MHz 25C	
Aging Rate:	0% Loss/Decade Hour	
Insulation Resistance:	100 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

