KEMET Part Number: M3253506E1B103JZMB

(C1210K103J1EML)



SMD MIL COG PRF32535, Ceramic, 0.01 uF, 5%, 100 VDC, COG, SMD, Low ESR, MIL-PRF-32535, N/A, 1210



Dimensions		
Chip Size	1210	
L	3.2mm +/-0.25mm	
	(0.126 in +/-0.01 in)	
w	2.49mm +/-0.25mm	
	(0.098 in +/-0.01 in)	
Т	2.79mm MAX (0.11 in MAX)	
В	0.51mm +/-0.36mm	
	(0.02 in +/-0.014 in)	

Packaging Specifications		
Packaging:	Waffle	
Packaging Quantity:	80	

General Information		
Series:	SMD MIL COG PRF32535	
Style:	SMD Chip	
Description:	SMD, Low ESR, MIL-PRF-32535	
RoHS:	No	
Prop 65:	warning: Cancer and reproductive harm - www.p65warnings.ca.gov.	
REACH:	SVHC (Pb – CAS 7439-92-1)	
SCIP Number:	d66873f5-e54d-410c-a0cf- ebf6fcf635b5	
Termination:	Solder Plated	
Failure Rate:	N/A	
Qualifications:	MIL-PRF-32535 M-Level	
AEC-Q200:	No	
Shelf Life:	78 Weeks	
MSL:	1	

Specifications		
Capacitance:	0.01 uF	
Capacitance Tolerance:	5%	
Voltage DC:	100 VDC	
Dielectric Withstanding Voltage:	250 VDC	
Temperature Range:	-55/+125°C	
Temperature Coefficient:	COG	
Dissipation Factor:	0.15% 1 MHz 25C	
Aging Rate:	0% Loss/Decade Hour	
Insulation Resistance:	100 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

