
## **KEMET Part Number: CKC21X473GWGACTU**

(CKC21X473GWGAC7800)



KC Link Auto COG, Ceramic, 0.047 uF, 2%, 650 VDC, COG, SMD, MLCC, FT-CAP, Ultra-Stable, 2220



Dimensions		
Chip Size	2220	
L	6.1mm +/-0.75mm	
W	5mm +/-0.4mm	
Т	1.4mm +/-0.15mm	
В	0.7mm +/-0.35mm	

Packaging Specifications		
Weight:	190 mg	
Packaging:	T&R, 180mm, Plastic Tape	
Packaging Quantity:	1000	

General Information		
Series:	KC Link Auto C0G	
Style:	SMD Chip	
Description:	SMD, MLCC, FT-CAP, Ultra- Stable	
Features:	FT-CAP, Ultra-Stable	
RoHS:	Yes	
Termination:	Flexible Termination	
Marking:	No	
Qualifications:	AEC-Q200	
AEC-Q200:	Yes	
Shelf Life:	78 Weeks	
MSL:	1	

Specifications	
Capacitance:	0.047 uF
Measurement Condition:	1 kHz 1.0Vrms
Capacitance Tolerance:	2%
Voltage DC:	650 VDC
Dielectric Withstanding Voltage:	845 VDC
Temperature Range:	-55/+150°C
Temperature Coefficient:	COG
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC):	30 ppm/C, 1kHz 1.0Vrms
Dissipation Factor:	0.1% 1 kHz 1.0Vrms
Aging Rate:	0% Loss/Decade Hour
Insulation Resistance:	21.2766 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

