



KPS SMD Comm X7R SnPb, Ceramic, 4.7 uF, 20%, 100 VDC, X7R, 2220-2

TOP VIEW
Single or Double Chip Stack



SIDE VIEW
Double Chip Stack



Dimensions

| | |
|----------|----------------|
| L | 6mm +/-0.5mm |
| W | 5mm +/-0.5mm |
| T | 5mm +/-0.50mm |
| B | 1.6mm +/-0.3mm |

Packaging Specifications

| | |
|----------------------------|--------------------------|
| Weight: | 390 mg |
| Packaging: | T&R, 180mm, Plastic Tape |
| Packaging Quantity: | 200 |

General Information

| | |
|---------------------|---|
| Series: | KPS SMD Comm X7R SnPb |
| Style: | Stacked Chip |
| Description: | SMD, MLCC, Stacked, Double Chip, Temperature Stable |
| Features: | Temperature Stable |
| RoHS: | No |
| Prop 65: | WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov . |
| REACH: | SVHC (Pb – CAS 7439-92-1) |
| SCIP Number: | 795b247e-78a9-405c-8728-223c2d9782a2 |
| Termination: | Lead (SnPb) |
| AEC-Q200: | No |
| Chip Size: | 2220-2 |
| Shelf Life: | 78 Weeks |
| MSL: | 1 |

Specifications

| | |
|--|---|
| Capacitance: | 4.7 uF |
| Measurement Condition: | 1 kHz 1.0Vrms |
| Capacitance Tolerance: | 20% |
| Voltage DC: | 100 VDC |
| Dielectric Withstanding Voltage: | 250 VDC |
| Temperature Range: | -55/+125°C |
| Temperature Coefficient: | X7R |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC): | 15%, 1kHz 1.0Vrms |
| Dissipation Factor: | 2.5% 1 kHz 1.0Vrms |
| Aging Rate: | 3% Loss/Decade Hour: Referee Time is 1000 Hours |
| Insulation Resistance: | 212.8 MOhms |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.