


# STS23 2XXXUXXX

## TVS Diode array ESD suppressor



### Product features

- 350 Watts peak pulse power per line ( $t_P = 8/20 \mu s$ )
- Protects two I/O lines with uni-directional
- Low clamping voltage
- Low leakage current
- Meets moisture sensitivity level (MSL) 3
- Molding compound flammability rating: UL 94V-0
- Termination finish: Tin

### Applications


- RS-232, RS-422 & RS-485
- Servers, notebook, and desktop
- Cellular handsets and accessories
- Control & monitoring systems
- Portable electronics
- Wireless bus protection
- Set-top box

### Environmental compliance and general specifications


- IEC61000-4-2 (ESD)
  - Up to  $\pm 15$  kV (air)
  - Up to  $\pm 8$  kV (contact)
- IEC61000-4-5 (Lightning) Up to 180 A (8/20  $\mu s$ )




### Ordering part number



### Pin out/functional diagram



SOT-23



Pin Configuration



Powering Business Worldwide

### Absolute maximum ratings

(+25 °C, RH=45%-75%, unless otherwise noted)

Parameter	Symbol	Value	Unit
Peak pulse power dissipation on 8/20 μs waveform	$P_{pp}$	350	W
ESD per IEC 61000-4-2 (Air)	$V_{ESD}$	+/-15	kV
ESD per IEC 61000-4-2 (Contact)		+/-8	
Lead soldering temperature	$T_L$	+260 (10 seconds)	°C
Operating junction temperature range	$T_J$	-55 to +125	°C
Storage temperature range	$T_{STG}$	-55 to +150	°C

### Electrical characteristics

(+25 °C)

#### STS232050U152

Parameter	Test condition	Minimum	Typical	Maximum	Symbol (Units)
Reverse working voltage	-	-	-	5.0	$V_{RWM}$ (V)
Reverse breakdown voltage	$I_T = 1$ mA	6.0	-	-	$V_{BR}$ (V)
Reverse leakage current	$V_{RWM} = 5$ V	-	-	1	$I_R$ (μA)
Clamping voltage	$I_{pp} = 1$ A, $t_p = 8/20$ μs	-	-	9.8	$V_C$ (V)
	$I_{pp} = 18$ A, $t_p = 8/20$ μs	-	-	16.7	$V_C$ (V)
Junction capacitance	$V_{RWM} = 0$ V, $f = 1$ MHz	-	150	180	$C_J$ (pF)

#### STS232120U581

Parameter	Test condition	Minimum	Typical	Maximum	Symbol (Units)
Reverse working voltage	-	-	-	12	$V_{RWM}$ (V)
Reverse breakdown voltage	$I_T = 1$ mA	13.3	-	-	$V_{BR}$ (V)
Reverse leakage current	$V_{RWM} = 12$ V	-	-	1	$I_R$ (μA)
Clamping voltage	$I_{pp} = 1$ A, $t_p = 8/20$ μs	-	-	19	$V_C$ (V)
	$I_{pp} = 12$ A, $t_p = 8/20$ μs	-	-	25	$V_C$ (V)
Junction capacitance	$V_{RWM} = 0$ V, $f = 1$ MHz	-	58	70	$C_J$ (pF)

#### STS232150U451

Parameter	Test condition	Minimum	Typical	Maximum	Symbol (Units)
Reverse working voltage	-	-	-	15	$V_{RWM}$ (V)
Reverse breakdown voltage	$I_T = 1$ mA	16.7	-	-	$V_{BR}$ (V)
Reverse leakage current	$V_{RWM} = 15$ V	-	-	1	$I_R$ (μA)
Clamping voltage	$I_{pp} = 1$ A, $t_p = 8/20$ μs	-	-	24	$V_C$ (V)
	$I_{pp} = 10$ A, $t_p = 8/20$ μs	-	-	35	$V_C$ (V)
Junction capacitance	$V_{RWM} = 0$ V, $f = 1$ MHz	-	45	-	$C_J$ (pF)


**STS232240U301**

Parameter	Test condition	Minimum	Typical	Maximum	Symbol (Units)
Reverse working voltage	-	-	-	24	$V_{RWM}$ (V)
Reverse breakdown voltage	$I_T = 1$ mA	26.7	-	-	$V_{BR}$ (V)
Reverse leakage current	$V_{RWM} = 24$ V	-	-	1	$I_R$ ( $\mu$ A)
Clamping voltage	$I_{PP} = 1$ A, $t_p = 8/20$ $\mu$ s	-	-	43	$V_C$ (V)
	$I_{PP} = 5$ A, $t_p = 8/20$ $\mu$ s	-	-	55	$V_C$ (V)
Junction capacitance	$V_{RWM} = 0$ V, $f = 1$ MHz	-	30	-	$C_J$ (pF)

**STS232360U261**


Parameter	Test condition	Minimum	Typical	Maximum	Symbol (Units)
Reverse working voltage	-	-	-	36	$V_{RWM}$ (V)
Reverse breakdown voltage	$I_T = 1$ mA	40	-	-	$V_{BR}$ (V)
Reverse leakage current	$V_{RWM} = 36$ V	-	-	1	$I_R$ ( $\mu$ A)
Clamping voltage	$I_{PP} = 1$ A, $t_p = 8/20$ $\mu$ s	-	-	60	$V_C$ (V)
	$I_{PP} = 4$ A, $t_p = 8/20$ $\mu$ s	-	-	75	$V_C$ (V)
Junction capacitance	$V_{RWM} = 0$ V, $f = 1$ MHz	-	26	-	$C_J$ (pF)

**Mechanical parameters, pad layout- mm/inches**




Dimension	Millimeters		Inches	
	Minimum	Maximum	Minimum	Maximum
A	0.90	1.15	0.035	0.045
A1	0.00	0.10	0.000	0.004
b	0.25	0.325	0.010	0.013
C	0.22	0.25	0.009	0.010
D	2.80	3.00	0.110	0.118
e	1.80	1.90	0.071	0.075
E	1.20	1.40	0.047	0.055
L	0.30	0.50	0.012	0.020
He	2.25	2.55	0.089	0.100
X	0.80 typ		0.031 typ	
X1	0.95 typ		0.037 typ	
Y	0.80 typ		0.031 typ	
Z	2.02 typ		0.080 typ	


**Part marking**




(STS232050U152)




(STS232120U581)



(STS232150U451)



(STS232240U301)




(STS232360U261)

**Packaging information mm/inches**

Drawing not to scale.


Supplied in tape and reel packaging, 3,000 parts per 7" diameter reel (EIA-481 compliant)




Symbol	Millimeters	Inches
	Typ.	Typ.
A	3.15	0.124
B	2.77	0.109
C	1.22	0.048
d	Φ1.50	Φ0.059
E	1.75	0.069
F	3.50	0.138
P0	4.00	0.157
P	4.00	0.157
P1	2.00	0.079
W	8.00	0.315
D	Φ178	Φ7.008
D1	54.40	2.142
D2	13.00	0.512
G	R78.00	R3.071
H	R25.60	R1.008
I	R6.50	R0.256
W1	9.50	0.374
W2	12.30	0.484

**Ratings and V-I characteristic curves** (+25 °C unless otherwise noted)


**V- I curve characteristics (Uni-directional)**




**Pulse waveform (8/20  $\mu$ s)**



**Pulse derating curve**



**ESD waveform**



Solder reflow profile




Table 1 - Standard SnPb solder (T<sub>c</sub>)

Package thickness	Volume mm <sup>3</sup> <350	Volume mm <sup>3</sup> ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2 - Lead (Pb) free solder (T<sub>c</sub>)

Package thickness	Volume mm <sup>3</sup> <350	Volume mm <sup>3</sup> 350 - 2000	Volume mm <sup>3</sup> >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 – 2.5 mm	260 °C	250 °C	245 °C
>2.5 mm	250 °C	245 °C	245 °C

Reference J-STD-020

Profile feature	Standard SnPb solder	Lead (Pb) free solder
Preheat and soak		
• Temperature min. (T <sub>smin</sub> )	100 °C	150 °C
• Temperature max. (T <sub>smax</sub> )	150 °C	200 °C
• Time (T <sub>smin</sub> to T <sub>smax</sub> ) (t <sub>s</sub> )	60-120 seconds	60-120 seconds
Ramp up rate T <sub>L</sub> to T <sub>p</sub>	3 °C/ second max.	3 °C/ second max.
Liquidous temperature (T <sub>L</sub> )	183 °C	217 °C
Time (t <sub>L</sub> ) maintained above T <sub>L</sub>	60-150 seconds	60-150 seconds
Peak package body temperature (T <sub>p</sub> )*	Table 1	Table 2
Time (t <sub>p</sub> )* within 5 °C of the specified classification temperature (T <sub>c</sub> )	20 seconds*	30 seconds*
Ramp-down rate (T <sub>p</sub> to T <sub>L</sub> )	6 °C/ second max.	6 °C/ second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

\* Tolerance for peak profile temperature (T<sub>p</sub>) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

**Eaton**  
Electronics Division  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
Eaton.com/electronics

© 2020 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. 11148 BU-MC20130  
September 2020

Eaton is a registered trademark.  
All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.







