

TO. : \_\_\_\_\_




NO. : \_\_\_\_\_



# APPROVAL SHEET

MULTILAYER CERAMIC CAPACITOR  
Commercial Grade  
(High Voltage Type (100V~3000V))

Approved by customer : (signing or stamping here)

SAMWHA CAPACITOR CO., LTD.		
Writtern by	Checked by	Approved by
		

2020. 02. 13.



**SAMWHA CAPACITOR CO., LTD.**

Address : 124, BUK-RI, NAMSA-MYUN YOUNGIN-SI, KYUNGKI-DO, KOREA

Contact : TEL 82-31-332-6441 , FAX 82-31-332-7661

Home page : [www.samwha.com](http://www.samwha.com)

## < SPEC SUMMARY >

SAMWHA Part no.	CS3216X7R225K101NRI		
Type	High voltage		
Item	Specification	Unit	Test methods and Conditions(Capacitance,IR)
Capacitance	2.2	$\mu F$	Testing Frequency : 1 $\pm$ 0.2kHz Testing Voltage : 1 $\pm$ 0.2Vrms
Capacitance Tolerance	$\pm 10$	%	
Dissipation Factor	Max. 5	%	
Insulation Resistance	More than 45,4	M $\Omega$	Applied the rated voltage for 2 minutes of charging.
Chip Size	3.20 $\pm$ 0.30	L (mm)	*Capacitance Tolerance Code --- page 1/9 *Chip size ----- page 2/9 *Characteristics & Test Method ---- page 3/9~6/9
	1.60 $\pm$ 0.30	W (mm)	
	1.60 $\pm$ 0.30	T (mm)	

Enactment : March 27,1996	STANDARD	NO	SW - M - 04B
	MULTILAYER CERAMIC CAPACITOR Commercial Grade	Page	1 / 9

## 1. General Article

### Application Range

These specifications refer to the "Multilayer Ceramic Capacitors "mainly used to the computer equipment, communication equipment.

**\*Caution : Industrial equipment / For the high reliability equipment / LED equipment / Etc.**  
**Please contact sales representatives or product engineers before using the products.**  
**(For details, please refer Page 9)**

## 2. General Code

### (1) Type Designation

<u>CS</u>	<u>3216</u>	<u>X7R</u>	<u>225</u>	<u>K</u>	<u>101</u>	<u>N</u>	<u>R</u>	<u>I</u>
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)

1) Multilayer Ceramic Capacitor (Commercial Grade)

2) Size Code :

This is expressed in tens of a millimeter.

The first two digits are the length, The last two digits are width.

3) Temperature Coefficient Code

Classification	Code	Temperature Range	Capacitance Tolerance
Class I	C0G	-55 to +125℃	±30 ppm/℃
Class II	X5R	-55 to +85℃	±15%
	X7R	-55 to +125℃	±15%
	Y5V	-30 to +85℃	+22% ~ -82%

4) Capacitance Code(Pico farads) :

The nominal Capacitance Value in pF is expressed by three digit numbers.

The first two digits represents significant figures and the last digit denotes the number of zero

ex) 104 = 100000 pF

R denotes decimal

8R2 = 8.2 pF

5) Capacitance Tolerance Code

Code	Tolerance
B	± 0.1 pF
C	± 0.25 pF
D	± 0.5 pF
F	± 1.0 %
G	± 2.0 %
J	± 5 %
K	± 10 %

Code	Tolerance
M	± 20 %
P	+ 100, - 0%
Z	+ 80, - 20%
H	+ 0.25/-0 pF
I	+ 0/-0.25 pF
U	+ 5/-0 %
V	+ 0/-5 %

## 6) Voltage Code

code	6R3	100	160	250	350	500	101	201	251	501	631	102	202	302
Vol.	DC 6.3V	DC 10V	DC 16V	DC 25V	DC 35V	DC 50V	DC 100V	DC 200V	DC 250V	DC 500V	DC 630V	DC 1KV	DC 2KV	DC 3KV

## 7) Termination Code

ex) N : Ni-Sn (Nickel-Tin Plate)

A : Ag/Ni-Sn (Ag Epoxy/Nickel-Tin Plate) -> **Soft Termination Type**

## 8) Packing Code

ex) R : 7" Reel Type

L : 13" Reel Type

B : Bulk Type

## 9) Thickness option


Thickness(mm)		Code
t	Tol(±)	
1.60	0.30	I

## 3. Temperature Characteristics

See Page 3/9 (No.7)

## 4. Constructions and Dimensions

(I) Dimensions



(Unit : mm)




Code	Dimension							
	Length		Width		Thickness		T1(min)	G(min)
	L	Tol(±)	W	Tol(±)	T	Tol(±)		
3216	3.20	0.30	1.60	0.30	1.60	0.30	0.15	1.00

## (2) Construction of Termination



## Specifications and Test Methods (High voltage type)

No.	Item	Specification		Test Methods and Conditions																		
		Class I	Class II																			
1	Operating Temperature Range	C0G :-55 to+125℃	X7R : -55 to +125℃																			
2	Dimensions	Within the specified dimension		Using calipers																		
3	Dielectric Strength	No defects or abnormalities		<p>No failure should be observed when voltage in table is applied between the terminations, provided the charge/discharge current is less than 50mA.</p> <table><tr><th>Cap.</th><th>Rated voltage</th><th>Test voltage</th><th>Time</th></tr><tr><td rowspan="3">C0G</td><td>DC100V~630V</td><td>150% of the rated voltage</td><td rowspan="6">1to5 sec.</td></tr><tr><td>DC1kV, DC2kV DC3kV, DC3.15kV</td><td>120% of the rated voltage</td></tr><tr><td rowspan="3">X7R</td><td>DC100V~630V</td><td>150% of the rated voltage</td></tr><tr><td>DC1kV</td><td rowspan="2">120% of the rated voltage</td></tr><tr><td>DC2kV</td></tr><tr><td></td><td>DC3kV</td></tr></table>	Cap.	Rated voltage	Test voltage	Time	C0G	DC100V~630V	150% of the rated voltage	1to5 sec.	DC1kV, DC2kV DC3kV, DC3.15kV	120% of the rated voltage	X7R	DC100V~630V	150% of the rated voltage	DC1kV	120% of the rated voltage	DC2kV		DC3kV
Cap.	Rated voltage	Test voltage	Time																			
C0G	DC100V~630V	150% of the rated voltage	1to5 sec.																			
	DC1kV, DC2kV DC3kV, DC3.15kV	120% of the rated voltage																				
	X7R	DC100V~630V		150% of the rated voltage																		
DC1kV		120% of the rated voltage																				
DC2kV																						
	DC3kV																					
4	Insulation Resistance	More than 10,000 MΩ	-DC100V~1KV :C≥0.01μF:More than 100MΩ·μF :C<0.01μF:More than 10,000MΩ -DC2~3KV:More than6,000 MΩ	Rated voltage <DC500V : Applied the rated voltage for 2 minutes of charging. Rated voltage ≥DC500V : The insulation resistance should be measured with DC500±50V and within 2 minutes of charging.																		
5	Capacitance	within the specified tolerance		<table><tr><th>Cap</th><th>Testing frequency</th><th>Testing Voltage</th><th>Measure temperature</th></tr><tr><td>C0G</td><td>1±0.2MHz(C&lt;1000pF) 1±0.1kHz(C≥1000pF)</td><td rowspan="2">AC 1±0.2Vrms</td><td rowspan="2">25℃</td></tr><tr><td>X7R</td><td>1±0.2kHz</td></tr></table>	Cap	Testing frequency	Testing Voltage	Measure temperature	C0G	1±0.2MHz(C<1000pF) 1±0.1kHz(C≥1000pF)	AC 1±0.2Vrms	25℃	X7R	1±0.2kHz								
Cap	Testing frequency	Testing Voltage	Measure temperature																			
C0G	1±0.2MHz(C<1000pF) 1±0.1kHz(C≥1000pF)	AC 1±0.2Vrms	25℃																			
X7R	1±0.2kHz																					
6	Dissipation Factor(D.F.)	C0G Char. : 30pFmin : Q≥1,000(DF≤0.1%) 30pFmax : Q≥400+20C (DF≤1/ (400+20C))	5% max	<ul style="list-style-type: none"><li>Initial measurement Perform the initial measurement according to Note1 for Class II</li><li>Measurement after test Take it out and set it for 24±2 hours (Class I ) or 24±2 hours (Class II) then measure</li></ul>																		
7	Capacitance Temperature Characteristics	Temp. Coefficient C0G char. : 0±30ppm/℃ (Temp. Range : -55to+125℃)	Cap. Change within ±15% (Temp. Range : -55 to +125℃)	<p>C0G : The temperature coefficient is determined using the capacitance measured in step 3 as a reference. When cycling the temperature sequentially from step 1 through 5 the capacitance should be within the specified tolerance for the temperature coefficient.</p> <table><tr><th>Step</th><th>Temperature(℃)</th></tr><tr><td>1</td><td>25±2</td></tr><tr><td>2</td><td>-55±3</td></tr><tr><td>3</td><td>25±2</td></tr><tr><td>4</td><td>125±3 (for C0G)</td></tr><tr><td>5</td><td>25±2</td></tr></table> <p>X7R : The range of capacitance change compared with the 25℃value should be within the specified range. -Pretreatment Perform a heat treatment at 150 -10, +0℃ for 60±5min. and then let sit for 24±2hrs.(Class I ), 24±2hrs.(Class II ) at room Temperature</p>	Step	Temperature(℃)	1	25±2	2	-55±3	3	25±2	4	125±3 (for C0G)	5	25±2						
Step	Temperature(℃)																					
1	25±2																					
2	-55±3																					
3	25±2																					
4	125±3 (for C0G)																					
5	25±2																					

No.	Item	Specification		Test Methods and Conditions																																			
		Class I	Class II																																				
8	Adhesive Strength of Termination	No removal of the terminations or other defect should occur		<p>Solder the capacitor to the testing jig(glass epoxy board) shown in Fig. 1 using a eutectic solder. Then apply 10N force in the direction of the arrow. The soldering should be done either with an iron or using the reflow method and should be conducted with care so that the soldering is uniform and free of defects such as heat shock.</p> <div><p>10N(5N:Size 1.6×0.8mm only), 10±1s Speed : 1.0mm/s Glass Epoxy Board</p></div>																																			
9	Vibration Resistance	Appearance	No defects or abnormalities		<p>The capacitor should be subjected to a simple harmonic motion having a total amplitude of 1.5mm, the frequency being varied uniformly between the approximate limits of 10 and 55Hz. The frequency range, from 10 to 55Hz and return to 10Hz, should be traversed in approximately 1 min. This motion should be applied for a period of 2hrs. in each 3mutually perpendicular directions(total of 6hrs.)</p>																																		
		Capacitance	Within the specified tolerance																																				
		Dissipation Factor(or Q)	<p>COG Char. : 30pFmin : <math>Q \geq 1,000(DF \leq 0.1\%)</math> 30pFmax : <math>Q \geq 400+20C</math> (<math>DF \leq 1/ (400+20C)</math>)</p>	5% max																																			
10	Bending strength	No cracking defects should occur.		<p>Solder the capacitor to the testing jig (glass epoxy board) shown in Fig. 2 using a eutectic solder. Then apply a force in the direction shown in Fig. 3. The soldering should be done either with an iron or using the reflow method and should be conducted with care so that the soldering is uniform and free of defects such as heat shock.</p> <div><table><tr><th>L×X (mm)</th><th colspan="4">Dimension(mm)</th></tr><tr><th></th><th>a</th><th>b</th><th>c</th><th>d</th></tr><tr><td>1.6×0.8</td><td>1.0</td><td>3.0</td><td>1.2</td><td rowspan="6">1.0</td></tr><tr><td>2.0×1.25</td><td>1.2</td><td>4.0</td><td>1.65</td></tr><tr><td>3.2×1.6</td><td>2.2</td><td>5.0</td><td>2.0</td></tr><tr><td>3.2×2.5</td><td>2.2</td><td>5.0</td><td>2.9</td></tr><tr><td>4.5×2.0</td><td>3.5</td><td>7.0</td><td>2.4</td></tr><tr><td>4.5×3.2</td><td>3.5</td><td>7.0</td><td>3.7</td></tr></table><div><p>20 50 Pressurizing speed : 1.0mm/s Pressurize R230 Capacitance meter Flexure=1 (in mm)</p></div><p>*. Test condition</p><ul style="list-style-type: none"><li>- Bending limit : 1mm</li><li>- Pressurizing speed : 1mm/sec</li><li>- Holding time : 5±1sec</li></ul></div>	L×X (mm)	Dimension(mm)					a	b	c	d	1.6×0.8	1.0	3.0	1.2	1.0	2.0×1.25	1.2	4.0	1.65	3.2×1.6	2.2	5.0	2.0	3.2×2.5	2.2	5.0	2.9	4.5×2.0	3.5	7.0	2.4	4.5×3.2	3.5	7.0	3.7
L×X (mm)	Dimension(mm)																																						
	a	b	c	d																																			
1.6×0.8	1.0	3.0	1.2	1.0																																			
2.0×1.25	1.2	4.0	1.65																																				
3.2×1.6	2.2	5.0	2.0																																				
3.2×2.5	2.2	5.0	2.9																																				
4.5×2.0	3.5	7.0	2.4																																				
4.5×3.2	3.5	7.0	3.7																																				
11	Solderability of Termination	75% of the terminations are to be soldered evenly and continuously.		<p>Immerse the capacitor in a solution of ethanol and rosin(25% rosin in weight proportion). Immerse in eutectic solder solution for 2±0.5 sec. at 245±5℃. Immersing speed : 25±2.5mm/s</p>																																			

No.	Item	Specification		Test Methods and Conditions															
		Class I	Class II																
12	Resistance to Soldering Heat	Appearance	No defects which may affect performance																
		Capacitance change	within ±2.5%or ±0.25pF (whichever is larger)	within ±10%															
		Dissipation Factor (or Q)	COG Char. : 30pFmin : Q≥1,000(DF≤0.1%) 30pFmax : Q≥400+20C (DF≤1/ (400+20C))	5% max															
		I.R.	More than 10,000MΩ	-DC100V~1KV :C≥0.01μF:More than 100MΩ·μF :C<0.01μF:More than 10,000MΩ -DC2~3KV:More than1,000 MΩ															
				Preheat the capacitor at 120 to 150℃* for 1 min. Immerse the capacitor in eutectic solder solution at 260±5℃ for 10±1 sec.  -Immersing speed : 25±2.5mm/s -Initial measurement Perform the initial measurement according to Note1 for Class II -Measurement after test Let sit at room Temperature for 24±2hrs.(Class I ), 24±2hrs.(Class II ) then measure. *Preheating for more than 3.2×2.5mm															
				<table><tr><td>Step</td><td>Temperature</td><td>Time</td></tr><tr><td>1</td><td>100℃ to 120℃</td><td>1 min</td></tr><tr><td>2</td><td>170℃ to 200℃</td><td>1 min</td></tr></table>	Step	Temperature	Time	1	100℃ to 120℃	1 min	2	170℃ to 200℃	1 min						
Step	Temperature	Time																	
1	100℃ to 120℃	1 min																	
2	170℃ to 200℃	1 min																	
13	Temperature Cycle	Appearance	No defects which may affect performance																
		Capacitance Change	Within ±2.5%or ±0.25pF (whichever is larger)	within ±15%															
		Dissipation Factor (or Q)	COG Char. : 30pFmin : Q≥1,000(DF≤0.1%) 30pFmax : Q≥400+20C (DF≤1/ (400+20C))	5% max															
		I.R	More than 10,000MΩ	-DC100V~1KV :C≥0.01μF:More than 100MΩ·μF :C<0.01μF:More than 10,000MΩ -DC2~3KV:More than 3,000MΩ															
				Perform the 5 cycles according to the 4 heat treatments listed in the following table.															
				<table><tr><td>Step</td><td>1</td><td>2</td><td>3</td><td>4</td></tr><tr><td>Temp (℃)</td><td>Min. operating temp. ±3</td><td>Room Temp</td><td>Max. operating temp. ±2</td><td>Room Temp</td></tr><tr><td>Time (min)</td><td>30±3</td><td>2 to3</td><td>30±3</td><td>2 to3</td></tr></table>	Step	1	2	3	4	Temp (℃)	Min. operating temp. ±3	Room Temp	Max. operating temp. ±2	Room Temp	Time (min)	30±3	2 to3	30±3	2 to3
Step	1	2	3	4															
Temp (℃)	Min. operating temp. ±3	Room Temp	Max. operating temp. ±2	Room Temp															
Time (min)	30±3	2 to3	30±3	2 to3															
				-Initial measurement Perform the initial measurement according to Note1 for Class II -Measurement after test Perform the final measurement according to Note2															
14	Humidity (Steady State)	Appearance	No defects which may affect performance																
		Capacitance Change	within ±5% or ±0.5pF (Whichever is larger)	Within ±15%															
		Dissipation Factor (or Q)	COG Char. : C≥30pF : Q≥350 C<30pF : Q≥275+ $\frac{5}{2}/C$	7.5% max															
		I.R	More than 1,000MΩ	-DC100V~1KV :C≥0.01μF:More than 10MΩ·μF :C<0.01μF:More than 1,000MΩ -DC2~3KV:More than 1,000MΩ															
				Let the capacitor sit at 40±2℃ and relative humidity of 90 to 95% for 500+24/-0 hrs.  -Initial measurement Perform the initial measurement according to Note1 for Class II -Measurement after test Perform the final measurement according to Note2															
15	High Temperature Load	Appearance	No defects which may affect performance																
		Capacitance Change	within ±3% or ±0.3pF (Whichever is larger)	DC100V,630V:Within ±15% DC1KV:Within ±20% DC2~3KV:Within ±20%															
		Dissipation (or Q)	COG Char. : C≥30pF : Q≥350 C<30pF : Q≥275+ $\frac{5}{2}/C$	7.5% max															
		I.R.	More than 1,000MΩ	-DC100V~1KV :C≥0.01μF:More than 10MΩ·μF :C<0.01μF:More than 1,000MΩ -DC2~3KV:More than 2,000MΩ															
				Apply the voltage in following table for 1,000+48/-0hrs. at maximum operating temperature ±3℃.  The charge/discharge current is less than 50mA.															
				<table><tr><td>Operating temperature range</td><td>Rated voltage</td><td>Test voltage</td></tr><tr><td rowspan="2">COG</td><td>Rated voltage ≥DC1KV</td><td>Rated voltage</td></tr><tr><td>Rated voltage &lt;DC1KV</td><td>120% of the rated voltage</td></tr><tr><td rowspan="3">X7R</td><td>DC100V~250V</td><td>150% of the rated voltage</td></tr><tr><td>DC500V~630V</td><td>120% of the rated voltage</td></tr><tr><td>DC1KV~DC3KV</td><td>110% of the rated voltage</td></tr></table>	Operating temperature range	Rated voltage	Test voltage	COG	Rated voltage ≥DC1KV	Rated voltage	Rated voltage <DC1KV	120% of the rated voltage	X7R	DC100V~250V	150% of the rated voltage	DC500V~630V	120% of the rated voltage	DC1KV~DC3KV	110% of the rated voltage
Operating temperature range	Rated voltage	Test voltage																	
COG	Rated voltage ≥DC1KV	Rated voltage																	
	Rated voltage <DC1KV	120% of the rated voltage																	
X7R	DC100V~250V	150% of the rated voltage																	
	DC500V~630V	120% of the rated voltage																	
	DC1KV~DC3KV	110% of the rated voltage																	
				-Initial measurement Perform the initial measurement according to Note1 for Class II -Measurement after test Perform the final measurement according to Note2															

No.	Item		Specification		Test Methods and Conditions
			Class I	Class II	
16	Humidity Load (Application : DC250V item)	Appearance		No defects which may affect performance	Apply the rated voltage at $40\pm 2^{\circ}\text{C}$ and relative humidity of 90 to 95 for $500\pm 24/-0$ hrs. ·Initial measurement Perform the initial measurement according to Note1 for Class II ·Measurement after test Perform the final measurement according to Note2
		Capacitance Change		Within $\pm 15\%$	
		Dissipation (or Q)		7.5% max	
		I.R.		$C \geq 0.01\mu\text{F}$ : More than $10\text{M}\Omega$ , $\mu\text{F}$ $C < 0.01\mu\text{F}$ : More than $1,000\text{M}\Omega$	

\*Note1. Initial Measurement for Class II

Perform a heat treatment at  $150\pm 0, -10^{\circ}\text{C}$  for one hour and then let sit for  $24\pm 2$  hours at room temperature, then measure

\*Note2. Measurement after test

1. Class I

Let sit for  $24\pm 2$  hours at room temperature, then measurement

2. Class II

Perform a heat treatment at  $150\pm 0, -10^{\circ}\text{C}$  for one hour and then let sit for  $24\pm 2$  hours at room temperature, then measure.



## 5. Packing


### (1) Bulk packing

- ① 1000 pcs per Polybag
- ② 5 Polybags per Inner box
- ③ 10 Inner boxes per Out box

### (2) Reel Packing

- ① 8~10 Reels per Inner box
- ② 6 Inner boxes per Out box

### (3) Reel Dimensions




(Unit : mm)

MARK	SIZE	A	B	C	D	E	W
7 " REEL	0603~3225	$\Phi 178 \pm 2$	$\Phi 50 \text{Min}$	$\Phi 13 \pm 0.5$	$\Phi 21 \pm 0.8$	$2 \pm 0.5$	$10 \pm 1.5$
	4520~4532	$\Phi 180 +0, -3$	$\Phi 60 -0, +1$	$\Phi 13 \pm 0.2$	$\Phi 57 -0 +1$	$3 \pm 0.2$	$13 \pm 0.5$
13 " REEL	1005~3225	$\Phi 330 \pm 2$	$\Phi 70 \text{Min}$	$\Phi 13 \pm 0.5$	$\Phi 21 \pm 0.8$	$2 \pm 0.5$	$10 \pm 1.5$


### (4) Number of Package

TYPE	EIA CODE	7"	13"
		Qt/REEL	Qt/REEL
CS0603	CC0201	15,000	
CS1005	CC0402	10,000	50,000
CS1608	CC0603	4,000	15,000
CS2012	CC0805	3,000 ~ 4,000	8,000 ~ 15,000
CS3216	CC1206	2,000 ~ 4,000	6,000 ~ 10,000
CS3225	CC1210	1,000 ~ 3,000	4,000 ~ 10,000
CS4520	CC1808	1,500 ~ 3,000	-
CS4532	CC1812	500 ~ 1,000	1,500 ~ 5,000

### (5) Tape Dimensions



TYPE	EIA CODE	A	B	C	D	E	F	G	H	J
CS0603	CC0201	$0.67 \pm 0.05$	$0.37 \pm 0.05$	$8.0 \pm 0.3$	$3.5 \pm 0.05$	$1.75 \pm 0.1$	$2.0 \pm 0.05$	$2.0 \pm 0.1$	$4.0 \pm 0.1$	$1.5 \pm 0.1$
CS1005	CC0402	$1.15 \pm 0.1$	$0.65 \pm 0.1$	$8.0 \pm 0.3$	$3.5 \pm 0.05$	$1.75 \pm 0.1$	$2.0 \pm 0.05$	$2.0 \pm 0.1$	$4.0 \pm 0.1$	$1.5 \pm 0.1$
CS1608	CC0603	$1.9 \pm 0.2$	$1.10 \pm 0.2$	$8.0 \pm 0.3$	$3.5 \pm 0.05$	$1.75 \pm 0.1$	$4.0 \pm 0.1$	$2.0 \pm 0.1$	$4.0 \pm 0.1$	$1.5 \pm 0.1$
CS2012	CC0805	$2.4 \pm 0.2$	$1.65 \pm 0.2$	$8.0 \pm 0.3$	$3.5 \pm 0.05$	$1.75 \pm 0.1$	$4.0 \pm 0.1$	$2.0 \pm 0.1$	$4.0 \pm 0.1$	$1.5 \pm 0.1$
CS3216	CC1206	$3.6 \pm 0.2$	$2.00 \pm 0.2$	$8.0 \pm 0.3$	$3.5 \pm 0.05$	$1.75 \pm 0.1$	$4.0 \pm 0.1$	$2.0 \pm 0.1$	$4.0 \pm 0.1$	$1.5 \pm 0.1$
CS3225	CC1210	$3.6 \pm 0.2$	$2.80 \pm 0.2$	$8.0 \pm 0.3$	$3.5 \pm 0.05$	$1.75 \pm 0.1$	$4.0 \pm 0.1$	$2.0 \pm 0.1$	$4.0 \pm 0.1$	$1.5 \pm 0.1$
CS4520	CC1808	$4.8 \pm 0.2$	$2.3 \pm 0.2$	$12.0 \pm 0.3$	$5.5 \pm 0.1$	$1.75 \pm 0.1$	$4.0 \pm 0.1$ $8.0 \pm 0.1$	$2.0 \pm 0.1$	$4.0 \pm 0.1$	$1.5 \pm 0.1$
CS4532	CC1812	$4.9 \pm 0.2$	$3.6 \pm 0.2$	$12.0 \pm 0.3$	$5.5 \pm 0.1$	$1.75 \pm 0.1$	$8.0 \pm 0.1$	$2.0 \pm 0.1$	$4.0 \pm 0.1$	$1.5 \pm 0.1$



## 6. Caution



### ► Reflow Soldering

1. The sudden temperature change easily causes mechanical damages to ceramic components. Therefore, the preheating procedures should be required for the soldering of ceramic components.
2. Please refer to the recommended soldering profiles as shown in figures, and keep the temperature difference( $\Delta T$ ) within the range recommended in Table 1.


Table 1

Size code	Temperature Difference
0603, 1005, 1608, 2012, 3216	$\Delta T \leq 190^\circ\text{C}$
3225size and over	$\Delta T \leq 130^\circ\text{C}$

### [Standard Conditions for Reflow Soldering]



### [Allowable Soldering Temperature and Time]



In case of repeated soldering, the accumulated soldering time must be within the range shown above.

### ► Storage Condition

\*When Solderability is considered, Capacitor are recommended to be used in 12 months

- (1) Temperature:  $25^\circ\text{C} \pm 10^\circ\text{C}$
- (2) Relative Humidity: Below 70% RH

### ► The Regulation of Environmental Pollution Materials.

\*Never use materials mentioned below in MLCC products regulated this document.

Pb, Cd, Hg,  $\text{Cr}^{+6}$ , PBB(Polybromide biphenyl), PBDE(Polybrominated diphenyl ethers), asbestos.

## \* Note

## (1) 'Aging'/'De-aging' Behavior of high dielectric MLCCs

(Typically represented by X7R, Y5V temperature characteristic of which main composition is BaTiO<sub>3</sub>)

'Aging' / 'De-aging' Behavior of high dielectric MLCCs Please note that high dielectric type dielectric Ceramic Capacitors have a "normal" 'aging' behavior / characteristic, that is; their capacitance value decreases with time from its value when it was first manufactured. From that date, the capacitance value begins to decrease at a logarithmic rate defined by:

$$C_t = C_{24} ( 1 - k \log_{10} t )$$


where :

$C_t$  = Capacitance Value,  $t$  hours after the start of 'aging'

$C_{24}$  = Capacitance Value, 24 hours after its manufacture

$k$  = aging constant ( capacitance decrease per decade-hour )

$t$  = time, in hours, from the start of 'aging'



The capacitance value can be restored ( a.k.a. 'de-aged' ) by exposing the component to elevated temperatures approaching its Curie Temperature ( approximately 120°C ). This 'deaging' can occur during the component's solder-assembly onto the PCB, during life or temperature cycle testing., or by ' baking ' at 150°C for about 1 hour.

- (2) Please contact our sales representatives or product engineers before using the products in this catalog for the applications listed below, which require especially high reliability for the prevention of defects which might directly damage a third party's life, body or property, or when one of our products is intended for use in applications other than those specified in this catalog.

- ① Aircraft equipment      ② Aerospace equipment      ③ Undersea equipment      ④ Power plant equipment
- ⑤ Medical equipment      ⑥ Transportation equipment (vehicles, trains, ships, etc.)
- ⑦ Traffic signal equipment      ⑧ Disaster prevention / crime prevention equipment
- ⑨ Industrial equipment (Conveyors, Robot equipment, etc)      ⑩ Led equipment
- ⑪ Application of similar complexity and/or reliability requirements to the applications listed above