

Datasheet of SAW Device


SAW Single Filter

for Band41 Full / Unbalanced / 5pin /1411

Murata PN: SAFRC2G59MD0F0A

Feature

- > New Generation for B41 Full
- ➤ High Middle Band Rejection
- Support HPUE



Note: Murata SAW Component is applicable for Cellular /Cordless phone (Terminal) relevant market only.

Please also read caution at the end of this document.





General Information

- Operating temperature :-20 to +85 deg.C Storage temperature :-40 to +85 deg.C

: +33.0dBm 5000h +50deg.C (1)(3) - Input Power

+31.5dBm 5000h +50deg.C (2)(4)

(1) applicable for W-CDMA, SC-FDMA, DFT-s-OFDM

(2) applicable for CP-OFDM

(3) 40% Duty Cycle (4) 50% Duty Cycle

(*)Input signal shall be applied to Terminal number(1).


- D.C. Volatage between the terminals : 3V (25+/-2 deg.C)

- Minimum Resistance between the terminals : 1M ohm - RoHS compliance : Yes - ESD (ElectroStatic Discharge) sensitive device



Package Dimensions & Recommended Land Pattern unit: mm

Dimensions



Marking: Laser Printing

*: Month code

\$: Date code

1 : L

2:s

Terminal Number

(1) : Unbalance Port (PA-side)


(4): Unbalance Port (Ant.-side)

Others: GND

Notice) Please refer to Measurement Circuit


for Port information in detail.

Land Pattern



UNIT : mm

Measurement Circuit (Top Thru View)



R1:50 ohm	L1 :3nH(Ideal inductor)
	C1 :1.2pF(Ideal capacitor)
R2:50 ohm	L2 :3.2nH(Ideal inductor)
	C2 :0.8pF(Ideal capacitor)



Electrical Characteristic < Item >


min. typ.* max. Center Frequency 2593 MHz					Characteristics					
Center Frequency		ltem	ltem			(-20 to +85 deg.C)			Unit	Note
						min.	typ.*	max.		
2500. 10 2515. MHz 2.1 3.2 dB 2545. 10 2545. MHz 1.7 2.8 dB 2545. 10 2575. MHz 1.6 2.8 dB 2675. 10 2675. MHz 2.1 2.8 dB 2675. 10 2675. MHz 2.1 2.8 dB 2675. 10 2690. MHz 2.1 2.8 dB 2498.5 10 2687.5 MHz 2.1 3.0 dB 2498.5 10 2687.5 MHz 2.3 3.3 dB 3.3 dB 4.3 4.5 dB 2498.5 10 2687.5 MHz 2.3 3.3 dB 4.3 4.5 dB 4.3 4.5 dB 2498.5 10 2687.5 MHz 2.3 3.3 dB dB 4.3 4.5 dB 4.3 dB	Center Frequency									
2515	Insertion Loss		to							
2545			to						_	
2575. 10 2675. MHz 2.1 2.8 dB 2498.5 to 2697.5 MHz 2.3 3.0 dB 2498.5 to 2687.5 MHz 2.3 3.3 dB _{INT} Any 4.5MHz 2498.5 to 2687.5 MHz 2.3 3.3 dB _{INT} Any 4.5MHz 2498.5 to 2690. MHz 2.3 3.0 dB _{INT} Any 4.5MHz 2498.5 to 2690. MHz 0.7 2.3 dB Any 100MHz 2496. to 2690. MHz 1.7 2.2 ANT. 2515. to 2675. MHz 1.7 2.0 ANT. 2515. to 2675. MHz 1.7 2.0 ANT. 2515. to 2675. MHz 1.7 2.0 ANT. 2515. to 2675. MHz 30 34 dB LB LB LB LB LB LB LB										
2675 10 2690 MHz 2.1 3.0 dB 2498.5 to 2687.5 MHz 2.3 3.3 dB _{NTT} Any 4.5MHz 2498.5 to 2687.5 MHz 2.3 3.0 dB _{NTT} +23 to +27deg.C, Any 4.5MHz 2515 to 2690 MHz 0.7 2.3 dB Any 20MHz 2496. to 2690 MHz 0.6 1.5 dB Any 100MHz 2496. to 2690 MHz 1.7 2.2 ANT. ANY 100MHz 2496. to 2690 MHz 1.7 2.2 ANT. 2496. to 2690 MHz 1.7 2.2 ANT. 2496. to 2690 MHz 1.7 2.2 ANT. ANY 100MHz 2515 to 2675 MHz 1.7 2.0 ANT. ANY 100MHz 2515 to 2675 MHz 1.7 2.0 ANT. ANY 100MHz 2515 to 2675 MHz 1.7 2.0 ANT. ANY 1166.22 to 1254 MHz 28 33 dB GPS L5+L2 GP							1			
2498.5 10 2687.5 MHz 2.3 3.3 dB _{NT} Any 4.5MHz 2498.5 to 2690. MHz 0.7 2.3 dB Any 20MHz 2515. to 2690. MHz 0.7 2.3 dB Any 20MHz 2496. to 2690. MHz 1.7 2.2 ANT. 2496. to 2690. MHz 1.7 2.2 ANT. 2496. to 2690. MHz 1.7 2.2 ANT. 2515. to 2675. MHz 1.7 2.2 ANT. 2515. to 2675. MHz 1.7 2.0 ANT. 2515. to 2675. MHz 3.0 34 dB LB LB LB LB LB LB LB										
Ripple Deviation										
Ripple Deviation										
VSWR 2496	D: 1 D : 1									· · ·
VSWR 2496. to 2690. MHz 1.7 2.2 ANT.	Ripple Deviation									
2496. 10 2690. MHz 1.7 2.2 TX/RX 2515. to 2675. MHz 1.7 2.0 ANT. ANT. 2515. to 2675. MHz 1.7 2.0 ANT. ANT. 2515. to 2675. MHz 1.7 2.0 TX/RX ANT. 2515. to 2675. MHz 1.7 2.0 TX/RX ANT. 2515. to 2675. MHz 28 33 dB GPS L5+L2 1559.05 to 1605.89 MHz 28 34 dB GPS L5+L2 1559.05 to 1605.89 MHz 28 34 dB GPS L1 1710. to 1785. MHz 30 36 dB B3 Tx 1805. to 1880. MHz 30 36 dB B3 Tx 1805. to 1880. MHz 30 39 dB B3 Rx 1800. to 1990. MHz 30 39 dB B1 Tx 1930. to 1990. MHz 30 39 dB B1 Tx 1930. to 1995. MHz 30 39 dB B1 Tx 1932. to 1992. MHz 30 39 dB B1 Rx 2110. to 2170. MHz 18 24 dB B1 Rx 2110. to 2170. MHz 18 24 dB B66 Rx 2110. to 2400. MHz 14 23 dB B66 Rx 2100. to 2463. MHz 30 43 dB B40 B40 2401. to 2463. MHz 30 43 dB B40 B40 2401. to 2463. MHz 30 41 dB B1 WLAN chil 1 91MHz-BW 2451. to 2473. MHz 20 37 dB B1 WLAN chil 1 91MHz-BW 2451. to 2468. MHz 30 41 dB B1 WLAN chil 1 91MHz-BW 2451. to 2468. MHz 35 41 dB B1 WLAN chil 1 91MHz-BW 2461. to 2468. MHz 35 41 dB B1 WLAN chil 1 91MHz-BW 2461. to 2468. MHz 35 41 dB B1 WLAN chil 1 91MHz-BW 2461. to 2473. MHz 20 37 dB B1 WLAN chil 1 91MHz-BW 2461. to 2473. MHz 20 37 dB B1 WLAN chil 1 91MHz-BW 2461. to 2473. MHz 20 37 dB B1 WLAN chil 1 91MHz-BW 2461. to 2473. MHz 20 37 dB B1 WLAN chil 1 91MHz-BW 2461. to 2473. MHz 20 37 dB B1 WLAN chil 1 91MHz-BW 2461. to 2473. MHz 20 37 dB B1 WLAN chil 1 91MHz-BW 2461. to 2473. MHz 20 37 dB B1 WLAN chil 1 91MHz-BW 2461. to 2473. MHz 20 37 dB B1 WLAN chil 1 91MHz-BW 2461. to 2473. MHz 20 37 dB B1 WLAN chil 1 91MHz-BW 2461. to 2473. MHz	VCMD								иь	
Absolute Attenuation	VSWK									
Absolute Attenuation Absolute Attenuation										
Absolute Attenuation 617. to 960. MHz 30 34 dB LB 1166.22 to 1254. MHz 28 33 dB GPS L5+L2 1559.05 to 1605.89 MHz 30 36 dB B3 Tx 1805. to 1880. MHz 30 39 dB B3 Tx 1805. to 1880. MHz 30 39 dB B3 Rx 1880. to 1920. MHz 30 39 dB B3 Rx 1920. to 1990. MHz 30 39 dB B3 Tx 1930. to 1995. MHz 30 39 dB B1 Tx 1930. to 1995. MHz 30 39 dB B1 Tx 1930. to 1995. MHz 30 39 dB B1 Tx 1932.5 to 1992.5 MHz 30 39 dB B1 Tx 2110. to 2200. MHz 14 23 dB B66 Rx 2112.5 to 2197.5 MHz 14 23 dB B66 Rx 2112.5 to 2197.5 MHz 14 23 dB B66 Rx 2300. to 2400. MHz 14 23 dB B66 Rx 2300. to 2400. MHz 10 16 dB B40 2401. to 2463. MHz 30 43 dB _{INT} WLAN ch1_9 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} WLAN ch1_10 19MHz-BW 2461. to 2483. MHz 30 41 dB _{INT} WLAN ch11 19MHz-BW 2461. to 2483. MHz 30 41 dB _{INT} WLAN ch11 19MHz-BW 2461. to 2483. MHz 30 41 dB _{INT} WLAN ch12 19MHz-BW 2461. to 2483. MHz 35 41 dB _{INT} +23 to +27deg.C,WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C,WLAN ch1_11 9MHz-BW 2461. to 2483. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch1_11 9MHz-BW 2461. to 2483. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch1_11 9MHz-BW 2461. to 2483. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch1_1 19MHz-BW 2461. to 2483. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch1_1 19MHz-BW 2461. to 2483. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch1_1 19MHz-BW 2461. to 2483. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch1_1 19MHz-BW 2456. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch1_1 19MHz-BW 2456. to 2478. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch1_1 19MHz-BW 2456. to 2478. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch1_1 19MHz-BW 2456. to 2478. MHz 20 27 dB n78 3800. to 3800. MHz 20 27 dB n79 4400. to 4800. MHz 20 27 dB n79 4400. to 4800. MHz 26 33 dB n79 4400. to 4800. MHz 26 33 dB n79 4400. to 4800. MHz 30 40 dB 20 5150. to 5850. MHz 30 54										
1166.22 to	Absolute Attenuation					30		2.0	dВ	
1559.05 to 1605.89 MHz	Absolute Attenuation						_			
1710. 10 1785. MHz 30 36 dB B3 Tx 1805. 10 1880. MHz 30 39 dB B3 Rx 1880. 10 1920. MHz 30 39 dB B3 Rx 1920. 10 1990. MHz 30 39 dB B1 Tx 1930. 10 1995. MHz 30 38 dB B25Rx 1932.5 10 1992.5 MHz 30 39 dB _{NT} Any 4.5MHz, B25Rx 1932.5 10 1992.5 MHz 30 39 dB _{NT} Any 4.5MHz, B25Rx 2110. 10 2170. MHz 18 24 dB B66 Rx 2112.5 10 2197.5 MHz 14 23 dB B66 Rx 2112.5 10 2197.5 MHz 14 23 dB B40 B40 2401. 10 2463. MHz 30 43 dB _{NT} WLAN ch1 9 19MHz-BW 2451. 10 2468. MHz 30 41 dB _{NT} WLAN ch1 10 19MHz-BW 2451. 10 2473. MHz 20 37 dB _{NT} WLAN ch1 10 19MHz-BW 2461. 10 2468. MHz 35 41 dB _{NT} WLAN ch13 19MHz-BW 2401. 10 2468. MHz 35 41 dB _{NT} WLAN ch3 19MHz-BW 2401. 10 2468. MHz 35 41 dB _{NT} +23 to +27deg.C, WLAN ch1 19MHz-BW 2451. 10 2468. MHz 35 41 dB _{NT} +23 to +27deg.C, WLAN ch1 19MHz-BW 2451. 10 2468. MHz 35 41 dB _{NT} +23 to +27deg.C, WLAN ch1 19MHz-BW 2451. 10 2468. MHz 35 41 dB _{NT} +23 to +27deg.C, WLAN ch1 19MHz-BW 2451. 10 2473. MHz 20 37 dB _{NT} +23 to +27deg.C, WLAN ch1 19MHz-BW 2456. 10 2473. MHz 20 37 dB _{NT} +23 to +27deg.C, WLAN ch1 19MHz-BW 2456. 10 2473. MHz 20 37 dB _{NT} +23 to +27deg.C, WLAN ch1 19MHz-BW 2456. 10 2473. MHz 20 27 dB N79 4400. 10 4800. MHz 20 25 dB N77 4400. 10 4800. MHz 20 25 dB N79 4400. 10 4800. MHz 20 25 dB N79 4400. 10 4800. MHz 20 25 dB N79 4400. 10 4800. MHz 20 30 40 dB WIFI 5G 40 WIFI 5G									_	
1805. to 1880. MHz 30 39 dB B3 Rx 1880. to 1920. MHz 30 43 dB B39 1920. to 1990. MHz 30 39 dB B1 Tx 1930. to 1995. MHz 30 39 dB B25Rx 1932.5 to 1992.5 MHz 30 39 dB _{INT} Any 4.5MHz, B25Rx 1932.5 to 1992.5 MHz 30 39 dB _{INT} Any 4.5MHz, B25Rx 2110. to 2200. MHz 18 24 dB B1 Rx 2110. to 2200. MHz 14 23 dB B66 Rx 2112.5 to 2197.5 MHz 14 23 dB B66 Rx 2300. to 2400. MHz 10 16 dB B40 2401. to 2463. MHz 30 43 dB _{INT} WLAN ch1 9 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} WLAN ch1 10 19MHz-BW 2451. to 2473. MHz 5.0 25.1 dB _{INT} WLAN ch11 19MHz-BW 2461. to 2468. MHz 30 41 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch13 19MHz-BW 2451. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch13 19MHz-BW 2451. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch13 19MHz-BW 2451. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch13 19MHz-BW 2456. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch11 19MHz-BW 2451. to 2468. MHz 30 41 dB _{INT} +23 to +27deg.C, WLAN ch12 19MHz-BW 2451. to 2483. MHz 30 41 dB _{INT} +23 to +27deg.C, WLAN ch13 19MHz-BW 2456. to 2473. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n79 dB n79 to CMCC 4992. to 5380. MHz 30 40 dB 210 5150. to 5850. MHz 30 54 dB WIFI 5G									_	
1880. to 1920. MHz 30 43 dB B39 1920. to 1990. MHz 30 39 dB B1 Tx 1930. to 1995. MHz 30 38 dB B25Rx 1932.5 to 1992.5 MHz 30 39 dB B1 Rx 2110. to 2170. MHz 18 24 dB B1 Rx 2110. to 2200. MHz 14 23 dB B66 Rx 2112.5 to 2197.5 MHz 14 23 dB B66 Rx 2300. to 2400. MHz 10 16 dB B40 MLAN ch1 9 19MHz-BW 2401. to 2463. MHz 30 41 dB_{INT} WLAN ch1 10 19MHz-BW 2451. to 2473. MHz 30 41 dB_{INT} WLAN ch11 19MHz-BW 2461. to 2483. MHz 30 41 dB_{INT} WLAN ch11 19MHz-BW 2461. to 2468. MHz 35 41 dB_{INT} wLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB_{INT} wLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB_{INT} wLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB_{INT} wLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB_{INT} wLAN ch13 19MHz-BW 2451. to 2473. MHz 20 37 dB_{INT} wLAN ch13 19MHz-BW 2451. to 2468. MHz 35 41 dB_{INT} wLAN ch13 19MHz-BW 2451. to 2473. MHz 20 37 dB_{INT} wLAN ch13 19MHz-BW 2451. to 2473. MHz 20 37 dB_{INT} wLAN ch13 19MHz-BW 2451. to 2473. MHz 20 37 dB_{INT} wLAN ch13 19MHz-BW 2451. to 2473. MHz 20 37 dB_{INT} wLAN ch10 wLAN ch113 19MHz-BW 2451. to 2483. MHz 30 14.1 dB_{INT} wLAN ch12 wLAN ch13 19MHz-BW 2451. to 2483. MHz 30 14.1 dB_{INT} wLAN ch12 wLAN ch13 wLAN c										
1920. 10 1990. MHz 30 39 dB B1 Tx 1930. 10 1995. MHz 30 38 dB B25Rx 1932.5 10 1992.5 MHz 30 39 dB _{INT} Any 4.5MHz, B25Rx 2110. 10 2170. MHz 18 24 dB B1 Rx 2110. 10 2200. MHz 14 23 dB B66 Rx 2112.5 10 2197.5 MHz 14 23 dB B66 Rx 2300. 10 2400. MHz 10 16 dB B40 B40 2401. 10 2463. MHz 30 41 dB _{INT} WLAN ch1 9 19MHz-BW 2451. 10 2473. MHz 20 37 dB _{INT} WLAN ch11 10 19MHz-BW 2456. 10 2473. MHz 20 37 dB _{INT} WLAN ch12 19MHz-BW 2461. 10 2468. MHz 30 41. dB _{INT} WLAN ch13 19MHz-BW 2461. 10 2468. MHz 30 41. dB _{INT} WLAN ch13 19MHz-BW 2401. 10 2468. MHz 35 41 dB _{INT} WLAN ch13 19MHz-BW 2401. 10 2468. MHz 35 41 dB _{INT} wLAN ch13 19MHz-BW 2451. 10 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1 9 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch1 19MHz-BW 2456. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch1 19MHz-BW 2456. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch1 19MHz-BW 2456. to 2473. MHz 20 27 dB N78 3300. to 3800. MHz 20 27 dB N79 for CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G										
1930. to 1995. MHz 30 38 dB B25Rx 1932.5 to 1992.5 MHz 30 39 dB _{INT} Any 4.5MHz, B25Rx 2110. to 2170. MHz 18 24 dB B1 Rx 2110. to 2200. MHz 14 23 dB B66 Rx 2112.5 to 2197.5 MHz 14 23 dB _{INT} Any 4.5MHz, B66Rx 2300. to 2400. MHz 10 16 dB B40 2401. to 2463. MHz 30 43 dB _{INT} WLAN ch1 9 19MHz-BW 2401. to 2468. MHz 30 41 dB _{INT} WLAN ch1 10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} WLAN ch1 19 HYZ-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} 423 to +27deg.C, WLAN ch19 19 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch19 19 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch19 19 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch19 19 19MHz-BW 2456. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch19 19 MHz-BW 2456. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch19 19 MHz-BW 2456. to 2473. MHz 30 14.1 dB _{INT} +23 to +27deg.C, WLAN ch19 19 MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch19 19 MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch19 19 MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n77 4400. to 4800. MHz 30 40 dB 210 5150. to 5850. MHz 30 54 dB WIFI 5G										
1932.5 to 1992.5 MHz 30 39 dB _{INT} Any 4.5MHz, B25Rx 2110. to 2170. MHz 18 24 dB B1 Rx 2110. to 2200. MHz 14 23 dB B66 Rx 2112.5 to 2197.5 MHz 14 23 dB _{INT} Any 4.5MHz, B66Rx 2300. to 2400. MHz 10 16 dB B40 2401. to 2463. MHz 30 43 dB _{INT} WLAN ch1 9 19MHz-BW 2401. to 2463. MHz 30 41 dB _{INT} WLAN ch1 10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} WLAN ch1 11 19MHz-BW 2456. to 2478. MHz 5.0 25.1 dB _{INT} WLAN ch12 19MHz-BW 2461. to 2468. MHz 35 41 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1 19 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1 19 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch1 19 19MHz-BW 2461. to 2483. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1 19 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch1 19 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch1 19 19MHz-BW 2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C, WLAN ch1 19 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch1 19 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch1 19 19MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n78 4800. to 4900. MHz 26 33 dB n79 4800. to 4900. MHz 26 33 dB n79 5150. to 5850. MHz 30 40 dB 2f0										
2110. 10 2170. MHz 18 24 dB B1 Rx 2110. to 2200. MHz 14 23 dB B66 Rx 2112.5 to 2197.5 MHz 14 23 dB B66 Rx 2300. to 2400. MHz 10 16 dB B40 2401. to 2463. MHz 30 43 dB _{INT} WLAN ch1_9 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} WLAN ch1_10 19MHz-BW 2456. to 2478. MHz 5.0 25.1 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_9 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch1_10 19MHz-BW 2456. to 2478. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_10 19MHz-BW 2456. to 2478. MHz 30 37 dB _{INT} +23 to +27deg.C, WLAN ch11 19MHz-BW 2456. to 2478. MHz 30 14.1 dB _{INT} +23 to +27deg.C, WLAN ch12 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch13 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch13 19MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n79 4400. to 4800. MHz 26 33 dB n79 to CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G		—							-	
2110. to 2200. MHz 14 23 dB B66 Rx 2112.5 to 2197.5 MHz 14 23 dB _{INT} Any 4.5MHz, B66Rx 2300. to 2400. MHz 10 16 dB B40 2401. to 2463. MHz 30 43 dB _{INT} WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 30 41 dB _{INT} WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} WLAN ch11 19MHz-BW 2456. to 2478. MHz 5.0 25.1 dB _{INT} WLAN ch12 19MHz-BW 2461. to 2468. MHz 35 41 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_10 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_9 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch1_10 19MHz-BW 2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C, WLAN ch11 19MHz-BW 2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C, WLAN ch12 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch12 19MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 27 dB n78 4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G										
2112.5 to 2197.5 MHz 14 23 dB _{INT} Any 4.5MHz, B66Rx 2300. to 2400. MHz 10 16 dB B40 2401. to 2463. MHz 30 43 dB _{INT} WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 30 41 dB _{INT} WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} WLAN ch11 19MHz-BW 2456. to 2478. MHz 5.0 25.1 dB _{INT} WLAN ch12 19MHz-BW 2461. to 2483. MHz 2.0 14.1 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C,WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C,WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch1_11 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch11 19MHz-BW 2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C,WLAN ch11 19MHz-BW 2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C,WLAN ch12 19MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n77 4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB WIFI 5G										
2300. to 2400. MHz 10 16 dB B40 2401. to 2463. MHz 30 43 dB _{INT} WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 30 41 dB _{INT} WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} WLAN ch11 19MHz-BW 2456. to 2478. MHz 5.0 25.1 dB _{INT} WLAN ch12 19MHz-BW 2461. to 2483. MHz 2.0 14.1 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg. C, WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg. C, WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg. C, WLAN ch1_11 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg. C, WLAN ch1_11 19MHz-BW 2461. to 2483. MHz 10 25 dB _{INT} +23 to +27deg. C, WLAN ch12 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg. C, WLAN ch12 19MHz-BW 3300. to 3800. MHz 3.0 14.1 dB _{INT} +23 to +27deg. C, WLAN ch12 19MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n78 3800. to 4200. MHz 20 25 dB n79 4800. to 4900. MHz 26 33 dB n79 4800. to 4900. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G										
2401. to 2463. MHz 30 43 dB _{INT} WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 30 41 dB _{INT} WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} WLAN ch11 19MHz-BW 2456. to 2478. MHz 5.0 25.1 dB _{INT} WLAN ch12 19MHz-BW 2461. to 2483. MHz 2.0 14.1 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch1_11 19MHz-BW 2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C, WLAN ch11 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch12 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch13 19MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n78 3800. to 4200. MHz 20 25 dB n79 4800. to 4900. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G										
2401. to 2468. MHz 30 41 dB _{INT} WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} WLAN ch11 19MHz-BW 2456. to 2478. MHz 5.0 25.1 dB _{INT} WLAN ch12 19MHz-BW 2461. to 2483. MHz 2.0 14.1 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch11 19MHz-BW 2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C, WLAN ch11 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch12 19MHz-BW 3300. to 3800. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch13 19MHz-BW 3800. to 4200. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n77 4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G		—							-	_
2451. to 2473. MHz 20 37 dB _{INT} WLAN ch11 19MHz-BW 2456. to 2478. MHz 5.0 25.1 dB _{INT} WLAN ch12 19MHz-BW 2461. to 2483. MHz 2.0 14.1 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch1_11 19MHz-BW 2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C, WLAN ch11 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch12 19MHz-BW 3300. to 3800. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch13 19MHz-BW 3800. to 4200. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n77 4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G										
2456. to 2478. MHz 5.0 25.1 dB _{INT} WLAN ch12 19MHz-BW 2461. to 2483. MHz 2.0 14.1 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch1_11 19MHz-BW 2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C, WLAN ch12 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch12 19MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n77 4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G										
2461. to 2483. MHz 2.0 14.1 dB _{INT} WLAN ch13 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C, WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C, WLAN ch11 19MHz-BW 2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C, WLAN ch12 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch13 19MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n77 4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 30 40 dB 2f0 5150. to 5850. MHz 30										
2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C,WLAN ch1_9 19MHz-BW 2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C,WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch11 19MHz-BW 2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C,WLAN ch12 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C,WLAN ch13 19MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n77 4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB WIFI 5G		—								
2401. to 2468. MHz 35 41 dB _{INT} +23 to +27deg.C,WLAN ch1_10 19MHz-BW 2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch11 19MHz-BW 2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C,WLAN ch12 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C,WLAN ch13 19MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n77 4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G										
2451. to 2473. MHz 20 37 dB _{INT} +23 to +27deg.C,WLAN ch11 19MHz-BW 2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C,WLAN ch12 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C,WLAN ch13 19MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n77 4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G				2468.						-
2456. to 2478. MHz 10 25 dB _{INT} +23 to +27deg.C, WLAN ch12 19MHz-BW 2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch13 19MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n77 4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G							37			+23 to +27deg.C,WLAN ch11 19MHz-BW
2461. to 2483. MHz 3.0 14.1 dB _{INT} +23 to +27deg.C, WLAN ch13 19MHz-BW 3300. to 3800. MHz 20 27 dB n78 3800. to 4200. MHz 20 25 dB n77 4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G				2478.		10	25			+23 to +27deg.C,WLAN ch12 19MHz-BW
3800. to 4200. MHz 20 25 dB n77 4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G		2461.	to	2483.	MHz	3.0	14.1		dB _{INT}	+23 to +27deg.C,WLAN ch13 19MHz-BW
4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G				3800.	MHz	20	27		dB	n78
4400. to 4800. MHz 18 24 dB n79 4800. to 4900. MHz 26 33 dB n79 for CMCC 4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G		3800.	to	4200.	MHz	20	25		dB	n77
4992. to 5380. MHz 30 40 dB 2f0 5150. to 5850. MHz 30 54 dB WIFI 5G		4400.		4800.	MHz	18	24		dB	n79
5150. to 5850. MHz 30 54 dB WIFI 5G		4800.	to	4900.	MHz	26	33		dB	n79 for CMCC
.0		4992.	to	5380.	MHz	30	40		dB	2f0
7488. to 8070. MHz 30 47 dB 3f0			to		MHz	30	54		dB	WIFI 5G
		7488.	to	8070.	MHz	30	47		dB	3f0


^{*} Typical value at 25±2deg.C



SAFRC2G59MD0F0A (Band41 Full / Unbalanced / 5pin / 1411) Electrical Characteristic

< ltem >









Dimensions of Tape & Reel unit: mm


Carrier Tape



Tape



Reel





Important Notice (1/2)

PLEASE READ THIS NOTICE BEFORE USING OUR PRODUCTS.

Please make sure that your product has been evaluated and confirmed from the aspect of the fitness for the specifications of our product when our product is mounted to your product. All the items and parameters in this product specification/datasheet/catalog have been prescribed on the premise that our product is used for the purpose, under the condition and in the environment specified in this specification. You are requested not to use our product deviating from the condition and the environment specified in this specification.

Please note that the only warranty that we provide regarding the products is its conformance to the specifications provided herein. Accordingly, we shall not be responsible for any defects in products or equipment incorporating such products, which are caused under the conditions other than those specified in this specification.

WE HEREBY DISCLAIMS ALL OTHER WARRANTIES REGARDING THE PRODUCTS, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, THAT THEY ARE DEFECT-FREE, OR AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS.

The product shall not be used in any application listed below which requires especially high reliability for the prevention of such defect as may directly cause damage to the third party's life, body or property. You acknowledge and agree that, if you use our products in such applications, we will not be responsible for any failure to meet such requirements.

Furthermore, YOU AGREE TO INDEMNIFY AND DEFEND US AND OUR AFFILIATES AGAINST ALL CLAIMS, DAMAGES, COSTS, AND EXPENSES THAT MAY BE INCURRED, INCLUDING WITHOUT LIMITATION, ATTORNEY FEES AND COSTS, DUE TO THE USE OF OUR PRODUCTS IN SUCH APPLICATIONS.

- Aircraft equipment.
- Aerospace equipment
- Undersea equipment.
- Power plant control equipment Medical equipment.
- Transportation equipment (vehicles, trains, ships, elevator, etc.).
- Traffic signal equipment.
- Disaster prevention / crime prevention equipment.
- Burning / explosion control equipment
- Application of similar complexity and/ or reliability requirements to the applications listed in the above.

We expressly prohibit you from analyzing, breaking, Reverse-Engineering, remodeling altering, and reproducing our product. Our product cannot be used for the product which is prohibited from being manufactured, used, and sold by the regulations and laws in the world.

Please do not use the product in molding condition.

This product is ESD (ElectroStatic Discharge) sensitive device.

When you install or measure this, you should be careful not to add antistatic electricity or high voltage. Please be advised that you had better check anti serge voltage.



SAFRC2G59MD0F0A (Band41 Full / Unbalanced / 5pin / 1411) Important Notice (2/2)

We do not warrant or represent that any license, either express or implied, is granted under any our patent right, copyright, mask work right, or our other intellectual property right relating to any combination, machine, or process in which our products or services are used. Information provided by us regarding third-party products or services does not constitute a license from us to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from us under our patents or other intellectual property.

Please do not use our products, our technical information and other data provided by us for the purpose of developing of mass-destruction weapons and the purpose of military use.

Moreover, you must comply with "foreign exchange and foreign trade law", the "U.S. export administration regulations", etc.

Please note that we may discontinue the manufacture of our products, due to reasons such as end of supply of materials and/or components from our suppliers.

Customer acknowledges that Murata will, if requested by you, conduct a failure analysis for defect or alleged defect of Products only at the level required for consumer grade Products, and thus such analysis may not always be available or be in accordance with your request (for example, in cases where the defect was caused by components in Products supplied to Murata from a third party).

The product shall not be used in any other application/model than that of claimed to Murata.

Customer acknowledges that engineering samples may deviate from specifications and may contain defects due to their development status.

We reject any liability or product warranty for engineering samples.

In particular we disclaim liability for damages caused by

- •the use of the engineering sample other than for evaluation purposes, particularly the installation or integration in the product to be sold by you,
 - ·deviation or lapse in function of engineering sample,
 - ·improper use of engineering samples.

We disclaim any liability for consequential and incidental damages.

If you can't agree the above contents, you should inquire our sales.