

20V N-Channel Enhancement Mode MOSFET

Description

The AP2302CI uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 2.5V. This device is suitable for use as a Battery protection or in other Switching application.


General Features

$V_{DS} = 20V$ $I_D = 2.3A$

$R_{DS(ON)} < 52m\Omega @ V_{GS}=4.5V$

Application

Battery protection
 Load switch
 Uninterruptible power supply



Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)
AP2302CI	SOT-23	A2SHB.	3000

Absolute Maximum Ratings ($T_C=25^\circ C$ unless otherwise noted)

Symbol	Parameter	Limit	Unit
V_{DS}	Drain-source Voltage	20	V
V_{GS}	Gate-source Voltage	± 12	V
I_D	Drain Current	$T_A=25^\circ C$ @ Steady State	2.3
		$T_A=70^\circ C$ @ Steady State	1.8
IDM	Pulsed Drain Current ^A	14	A
P_D	Total Power Dissipation @ $T_A=25^\circ C$	0.7	W
$R_{\theta JA}$	Thermal Resistance Junction-to-Ambient@Steady State	178	$^\circ C/W$
T_J, T_{STG}	Junction and Storage Temperature Range	-55~+150	$^\circ C$

20V N-Channel Enhancement Mode MOSFET

Electrical Characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	20	21		V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=20V, V_{GS}=0V, T_C=25^\circ\text{C}$			1	μA
I_{GSS}	Gate-Body Leakage Current	$V_{GS}=\pm 12V, V_{DS}=0V$			± 100	nA
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	0.45	0.58	0.9	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	$V_{GS}=4.5V, I_D=3.0A$		48	52	m Ω
		$V_{GS}=2.5V, I_D=2.0A$		55	66	
C_{iss}	Input Capacitance	$V_{DS}=10V, V_{GS}=0V, f=1\text{MHZ}$		280		pF
C_{oss}	Output Capacitance			46		
C_{rss}	Reverse Transfer Capacitance			29		
Q_g	Total Gate Charge	$V_{GS}=4.5V, V_{DS}=10V, I_D=3.0A$		2.9		nC
Q_{gs}	Gate Source Charge			0.4		
Q_{gd}	Gate Drain Charge			0.6		
$tD(on)$	Turn-on Delay Time	$V_{GS}=4.5V, V_{DD}=10V, R_L=1.5\Omega, R_{GEN}=3\Omega$		13		ns
t_r	Turn-on Rise Time			54		
$tD(off)$	Turn-off Delay Time			18		
t_f	Turn-off Fall Time			11		
I_S	Maximum Body-Diode Continuous Current				3.0	A
V_{SD}	Diode Forward Voltage	$I_S=3.0A, V_{GS}=0V$			1.2	V

Note:

- 1、Pulse Test: Pulse Width $\leq 300\mu s$, Duty cycle $\leq 2\%$.
- 2、Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch.

20V N-Channel Enhancement Mode MOSFET

Typical Characteristics




Figure1. Output Characteristics




Figure2. Transfer Characteristics




Figure3. Capacitance Characteristics




Figure4. Gate Charge




Figure5. Drain-Source on Resistance




Figure6. Drain-Source on Resistance



20V N-Channel Enhancement Mode MOSFET




Figure7. Safe Operation Area





Figure8. Switching wave

20V N-Channel Enhancement Mode MOSFET

Package Mechanical Data-SOT-23



Symbol	Dimensions in Millimeters	
	MIN.	MAX.
A	0.900	1.150
A1	0.000	0.100
A2	0.900	1.050
b	0.300	0.500
c	0.080	0.150
D	2.800	3.000
E	1.200	1.400
E1	2.250	2.550
e	0.950TYP	
e1	1.800	2.000
L	0.550REF	
L1	0.300	0.500
θ	0°	8°

20V N-Channel Enhancement Mode MOSFET

Attention

1, Any and all APM Microelectronics products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your APM Microelectronics representative nearest you before using any APM Microelectronics products described or contained herein in such applications.

2, APM Microelectronics assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all APM Microelectronics products described or contained herein.

3, Specifications of any and all APM Microelectronics products described or contained here instipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

4, APM Microelectronics Semiconductor CO., LTD. strives to supply high quality high reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

5, In the event that any or all APM Microelectronics products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

6, No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of APM Microelectronics Semiconductor CO., LTD.

7, Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. APM Microelectronics believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

8, Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the APM Microelectronics product that you intend to use.