

High Speed Switching Diode



SOT-23

Features


- Epoxy meets UL-94 V-0 flammability rating and halogen free
- Moisture Sensitivity Level 1
- V_{BR} 100V
- I_{FAV} 200mA@ Single diode loaded
- Part no. with suffix "Q" means AEC-Q101 qualified

Applications


- Extreme fast switches

Mechanical Data


- **Case:** SOT-23
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102



BAW56Q
Marking:A1



BAV70Q
Marking:A4



BAV99Q
Marking:A7

■ Maximum Ratings ($T_a=25^\circ\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	CONDITIONS	VALUE
Reverse Breakdown Voltage	V_{BR}	V		100
Average Forward Current	$I_{FAV[1]}$	mA		200
Non-Repetitive Peak Forward Surge Current	I_{FSM}	A	$t_p=1$ ms	1
Power Dissipation	$P_{tot[1]}$	mW		350
Thermal Resistance Junction to Ambient	R_{thJA}	$^\circ\text{C}/\text{W}$		357
Maximum Junction Temperature	T_j	$^\circ\text{C}$		150
Storage Temperature Range	T_{stg}	$^\circ\text{C}$		-55 to +150

[1] Single diode loaded



BAW56Q&BAV70Q&BAV99Q

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)


PARAMETER	SYMBOL	UNIT	CONDITIONS	VALUE
Forward Voltage	V _F	V	I _F =1mA	0.715
			I _F =10mA	0.855
			I _F =50mA	1.0
			I _F =150mA	1.25
Reverse Current	I _R	μA	V _R =75V	1
Reverse Breakdown Voltage	V _{BR}	V	I _R =10μA	100
Junction Capacitance	C _J	pF	V _R =V _F =0V, f =1MHz	4
Reverse Recovery Time	t _{rr}	ns	I _F =10mA, I _{rr} =0.1I _R , R _L =100Ω	4

■ Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
BAW56Q&BAV70Q&BAV99Q	F2	Approximate 0.010	3000	30000	120000	7" reel

■ Characteristics (Typical)


Fig.1 - Forward Characteristics



Reverse Characteristics







Capacitance Characteristics





BAW56Q&BAV70Q&BAV99Q

■ Outline Dimensions




UNIT: mm

SYMBOL	DIMENSIONS			
	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.045	0.900	1.150
A1	0.000	0.004	0.000	0.100
A2	0.035	0.041	0.900	1.050
b	0.012	0.020	0.300	0.500
c	0.004	0.008	0.100	0.200
D	0.110	0.118	2.800	3.000
E	0.047	0.055	1.200	1.400
E1	0.089	0.100	2.250	2.550
e	0.037TYP		0.950TYP	
e1	0.071	0.079	1.800	2.000
L	0.022REF		0.550REF	
L1	0.012	0.200	0.300	0.500
θ	0°	8°	0°	8°

NOTE:
 1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
 2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
 3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.

■ Marking Information



Note:

1. All marking is at middle of the product body
2. All marking is in laser marking
3. XX is Marking Code
4. Body color: Black



BAW56Q&BAV70Q&BAV99Q

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, life-sustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.