

Micro Monitor Supply Control


(compatible to MAX705/SP705/ADM705/DS1705/ISL88705)

The HT705 is designed to control power supply and to start microcontroller and microprocessor systems. It is used for securing stable functioning of the system when starting and halting the device as well as in the case of the supply voltage drops.



The HT705 contains a source of reference voltage, two analog comparators, watchdog timer, digital sampler, digital delay.

Features:

- rated supply voltage 5.0 V;
- generation of reset signal when power supply is on for correct start of microprocessor;
- generation of reset signal when power supply drops below the operating one to avoid incorrect functioning of microprocessor;
- generation of reset signal when pushing reset button;
- possibility to program threshold voltage at which reset signal is generated.
- generation of reset signal per fixed level of supply voltage;
- generation of reset signal from external “Reset” button;
- generation of signal of watchdog timer status;
- emergency interruption of primary power source.



PIN DESCRIPTION



<u>PBRST</u>	- Pushbutton Reset Input
<u>Vcc</u>	- Power Supply
<u>GND</u>	- Ground
<u>IN</u>	- Input
<u>NMI</u>	- Non-maskable Interrupt
<u>ST</u>	- Strobe Input
<u>RST</u>	- Active Low Reset Output
<u>*RST</u>	- Active High Reset Output (HT1706P and HT1706L only)
<u>WDS</u>	- Watchdog Status Output

Industrial temperature range

Industrial temperature range - 40°C to + 85°C.

Table 1 – Recommended operating conditions

Symbol	Parameter	Typical		Units
		min	max	
V _{CC}	Supply voltage	1.2	5.5	V
V _{IH}	Input voltage, high level	2.0	V _{CC} +0.3	V
V _{IL}	Input voltage, low level	-0.03	0.5	V
T _A	Operating temperature range	-40	85	°C

Table 2 – Absolute maximum ratings

Symbol	Parameter	Typical		Units
		min	max	
V _{CC}	Supply voltage	-0.5	7.0	V
V _{IH}	Input voltage, high level	-	V _{CC} +0.5	V
V _{IL}	Input voltage, low level	-0.5	-	V
T _{stg}	Storage temperature	-60	125	°C

Exposure to absolute maximum rating conditions may affect reliability of IC and its functional operation.
 Upon removing the absolute maximum ratings conditions, functional operation is guaranteed in recommended operating conditions.

* Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device.
 These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied.
 Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

Table 3 – DC electrical characteristics ($T_A = -40^\circ \text{ to } +85^\circ\text{C}$)

Symbol	Parameter	Test conditions	Typical		Units
			min	max	
V_{IL}	Input voltage, low level	$V_{CC}=\text{from } 2.4 \text{ to } 5.5\text{V}$	-	0.5	V
V_{IH}	Input voltage, high level	$V_{CC}=\text{from } 2.4 \text{ to } 5.5\text{V}$	2.0		V
I_{OL}	Output current, low level (NMI, RST)	$V_{CC}=\text{from } 2.4 \text{ to } 5.5\text{V}$ $V_{OL}=0.4\text{V}$	10.0	-	mA
I_{OH}	Output current, high level (WDS, NMI)	$V_{CC}=\text{from } 4.5 \text{ to } 5.5\text{V}$ $V_{OH}=2.4\text{V}$	-100	-1000	μA
I_{OHI}	Output current, high level, (RST)	$V_{CC}=\text{from } 5.0 \text{ to } 5.5\text{V}$ $V_{OH}=2.4\text{V}$	-10	-	mA
V_{OH}	Output voltage, high level (RST)	$V_{CC}=\text{from } 5.0 \text{ to } 5.5\text{V}$ $I_{OH}=-500\text{m}\text{A}$	$V_{CC}-0.3$	-	V
I_{LIL1}	Input leakage current, low level (IN)	$V_{CC}=\text{from } 1.2 \text{ to } 5.5\text{V}$ $V_{IL}=0\text{ V}$	-	-1.0	μA
I_{LIL2}	Input leakage current, low level (ST)	$V_{CC}=5.5\text{V}$ $V_{IL}=0\text{ V}$	-10	-100	μA
I_{LIL3}	Input leakage current, low level (PBRST)	$V_{CC}=5.5\text{V}$ $V_{IL}=0\text{ V}$	-50	-450	μA
I_{LIH}	Input leakage current, high level	$V_{CC}=\text{from } 1.2 \text{ to } 5.5\text{V}$ $V_{IH}=V_{CC}$	-	1.0	μA
I_{CC}	Operating current	$V_{CC}=\text{from } 1.2 \text{ to } 5.5\text{V}$ $V_{IL}=0\text{ V}, V_{IH}=V_{CC}$	-	60	μA
V_{CCTP}	V_{CC} trip point	$V_{IL}=0\text{ V}, V_{IH}=V_{CC}$	4.5	4.75	V
V_{TP}	IN input trip point	$V_{CC}=5.0\text{ V}$ $V_{IL}=0\text{ V}, V_{IH}=V_{CC}$	1.2	1.3	V

Table 4 – AC electrical characteristics ($V_{CC} = 5.0$ V, $T_A = -40^\circ$ to $+85^\circ$ C)

Symbol	Parameter	Typical		Units
		min	max	
t_{TD}	Watchdog timeout	1.0	2.2	s
t_{PDLY}	\overline{PBRST} stable low to RST and \overline{RST}	-	250	ns
t_{RST}	Reset active time	130	285	ms
t_{RPD}	V_{CC} detect to RST and \overline{RST}	-	8.0	μ s
t_{RPU}	V_{CC} detect to RST and \overline{RST}	130	285	ms
t_{IPD}	VIN detect to NMI	-	8.0	μ s
t_{PB}	($\overline{PBRST} = V_{IL}$)	150	-	ns
t_{ST}	\overline{ST} Pulse Width	10	-	ns

Timing diagrams




Fig. 3 – Timing diagram of forming reset signal from external PBRST control button






Fig. 4 – Timing diagram: strobe input

TIMING DIAGRAM: POWER-DOWN



TIMING DIAGRAM: POWER-UP










Fig. 8 – Block Diagram

N SUFFIX DIP
(MS - 001BA)


	Dimension, mm	
Symbol	MIN	MAX
A	8.51	10.16
B	6.10	7.11
C		5.33
D	0.36	0.56
F	1.14	1.78
G		2.54
H		7.62
J	0°	10°
K	2.92	3.81
L	7.62	8.26
M	0.20	0.36
N	0.38	

NOTES:

- Dimensions "A", "B" do not include mold flash or protrusions.
Maximum mold flash or protrusions 0.25 mm (0.010) per side.

D SUFFIX SOP
(MS - 012AA)


	Dimension, mm	
Symbol	MIN	MAX
A	4.80	5.00
B	3.80	4.00
C	1.35	1.75
D	0.33	0.51
F	0.40	1.27
G		1.27
H		5.72
J	0°	8°
K	0.10	0.25
M	0.19	0.25
P	5.80	6.20
R	0.25	0.50

NOTES:

- Dimensions A and B do not include mold flash or protrusion.
- Maximum mold flash or protrusion 0.15 mm (0.006) per side for A; for B - 0.25 mm (0.010) per side.