



Pin	A	B	C
2	3.96	9.9	11.88
3	7.92	13.86	15.84
4	11.88	17.82	19.80
5	15.84	21.78	23.76
6	19.80	25.74	27.72
7	23.76	29.70	31.68
8	27.72	33.66	35.64
9	31.68	37.62	39.60
10	35.64	41.58	43.56
10	39.60	45.54	47.52
12	43.56	49.50	51.48

PCB Layout(Pattern side)

SPECIFICATIONS

1. Voltage rating: 250V AC, DC
2. Current rating: 7A, AC, DC
3. Withstanding Voltage: 1500V AC/minute
4. Insulation resistance: 1000MΩ min
5. Temperature range: -25°C~+85°C
6. Contact resistance: 10mΩ max

WAFFER  
 Housing Material: LCP UL 94V0  
 Pin Material: Phosphor Bronze or Brass  
 Contact Area Plating: Plated Tin or Plated Gold

ECN NO.		REV.		DATE.		DESCRIPTION.		CHANGE.		CHECK.		APPRO.	
NEW		A											

APPROVALS		DATE
DRAWN	G.M.Chen	2015/5/29
CHECKED		
APPROVALS		

TOLERANCES ARE		30 <sup>±0.15</sup>	±0.30	ANGLE	PART NO.	SCALE: 1:1	SHEET 1 OF 1
10 <sup>±0.10</sup>	±0.20	5 <sup>±0.10</sup>	±0.15	±2°	L396VII-XXPW		PROJ.
~5	±0.10						

**DEALON** 德之隆  
 ELECTRONICS CO.,LTD  
 CONNECTOR