PRODUCT NO.	RoHS compliant
DSIC02TSGET	

REV.	ECN NO.	DR	DATE

NOTES :

1.Specification:

1>.Operating force: 1000gf Max

2>.Operating Temperature: −40° to+85°

3>.Storage Temperature:: −40° to+85°

4>.Mechanical Life: 3000cycles minimum

5>.Electrical Life: 2000cycles minimum

2. PLATING:

GOLD FLASH 1u"~2u" SOLDERTAIL,
1u"~3u" GOLD PLATING ON THE CONTACT AREA,
WITH 50u" NICKEL UNDERPLATINGOVERALL.

3. PART NUMBER DESCRIPTION

DSIC XX T S G E T

- [包装方式: T=管装 R=Reel]
- [电镀层: E=接触部1u"~3u" /焊接部1u"~2u"]
- [G=镀全金 S=内金外镍]
- [脚型: S脚 / J脚 / H脚 / A脚 / Z脚]
- [T=低推贴胶 S=低推不贴胶 L=长推]
- [产品P数: 02=2P ..... 08=8P 10=10P 12=12P]







[Schematic]





RECOMMENDED P.C.B. LAYOUT (TOP VIEW)

[推钮行程]



(Construction)



Number	Part Name	Material	Finished
①	Actuator	UL94 V0	White
②	Cover	UL94 V0	Black
③	Movable	Copper Alloy	1u"~3u"Gold
④	Terminal	Brass	1u"~2u"Gold
⑤	Base	UL94 V0	Black
⑥	Terminal Contact	Brass	1u"~3u"Gold
⑦	Mylar	UL94 V0	0.05mm

TOLERANCE UNLESS OTHERWISE SPECIFIED	
LINER	ANGLES
.0 ± 0.25	0. ± 2°
.00 ± 0.15	.0 ± 1°
.000± 0.10	.00± 0.5°
DESIGN	kathy
DRAWING	
CHECK	
APPRO.	

INSPECTION COPY

PROJECTION

2012/04/12

东莞市广都实业有限公司
DongGuan Kingtek Industrial Co., Ltd.

TITLE
BY DSIC SERIES PITCH 2.54mm

PRODUCT FAMILY DSIC SERIES

PRAT NO. DSIC02TSGET

FILE NO. DSIC02TSGET-A

SIZE	UNIT	SCALE	SHEET	REV.
A4	mm	2 : 1	1OF1	A