

Product Summary

V _{(BR)DSS}	R _{DS(on)MAX}	I _D
20V	380mΩ@4.5V	0.75A
	450mΩ@2.5V	
	800mΩ@1.8V	



Feature

- Surface Mount Package
- N-Channel Switch with Low R_{DS(on)}
- Operated at Low Logic Level Gate Drive

Application

- Load/Power Switching
- Interfacing Switching
- Battery Management for Ultra Small Portable Electronics
- Logic Level Shift

MARKING:



ABSOLUTE MAXIMUM RATINGS (T_a=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V _{DS}	20	V
Gate-Source Voltage	V _{GS}	±12	V
Continuous Drain Current ⁽¹⁾	I _D	0.75	A
Power Dissipation ⁽¹⁾	P _D	150	mW
Thermal Resistance from Junction to Ambient ⁽¹⁾	R _{θJA}	833	°C/W
Junction Temperature	T _J	150	°C
Storage Temperature	T _{STG}	-55~+150	°C









MOSFET ELECTRICAL CHARACTERISTICS($T_a=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Static Characteristics						
Drain-source breakdown voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}} = 0\text{V}, I_D = 250\mu\text{A}$	20			V
Zero gate voltage drain current	I_{DSS}	$V_{\text{DS}} = 20\text{V}, V_{\text{GS}} = 0\text{V}$			1	μA
Gate-body leakage current	I_{GSS}	$V_{\text{GS}} = \pm 10\text{V}, V_{\text{DS}} = 0\text{V}$			± 20	μA
Gate threshold voltage ⁽¹⁾	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}} = V_{\text{GS}}, I_D = 250\mu\text{A}$	0.35	0.75	1.1	V
Drain-source on-resistance ⁽¹⁾	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}} = 4.5\text{V}, I_D = 650\text{mA}$		190	380	$\text{m}\Omega$
		$V_{\text{GS}} = 2.5\text{V}, I_D = 550\text{mA}$		260	450	
		$V_{\text{GS}} = 1.8\text{V}, I_D = 450\text{mA}$		390	800	
Forward transconductance ⁽¹⁾	g_{FS}	$V_{\text{DS}} = 10\text{V}, I_D = 800\text{mA}$		1.6		S
Dynamic characteristics⁽²⁾						
Input Capacitance	C_{iss}	$V_{\text{DS}} = 16\text{V}, V_{\text{GS}} = 0\text{V}, f = 1\text{MHz}$			120	pF
Output Capacitance	C_{oss}				20	
Reverse Transfer Capacitance	C_{rss}				15	
Switching Characteristics⁽²⁾						
Turn-on delay time	$t_{\text{d}(\text{on})}$	$V_{\text{DS}} = 10\text{V}, I_D = 500\text{mA}, V_{\text{GS}} = 4.5\text{V}, R_G = 10\Omega$		6.7		ns
Turn-on rise time	t_r			4.8		
Turn-off delay time	$t_{\text{d}(\text{off})}$			17.3		
Turn-off fall time	t_f			7.4		
Source-Drain Diode characteristics						
Diode Forward voltage ⁽¹⁾	V_{DS}	$I_S = 0.15\text{A}, V_{\text{GS}} = 0\text{V}$			1.2	V



Notes:

1. Pulse Test : Pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 0.5\%$.
2. Guaranteed by design, not subject to production testing

Typical Electrical and Thermal Characteristics



SOT-363 Package Information




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.150	0.350	0.006	0.014
c	0.100	0.150	0.004	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.400	0.085	0.094
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°

SOT-363 Tape and Reel


SOT-363 Tape and reel

SOT-363 Embossed Carrier Tape




Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-363	2.25	2.55	1.20	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-363 Tape Leader and Trailer



SOT-363 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7" Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	30,000 pcs	203×203×195	120,000 pcs	438×438×220	