



R1A THRU R1M


1.0AMP Surface Mount Glass Superfast Recovery Rectifier

Features

- Fast switching for high efficiency
- Low Power Loss, High Efficiency
- High current capability
- For Use in Low Voltage Application
- Plastic Case Material has UL Flammability Classification Rating 94V-0

Mechanical Data

- Case: Molded plastic SMAF
- Terminals: Plated leads solderable per MIL-STD-750, Method 2026 guaranteed
- Polarity: Cathode Band or Cathode Notch
- Mounting Position: Any
- Making: Type Number



Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load

For capacitive load derate current by 20%

Type Number	SYMBOL	R1A	R1B	R1D	R1G	R1J	R1K	R1M	Unit
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Average Rectified Output Current @ $T = 90^{\circ}C$	$I_{F(AV)}$	1.0							A
Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	30							A
I^2t Rating for Fusing ($t < 8.3ms$)	I^2t	3.735							A^2s
Forward Voltage @ $I_F=1.0A$	V_{FM}	1.3							V
Peak Reverse Current @ $T_A=25^{\circ}C$	I_R	5.0							uA
At Rated DC Blocking Voltage @ $T_A=125^{\circ}C$		150							
Maximum Reverse Recovery Time (Note 1)	T_{rr}	150			250		500		ns
Typical Junction Capacitance (Note 2)	C_J	7							pF
Typical Thermal Resistance Junction to Ambient (Note 3)	$R_{\theta JA}$	70							$^{\circ}C/W$
Operating Temperature Range	T_J	-55 to +150							$^{\circ}C$
Storage Temperature Range	T_{STG}	-55 to +150							$^{\circ}C$

Note: 1. Reverse Recovery Test Conditions: $I_F=0.5A, I_R=1.0A, I_{RR}=0.25A$.

2. Measured at 1.0 MHz and Applied reverse Voltage of 4.0V D.C

3. Device mounted on FR-4 substrate, 1" x 1", 2oz, single-sided, PC boards with 0.06" x 0.09" copper pad.



R1A THRU R1M

1.0AMP Surface Mount Glass Superfast Recovery Rectifier









Fig.6 TYPICAL CAPACITANCE





Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from XINNUO
- XINNUO reserves the right to make changes to this document and its products and specifications
- XINNUO disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- XINNUO does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications.
XINNUO makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown here in are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify XINNUO for any damages resulting from such improper use or sale.
- Since XINNUO uses lot number as the tracking base, please provide the lot number for tracking when complaining.