




## FEATURES

- Rating to 1000V PRVP
- Surge overload rating to 60 Amperes peak
- Ideal for printed circuit board
- Reliable low cost construction utilizing molded plastic technique results in inexpensive product
- Lead solderable per MIL-STD-202 method 208
- Glass passivated chip junctions
- Plastic material has UL flammability classification 94V-O



DB-1		
Dim	Min	Max
A	8.20	8.60
B	6.10	6.50
C	2.35	2.65
E	0.15	0.35
F	5.40	6.00
I	0.35	0.65
J	8.40	9.00
K	4.80	5.20
L	7.65	8.15

All Dimensions in mm

## Maximum Ratings (@TA = 25°C unless otherwise specified)

Characteristic	Symbol	DB201	DB202	DB203	DB204	DB205	DB206	DB207	UNITS
Peak Repetitive Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
RMS Reverse Voltage	$V_{RMS}$	35	75	140	280	420	560	700	V
DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum average forward Output current @TA=25°C	$I_{F(AV)}$	2.0							A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	$I_{FSM}$	60							A
I <sup>2</sup> t Rating for fusing @Tj=25°C	I <sup>2</sup> t	14.9							A <sup>2</sup> S





## Thermal Characteristics

Characteristic	Symbol	DB201	DB202	DB203	DB204	DB205	DB206	DB207	UNITS
Typical thermal resistance per leg (Note 1)	$R_{\theta JA}$	70							°C/W
	$R_{\theta JC}$	31							
	$R_{\theta JL}$	29							
Operating junction temperature range	$T_J$	- 55 ---- + 150							°C
Storage temperature range	$T_{STG}$	- 55 ---- + 150							°C

Note: 1. Device mounted on PCB with 10 mm x 20 mm x 0.1mm copper pad areas

## Electrical Characteristics (@TA = 25°C unless otherwise specified)

Characteristic	Symbol	DB201	DB202	DB203	DB204	DB205	DB206	DB207	UNITS
Maximum instantaneous forward voltage at 2.0 A	$V_F$	1.1							V
Maximum reverse current @TA=25°C at rated DC blocking voltage @TA=100°C	$I_R$	5.0							μ A
		0.5							mA

**FIG.1 – PEAK FORWARD SURGE CURRENT**

**FIG.2 – FORWARD DERATING CURVE**

**FIG.3 – TYPICAL FORWARD CHARACTERISTIC**

**FIG.4 – TYPICAL REVERSE CHARACTERISTIC**


Device	Package	Shipping
DB201-DB207	DB-1	50unit/pipe