



CHENMKO ENTERPRISE CO.,LTD

SURFACE MOUNT

SCHOTTKY BARRIER DIODE

VOLTAGE 30 Volts CURRENT 0.2 Ampere

Halogens free devices

CH520G2-30GP

APPLICATION

- * Low power rectification and high speed switching

FEATURE

- * Extremely small surface mounting type. (FBPD-923)
- * Low IR. (IR=0.1uA Typ.)
- * High reliability
- * Lead free devices


CONSTRUCTION

- * Silicon epitaxial planar


MARKING

- * B

CIRCUIT



FBPD-923



Dimensions in millimeters

FBPD-923

MAXIMUM RATINGS (At TA = 25°C unless otherwise noted)

RATINGS	SYMBOL	CH520G2-30GP	UNITS
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	30	Volts
Maximum RMS Voltage	V _{RMS}	21	Volts
Maximum DC Blocking Voltage	V _D	30	Volts
Maximum Average Forward Rectified Current	I _O	0.2	Amps
Peak Forward Surge Current at 8.3 mSec single half sine-wave	I _{FSM}	1.0	Amps
Typical Junction Capacitance between Terminal (Note 1)	C _J	6.0	pF
Maximum Operating Temperature Range	T _J	+125	°C
Storage Temperature Range	T _{STG}	-40 to +125	°C

ELECTRICAL CHARACTERISTICS (At TA = 25°C unless otherwise noted)

CHARACTERISTICS	SYMBOL	CH520G2-30GP	UNITS
Maximum Instantaneous Forward Voltage at I _F = 200mA	V _F	0.60	Volts
Maximum Average Reverse Current at V _R = 10V	I _R	1.0	uAmps

NOTES : 1. Measured at 1.0 MHz and applied reverse voltage of 10.0 volts.
2. ESD sensitive product handling required.

2013-03

RATING CHARACTERISTIC CURVES (CH520G2-30GP)

FIG. 1 - FORWARD CHARACTERISTICS




FIG. 2 - REVERSE CHARACTERISTICS




FIG. 3 - TYPICAL JUNCTION CAPACITANCE




FIG. 4 - TYPICAL FORWARD CURRENT DERATING CURVE

