

General Description

The CMS6679 uses advanced trench technology to provide excellent RDS(ON) and ultra-low low gate charge. This device is suitable for use as a load switch or in PWM applications.

Features


- RDS(ON)=14mΩ @ VGS=-10V
- RDS(ON)=25mΩ @ VGS=-4.5V
- Ultra low On-Resistance.
- Surface mount package.

Product Summary

BVDSS	RDS(ON)	ID
-30V	14mΩ	-18A

Applications

- Inverter Switch
- Synchronous Rectifier
- Load Switch
- DC/DC Converter

SOP-8 Pin Configuration

Type	Package	Marking
CMS6679	SOP- 8	CMS6679

Absolute Maximum Ratings (TA=25°C Unless Otherwise Noted)

Symbol	Parameter	Rating	Units
V _{DS}	Drain-Source Voltage	-30	V
V _{GS}	Gate-Source Voltage	±20	V
I _D	Continuous Drain Current	-18	A
I _{DM}	Pulsed Drain Current	-60	A
P _D @T _A =25°C	Total Power Dissipation	3	W
T _{STG}	Storage Temperature Range	-55 to 150	°C
T _J	Operating Junction Temperature Range	150	°C

Thermal Data

Symbol	Parameter	Typ.	Max.	Unit
R _{θJA}	Thermal Resistance, Junction-to-Ambient	---	150	°C/W

Electrical Characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$, $I_D=-250\mu\text{A}$	-30	---	---	V
$R_{\text{DS}(\text{ON})}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=-10\text{V}$, $I_D=-10\text{A}$	---	---	14	$\text{m}\Omega$
		$V_{\text{GS}}=-4.5\text{V}$, $I_D=-10\text{A}$	---	---	25	
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	$V_{\text{GS}}=V_{\text{DS}}$, $I_D = -250\mu\text{A}$	-1	---	-3	V
I_{DSS}	Drain-Source Leakage Current	$V_{\text{DS}}=-24\text{V}$, $V_{\text{GS}}=0\text{V}$	---	---	-1	μA
I_{GSS}	Gate-Source Leakage Current	$V_{\text{GS}} = \pm 20\text{V}$, $V_{\text{DS}}=0\text{V}$	---	---	± 100	nA
g_{fs}	Forward Transconductance	$V_{\text{DS}}=-20\text{V}$, $I_D=-10\text{A}$	---	10.5	---	S
Q_g	Total Gate Charge	$V_{\text{DS}}=-15\text{V}$, $V_{\text{GS}}=-10\text{V}$, $I_D=-18\text{A}$	---	32	---	nC
Q_{gs}	Gate-Source Charge		---	6	---	
Q_{gd}	Gate-Drain Charge		---	9	---	
$T_{\text{d}(\text{on})}$	Turn-On Delay Time	$V_{\text{DS}}=-15\text{V}$, $V_{\text{GS}}=-10\text{V}$, $R_L=1.25\Omega$	---	13	---	ns
T_r	Rise Time		---	8	---	
$T_{\text{d}(\text{off})}$	Turn-Off Delay Time		---	26	---	
T_f	Fall Time		---	12	---	
C_{iss}	Input Capacitance	$V_{\text{DS}}=-15\text{V}$, $V_{\text{GS}}=0\text{V}$, $f=1\text{MHz}$	---	2000	---	pF
C_{oss}	Output Capacitance		---	500	---	
C_{rss}	Reverse Transfer Capacitance		---	300	---	

Diode Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
V_{SD}	Diode Forward Voltage	$V_{\text{GS}}=0\text{V}$, $I_{\text{SD}}=-1\text{A}$	---	---	-1.3	V

This product has been designed and qualified for the consumer market.
 Cmos assumes no liability for customers' product design or applications.
 Cmos reserves the right to improve product design, functions and reliability without notice.