## **SIEMENS**

Data sheet US2:111D3BH



Class 11, manual switch, 1 Amps, NEMA 1,

Figure similar

product brand name	Class 11
design of the product	Manual Switch
General technical data	
ambient temperature [°F]	
during storage	122 176 °F
<ul><li>during operation</li></ul>	68 140 °F
ambient temperature	
during storage	50 80 °C
<ul><li>during operation</li></ul>	20 60 °C
number of poles for main current circuit	3
Horsepower ratings	
yielded mechanical performance [hp] for 3-phase AC motor	
<ul><li>at 460/480 V rated value</li></ul>	0.5 hp
<ul><li>at 575/600 V rated value</li></ul>	0.5 hp
Contactor	
mechanical service life (switching cycles) of the main contacts typical	100000
Overload relay	
adjustable current response value current of the current- dependent overload release	1 A
Mounting/wiring	
fastening method	wall mounting
type of electrical connection for supply voltage line-side	Screw-type terminals
Short-circuit current rating	
design of the short-circuit trip	magnetic
Certificates/ approvals	
certificate of suitability	UL
Further information	

Industrial Controls - Product Overview (Catalogs, Brochures,...)

www.usa.siemens.com/iccatalog

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:111D3BH

 $Service \& Support\ (Manuals,\ Certificates,\ Characteristics,\ FAQs,...)$ 

https://support.industry.siemens.com/cs/US/en/ps/US2:111D3BH

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:111D3BH&lang=en">http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:111D3BH&lang=en</a>

Certificates/approvals

https://support.industry.siemens.com/cs/US/en/ps/US2:111D3BH/certificate

last modified: 5/31/2021 🖸