

Class 11, manual starter, 2.2-3.2 Amps, NEMA 1,

product brand name	Class 11
design of the product	Manual Starter

General technical data

ambient temperature [°F]	
<ul style="list-style-type: none"> during storage during operation 	122 ... 176 °F 68 ... 140 °F
ambient temperature	
<ul style="list-style-type: none"> during storage during operation 	50 ... 80 °C 20 ... 60 °C
number of poles for main current circuit	3

Contactors

mechanical service life (switching cycles) of the main contacts typical	100000
-------------------------------------------------------------------------	--------

Coil

type of voltage of the control supply voltage	n.a.
-----------------------------------------------	------

Overload relay

adjustable current response value current of the current-dependent overload release	2.2 ... 2.2 A
-------------------------------------------------------------------------------------	---------------

Mounting/wiring

fastening method	wall mounting
------------------	---------------

Short-circuit current rating

design of the short-circuit trip	magnetic
----------------------------------	----------

Certificates/ approvals

certificate of suitability	UL
----------------------------	----

Further information

Industrial Controls - Product Overview (Catalogs, Brochures,...)

www.usa.siemens.com/iccatalog

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:11PD3BF>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/US/en/ps/US2:11PD3BF>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:11PD3BF&lang=en

Certificates/approvals

<https://support.industry.siemens.com/cs/US/en/ps/US2:11PD3BF/certificate>

last modified:

5/31/2021 