

SuperDiode – 1A, 50~1000V Surface Mount Fast Recovery Rectifier



1. Features

- Glass passivated device
- Low reverse leakage
- Metallurgically bonded construction
- High temperature soldering guaranteed: 260 °C/10 seconds,0.375”(9.5mm) lead length,5 lbs. (2.3kg) tension

2. Mechanical Data

- Case: SOD-123FL molded plastic body over passivated chip
- Terminals: Solderable per MIL-STD-750, Method 2026
- Polarity: Color band denotes cathode end
- Mounting Position: Any

3. Marking and Circuit

Marking	Circuit
	

4. Specification

Absolute Maximum Rating & Electrical Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified.







Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Parameters	Symbols	F1	F2	F3	F4	F5	F6	F7	Unit
Maximum repetitive peak reverse voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum average forward rectified current at TA=65°C (NOTE 1)	$I_{(AV)}$	1							A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	$I_{FSM}$	25							A
Maximum instantaneous forward voltage at 1.0A	$V_F$	1.3							V
Maximum DC reverse current TA=25 C at rated DC blocking voltage TA=125 C	$I_R$	5.0							uA
		50.0							
Typical junction capacitance (NOTE 3)	$C_J$	15							pF
Maximum reverse recovery time (NOTE 2)	$T_{RR}$	150				250	500		°C/W
Operating junction and storage temperature range	$T_J, T_{STG}$	-55 to +150							°C


Note:

1. Averaged over any 20ms period.
2. Measured with  $I_F=0.5A$ ,  $I_R=1A$ ,  $I_{rr}=0.25A$ .
3. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

## 5. Typical Characteristic




6. Dimension and Patterns (SOD-123FL)



Units: mm

Symbol	Min.	Max.
A	2.50	2.70
B	1.70	1.90
C	3.50	3.70
D	0.10	0.20
E	0.50	0.70
F	0.90	1.10
G	0.88	1.08



Note:

1. Controlling dimension: in millimeters
2. General tolerance:  $\pm 0.05\text{mm}$
3. The pad layout is for reference only
4. Unit: mm

**DISCLAIMER**

ELECSUPER PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with ElecSuper products. You are solely responsible for

- (1) selecting the appropriate ElecSuper products for your application;
- (2) designing, validating and testing your application;
- (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements.

These resources are subject to change without notice. ElecSuper grants you permission to use these resources only for development of an application that uses the ElecSuper products described in the resource. Other reproduction and display of these resources are prohibited. No license is granted to any other ElecSuper intellectual property right or to any third party intellectual property right. ElecSuper disclaims responsibility for, and you will fully indemnify ElecSuper and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources. ElecSuper's products are provided subject to ElecSuper's Terms of Sale or other applicable terms available either on [www.elecsuper.com](http://www.elecsuper.com) or provided in conjunction with such ElecSuper products. ElecSuper's provision of these resources does not expand or otherwise alter ElecSuper's applicable warranties or warranty disclaimers for ElecSuper products.