

SuperSchottky – 1A, 20~200V Schottky barrier rectifiers



**1. Features**

- The plastic package carries Underwriters Laboratory
- Flammability Classification 94V-0
- For surface mounted applications
- Built-in strain relief, ideal for automated placement
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed 250 C/10 seconds at terminals

**2. Mechanical Data**

- Case: Molded plastic body
- Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity: Polarity symbol marking on body
- Mounting Position: Any
- Weight: 0.0023 ounce, 0.07 grams

**3. Marking and Circuit**

Marking	Circuit
	

**4. Specification**

**Absolute Maximum Rating & Electrical Characteristics**

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load.

Parameters	Symbol	SS12A	SS14A	SS145A	SS16A	SS18A	SS110A	SS115A	SS120A	Unit
Maximum repetitive peak reverse voltage	$V_{RRM}$	20	40	45	60	80	100	150	200	V
Maximum RMS voltage	$V_{RMS}$	14	28	31.5	42	56	70	105	140	V
Maximum DC blocking voltage	$V_{DC}$	20	40	45	60	80	100	150	200	V
Maximum average forward rectified current at $T_L=100^{\circ}C$	$I_{F(AV)}$	1.0								A
Non-Repetitive Peak Forward Surge Current: 8.3ms single half sine-wave superimposed on rated load	$I_{FSM}$	30								A
Maximum instantaneous forward voltage at 1.0A	$V_F$	0.55		0.7		0.85		0.95		V
Maximum DC reverse current at rated	$I_R$	$T_J=25^{\circ}C$				$T_J=125^{\circ}C$				mA
DC blocking voltage		0.5				0.05				
Typical thermal resistance	$R_{\theta JA}$	80								$^{\circ}C/W$
Operating junction temperature range	$T_J$	-55 TO +125				-55 TO +150				$^{\circ}C$
Storage temperature range	$T_{STG}$	-55 TO +150								$^{\circ}C$

## 5. Typical Characteristic

FIG. 1- DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PER LEG




FIG. 3-TYPICAL FORWARD VOLTAGE CHARACTERISTICS







FIG. 4-TYPICAL REVERSE LEAKAGE CHARACTERISTICS



6. Dimension (DO-214AC/SMA)



Suggested Pad Layout



Symbol	Unit (mm)	Unit (inch)
A	1.68	0.066
B	1.52	0.060
C	3.90	0.154
D	2.41	0.095
E	5.45	0.215

**DISCLAIMER**

ELECSUPER PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with ElecSuper products. You are solely responsible for

- (1) selecting the appropriate ElecSuper products for your application;
- (2) designing, validating and testing your application;
- (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements.

These resources are subject to change without notice. ElecSuper grants you permission to use these resources only for development of an application that uses the ElecSuper products described in the resource. Other reproduction and display of these resources are prohibited. No license is granted to any other ElecSuper intellectual property right or to any third party intellectual property right. ElecSuper disclaims responsibility for, and you will fully indemnify ElecSuper and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources. ElecSuper's products are provided subject to ElecSuper's Terms of Sale or other applicable terms available either on [www.elecsuper.com](http://www.elecsuper.com) or provided in conjunction with such ElecSuper products. ElecSuper's provision of these resources does not expand or otherwise alter ElecSuper's applicable warranties or warranty disclaimers for ElecSuper products.