





修订 REV	标记 MARK	修改摘要 REVISION DESCRIPTION	签名 SIGNATURE	日期 DATE
AO		NEW RELEASE	黄艳兰	2022-03-10




材质：  
 塑胶：PA66  
 PIN针：黄铜镀锡

线数 poles	编号 part no	尺寸 Dimensions (mm)	
		A	B
2	HDGC2505WR-2P	2.50	7.50
3	HDGC2505WR-3P	5.00	10.0
4	HDGC2505WR-4P	7.50	12.5
5	HDGC2505WR-5P	10.00	15.0
6	HDGC2505WR-6P	12.50	17.5
7	HDGC2505WR-7P	15.00	20.0
8	HDGC2505WR-8P	17.50	22.5
9	HDGC2505WR-9P	20.00	25.0
10	HDGC2505WR-10P	22.50	27.5
11	HDGC2505WR-11P	25.00	30.0
12	HDGC2505WR-12P	27.50	32.5
13	HDGC2505WR-13P	30.00	35.0
14	HDGC2505WR-14P	32.50	37.5
15	HDGC2505WR-15P	35.00	40.0
16	HDGC2505WR-16P	37.50	42.5

### 技术要求

1. 温度范围 (Temperature range):  $-25^{\circ} \text{C} \sim +85^{\circ} \text{C}$
2. 额定电压 (Voltage rating): 250V. AC/DC
3. 额定电流 (Current rating): 3A
4. 接触电阻 (Contact resistance):  $\leq 0.02 \Omega$
5. 绝缘电阻 (Insulation resistance)  $\geq 1000 \text{M} \Omega$
6. 耐压 (Withstand voltage): 1000V. AC/1分钟 (Minute)

 <b>深圳市华德共创科技有限公司</b> Shenzhen Huade co-create Technology Co., LTD TEL : 0755-27111225 FAX : 0755-29940187		TITLE: 产品名称: 5264 弯针						
		PART NO: 产品编号: HDGC2505WR-XP		DATE	SCALE	UNIT	CODE NUMBER	
X.X	±0.30	X.X°	±3°	APPD: 核准: 谢亮				
X.XX	±0.30	X.XX°	±2°	CHECK: 校对: 王建业				
X.XXX	±0.10	X.XXX°	±1°	DRAW: 绘图: 黄艳兰	2022-03-10	1:1	mm	A126