

## TPS22925 3.6V、3A、导通电阻为 9mΩ 的负载开关

### 1 特性

- 输入电压范围：0.65V 至 3.6V
- 导通电阻
  - $V_{IN} = 3.6V$  时,  $R_{ON} = 9.2m\Omega$
  - $V_{IN} = 1.8V$  时,  $R_{ON} = 9.2m\Omega$
  - $V_{IN} = 1V$  时,  $R_{ON} = 10.2m\Omega$
  - $V_{IN} = 0.65V$  时,  $R_{ON} = 13.1m\Omega$
- 3A 最大连续开关电流
- 静态电流  $I_{Q,VIN} = 29\mu A$  ( $V_{IN} = 3.6V$  时)
- 低控制输入阈值, 支持使用 1.2V、1.8V、2.5V 或 3.3V 逻辑器件
- 受控转换率
  - $t_R = 97\mu s$  ( $V_{IN} = 3.6V$  时) (TPS22925Bx)
  - $t_R = 810\mu s$  ( $V_{IN} = 3.6V$  时) (TPS22925Cx)
- 阻断反向电流 (禁用时)
- 快速输出放电 (QOD) (仅限 TPS22925B 和 TPS22925C)
- 晶圆级芯片规模封装:
  - 0.9mm x 1.4mm、间距为 0.5mm、高度为 0.5mm
- 静电放电 (ESD) 性能经测试符合 JESD 22 规范
  - 1kV 人体放电模式 (HBM) 和 500V 组件充电模式 (CDM)

### 2 应用

- 计算
- 固态硬盘 (SSD)
- 平板电脑
- 可穿戴产品
- 电子销售点 (EPOS)

### 3 说明

TPS22925 产品系列包括 4 款器件: TPS22925B、TPS22925BN、TPS22925C 和 TPS22925CN。每款器件都是一个转换率受控的 9mΩ 单通道负载开关。

该系列器件包含一个可在 0.65V 至 3.6V 输入电压范围内运行的 N 沟道 MOSFET, 最高可支持 3A 持续电流。这种持续电流性能使得该系列器件适用于多种设计与终端设备。TPS22925 系列的每一款器件在禁用时都提供反向电流阻断功能, 从而保护电源并且实现电源多路复用功能。

器件的可控上升时间可大幅降低大容量负载电容所产生的浪涌电流, 从而降低或消除电源压降。当工作输入电压为 3.6V 时, TPS22925Bx 器件的上升时间为 97μs, 而 TPS22925Cx 器件的上升时间为 810μs。


TPS22925 系列器件提供一个可选的 150Ω 集成下拉电阻, 方便在开关断开时实现快速输出放电 (QOD), 这有助于缩减总体解决方案尺寸。TPS22925 系列的每一款器件都采用 0.9mm x 1.4mm、间距 0.5mm、高度为 0.4mm 的 6 引脚晶圆级芯片规模封装 (WCSP), 有助于实现尺寸更小、集成度更高的设计。WCSP 封装与 9mΩ 导通电阻使得该系列器件适用于空间受限型电池供电类应用。器件在自然通风环境下的额定工作温度范围为 -40°C 至 105°C。

器件信息(1)


器件型号	封装	封装尺寸 (标称值)
TPS22925B	DSBGA (6)	0.90mm x 1.40mm
TPS22925BN		
TPS22925C		
TPS22925CN		

(1) 要了解所有可用封装, 请见数据表末尾的可订购产品附录。

简化应用



导通电阻与输入电压间的关系



## 目录

1 特性 .....	1	8.2 Functional Block Diagram .....	13
2 应用 .....	1	8.3 Feature Description .....	13
3 说明 .....	1	8.4 Device Functional Modes .....	15
4 修订历史记录 .....	2	<b>9 Application and Implementation .....</b>	<b>16</b>
<b>5 Device Comparison Table .....</b>	<b>3</b>	9.1 Application Information .....	16
<b>6 Pin Configuration and Functions .....</b>	<b>3</b>	9.2 Typical Application .....	18
<b>7 Specifications .....</b>	<b>4</b>	<b>10 Power Supply Recommendations .....</b>	<b>19</b>
7.1 Absolute Maximum Ratings .....	4	<b>11 Layout .....</b>	<b>20</b>
7.2 ESD Ratings .....	4	11.1 Layout Guidelines .....	20
7.3 Recommended Operating Conditions .....	4	11.2 Layout Example .....	20
7.4 Thermal Information .....	4	<b>12 器件和文档支持 .....</b>	<b>21</b>
7.5 Electrical Characteristics .....	5	12.1 社区资源 .....	21
7.6 Switching Characteristics .....	6	12.2 商标 .....	21
7.7 Typical Characteristics .....	8	12.3 静电放电警告 .....	21
7.8 Typical Characteristics .....	11	12.4 Glossary .....	21
<b>8 Detailed Description .....</b>	<b>13</b>	<b>13 机械、封装和可订购信息 .....</b>	<b>21</b>
8.1 Overview .....	13		

## 4 修订历史记录

Changes from Revision B (January 2016) to Revision C	Page
• 已更改 <a href="#">Device Comparison Table</a> .....	1

---

Changes from Revision A (December 2015) to Revision B	Page
• Deleted the STATUS column from the <a href="#">Device Comparison Table</a> .....	3


---

Changes from Original (November 2015) to Revision A	Page
• 已将文档状态由“产品预览”更新为“量产数据” .....	1

## 5 Device Comparison Table

DEVICE	QOD	$R_{ON}$ (m $\Omega$ ) at $V_{IN} = 3.6$ V	$t_R$ ( $\mu$ s) at $V_{IN} = 3.6$ V	MAXIMUM OUTPUT CURRENT $I_{MAX}$ (A)	ENABLE (ON PIN)
TPS22925B	Yes	9.2	97	3	Active High
TPS22925BN	No				
TPS22925C	Yes		810		
TPS22925CN	No				

## 6 Pin Configuration and Functions



### Pin Assignments

<b>C</b>	GND	ON
<b>B</b>	VOUT	VIN
<b>A</b>	VOUT	VIN
	<b>1</b>	<b>2</b>

### Pin Functions

PIN		TYPE	DESCRIPTION
NAME	NO.		
GND	C1	GND	Ground
ON	C2	I	Switch control input. Active high. Do not leave floating.
VIN	A2	I	Switch input; bypass this input with a ceramic capacitor to ground. See <a href="#">Application Information</a> section for more detail.
	B2		
VOUT	A1	O	Switch output
	B1		

## 7 Specifications

### 7.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)<sup>(1)</sup>

		MIN	MAX	UNIT
Input voltage	V <sub>IN</sub> , ON	-0.3	4	V
Output voltage	V <sub>OUT</sub>	-0.3	4	V
Maximum continuous switch current at T <sub>A</sub> = 60°C	I <sub>MAX</sub>		3	A
Maximum pulsed switch current, 100-μs pulse, 2% duty cycle	I <sub>PLS</sub>		4	A
Junction temperature, T <sub>J</sub>			125	°C
Storage temperature range, T <sub>stg</sub>		-65	150	°C

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

### 7.2 ESD Ratings

		VALUE	UNIT
V <sub>(ESD)</sub>	Electrostatic discharge	Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 <sup>(1)</sup>	±1000
		Charged-device model (CDM), per JEDEC specification JESD22-C101 <sup>(2)</sup>	±500

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process. Manufacturing with less than 500-V HBM is possible with the necessary precautions.  
 (2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process. Manufacturing with less than 250-V CDM is possible with the necessary precautions.

### 7.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

		MIN	MAX	UNIT
V <sub>IN</sub>	Input voltage	0.65	3.6	V
V <sub>OUT</sub>	Output voltage	0	3.6	V
V <sub>IH</sub>	High-level input voltage, ON	0.9	3.6	V
V <sub>IL</sub>	Low-level input voltage, ON	0	0.45	V
C <sub>IN</sub>	Input capacitance	1		μF
T <sub>A</sub>	Operating free-air temperature	-40	105	°C

### 7.4 Thermal Information

THERMAL METRIC <sup>(1)</sup>		TPS22925xx	UNIT
		YPH (DSBGA)	
		6 PINS	
R <sub>θJA</sub>	Junction-to-ambient thermal resistance	110.9	°C/W
R <sub>θJC(top)</sub>	Junction-to-case (top) thermal resistance	1.2	°C/W
R <sub>θJB</sub>	Junction-to-board thermal resistance	30.4	°C/W
ψ <sub>JT</sub>	Junction-to-top characterization parameter	0.8	°C/W
ψ <sub>JB</sub>	Junction-to-board characterization parameter	30.4	°C/W

- (1) For more information about traditional and new thermal metrics, see the *Semiconductor and IC Package Thermal Metrics* application report, [SPRA953](#).

## 7.5 Electrical Characteristics

over operating free-air temperature range (unless otherwise noted). Typical values are for  $T_A = 25^\circ\text{C}$ .

PARAMETER	TEST CONDITIONS	$T_A$	MIN	TYP	MAX	UNIT
$I_{Q,VIN}$ Quiescent current	$V_{ON} = 3.6\text{ V}, I_{OUT} = 0\text{ A}$	$V_{IN} = 3.6\text{ V}$	$-40^\circ\text{C to } 85^\circ\text{C}$	29	71	$\mu\text{A}$
			$-40^\circ\text{C to } 105^\circ\text{C}$		84	
		$V_{IN} = 2.5\text{ V}$	$-40^\circ\text{C to } 85^\circ\text{C}$	28	67	
			$-40^\circ\text{C to } 105^\circ\text{C}$		79	
		$V_{IN} = 1.8\text{ V}$	$-40^\circ\text{C to } 85^\circ\text{C}$	26	65	
			$-40^\circ\text{C to } 105^\circ\text{C}$		76	
		$V_{IN} = 1.2\text{ V}$	$-40^\circ\text{C to } 85^\circ\text{C}$	20	55	
			$-40^\circ\text{C to } 105^\circ\text{C}$		66	
		$V_{IN} = 1.0\text{ V}$	$-40^\circ\text{C to } 85^\circ\text{C}$	16	50	
			$-40^\circ\text{C to } 105^\circ\text{C}$		60	
		$V_{IN} = 0.65\text{ V}$	$-40^\circ\text{C to } 85^\circ\text{C}$	10	39	
			$-40^\circ\text{C to } 105^\circ\text{C}$		49	
$I_{SD,VIN}$ VIN shutdown current	$V_{ON} = 0\text{ V}, V_{OUT} = 0\text{ V}$	$V_{IN} = 3.6\text{ V}$	$-40^\circ\text{C to } 85^\circ\text{C}$	0.5	5	$\mu\text{A}$
			$-40^\circ\text{C to } 105^\circ\text{C}$		9	
		$V_{IN} = 2.5\text{ V}$	$-40^\circ\text{C to } 85^\circ\text{C}$	0.5	4	
			$-40^\circ\text{C to } 105^\circ\text{C}$		6	
		$V_{IN} = 1.8\text{ V}$	$-40^\circ\text{C to } 85^\circ\text{C}$	0.5	4	
			$-40^\circ\text{C to } 105^\circ\text{C}$		6	
		$V_{IN} = 1.2\text{ V}$	$-40^\circ\text{C to } 85^\circ\text{C}$	0.5	3	
			$-40^\circ\text{C to } 105^\circ\text{C}$		5	
		$V_{IN} = 1.0\text{ V}$	$-40^\circ\text{C to } 85^\circ\text{C}$	0.5	3	
			$-40^\circ\text{C to } 105^\circ\text{C}$		5	
		$V_{IN} = 0.65\text{ V}$	$-40^\circ\text{C to } 85^\circ\text{C}$	0.5	3	
			$-40^\circ\text{C to } 105^\circ\text{C}$		5	
$I_{ON}$ ON pin input leakage current	$0.9\text{ V} \leq V_{ON} \leq 3.6\text{ V}$	$-40^\circ\text{C to } 105^\circ\text{C}$			0.1	$\mu\text{A}$
$I_{RC,VIN}$ Reverse current when disabled	$V_{IN} = V_{ON} = 0\text{ V}, V_{OUT} = 3.6\text{ V}$	$-40^\circ\text{C to } 85^\circ\text{C}$		-0.2	-2.5	$\mu\text{A}$
		$-40^\circ\text{C to } 105^\circ\text{C}$			-6	
$R_{ON}$ On-resistance	$I_{OUT} = -200\text{ mA}$	$V_{IN} = 3.6\text{ V}$	25°C	9.2	13	$\text{m}\Omega$
			$-40^\circ\text{C to } 85^\circ\text{C}$		15	
			$-40^\circ\text{C to } 105^\circ\text{C}$		16	
		$V_{IN} = 2.5\text{ V}$	25°C	9.2	13	
			$-40^\circ\text{C to } 85^\circ\text{C}$		15	
			$-40^\circ\text{C to } 105^\circ\text{C}$		16	
		$V_{IN} = 1.8\text{ V}$	25°C	9.2	13	
			$-40^\circ\text{C to } 85^\circ\text{C}$		15	
			$-40^\circ\text{C to } 105^\circ\text{C}$		16	
		$V_{IN} = 1.2\text{ V}$	25°C	9.5	14	
			$-40^\circ\text{C to } 85^\circ\text{C}$		16	
			$-40^\circ\text{C to } 105^\circ\text{C}$		17	
		$V_{IN} = 1.0\text{ V}$	25°C	10.2	15	
			$-40^\circ\text{C to } 85^\circ\text{C}$		17	
			$-40^\circ\text{C to } 105^\circ\text{C}$		18	
		$V_{IN} = 0.65\text{ V}$	25°C	13.1	20	
			$-40^\circ\text{C to } 85^\circ\text{C}$		23	
			$-40^\circ\text{C to } 105^\circ\text{C}$		25	

## Electrical Characteristics (continued)

over operating free-air temperature range (unless otherwise noted). Typical values are for  $T_A = 25^\circ\text{C}$ .

PARAMETER	TEST CONDITIONS	$T_A$	MIN	TYP	MAX	UNIT		
$V_{HYS}$	ON pin hysteresis	25°C				mV		
							$V_{IN} = 3.6\text{ V}$	86
							$V_{IN} = 2.5\text{ V}$	83
							$V_{IN} = 1.8\text{ V}$	82
							$V_{IN} = 1.2\text{ V}$	80
							$V_{IN} = 1.0\text{ V}$	79
	$V_{IN} = 0.65\text{ V}$	79						
$R_{PD}^{(1)}$	Output pull-down resistance	-40°C to 85°C			150	205		
							-40°C to 105°C	215


(1) Applies to TPS22925B and TPS22925C only.

## 7.6 Switching Characteristics<sup>(1)</sup>


over operating free-air temperature range (unless otherwise noted)  $V_{ON} = 3.6\text{ V}$ ,  $R_L = 10\ \Omega$ ,  $C_{IN} = 1\ \mu\text{F}$ ,  $C_L = 0.1\ \mu\text{F}$ ,  $T_A = 25^\circ\text{C}$

PARAMETER	TEST CONDITIONS	TYP (TPS22925Bx)	TYP (TPS22925Cx)	UNIT			
$t_{ON}$	Turn-on time			$\mu\text{s}$			
					$V_{IN} = 3.6\text{ V}$	110	900
					$V_{IN} = 1.8\text{ V}$	94	730
	$V_{IN} = 0.65\text{ V}$	86	620				
$t_{OFF}$	Turn-off time			$\mu\text{s}$			
					$V_{IN} = 3.6\text{ V}$	3	3
					$V_{IN} = 1.8\text{ V}$	2.7	2.7
	$V_{IN} = 0.65\text{ V}$	10.9	10.9				
$t_R$	Output voltage rise time			$\mu\text{s}$			
					$V_{IN} = 3.6\text{ V}$	97	810
					$V_{IN} = 1.8\text{ V}$	61	520
	$V_{IN} = 0.65\text{ V}$	36	300				
$t_F$	Output voltage fall time			$\mu\text{s}$			
					$V_{IN} = 3.6\text{ V}$	2.2	2.2
					$V_{IN} = 1.8\text{ V}$	2.1	2.1
	$V_{IN} = 0.65\text{ V}$	3.6	3.6				
$t_D$	Delay time			$\mu\text{s}$			
					$V_{IN} = 3.6\text{ V}$	64	500
					$V_{IN} = 1.8\text{ V}$	66	490
	$V_{IN} = 0.65\text{ V}$	68	470				

(1) Turn-off time and fall time are dependent on the time constant at the load. For TPS22925BN and TPS22925CN, there is no QOD. The time constant is  $R_L \times C_L$ . For TPS22925B and TPS22925C, internal pull-down resistor  $R_{PD}$  is enabled when the switch is disabled. The time constant is  $(R_{PD} \parallel R_L) \times C_L$ .



**Figure 1. Timing Test Circuit**



Rise times and fall times of the control signal is 100 ns.

**Figure 2. Timing Waveforms**

### 7.7 Typical Characteristics




Figure 3. Quiescent Current vs Input Voltage




Figure 4. Input Shutdown Current vs Input Voltage




Figure 5. On-Resistance vs Temperature




Figure 6. On-Resistance vs Output Current




Figure 7. On-Resistance vs Input Voltage




Figure 8. On-Resistance vs Input Voltage



Typical Characteristics (continued)




Figure 9. Output Pull-Down Resistance vs Input Voltage




Figure 10. Hysteresis vs Input Voltage




Figure 11. High-Level Input Voltage vs Input Voltage




Figure 12. Low-Level Input Voltage vs Input Voltage




Figure 13. Turn-on Time vs Input Voltage (TPS22925Bx)










Figure 14. Turn-on Time vs Input Voltage (TPS22925Cx)

Typical Characteristics (continued)



## 7.8 Typical Characteristics

$C_{IN} = 1 \mu\text{F}$ ,  $C_L = 0.1 \mu\text{F}$ ,  $R_L = 10 \Omega$ ,  $T_A = 25^\circ\text{C}$




Figure 21. Turn-On Response (TPS22925Bx)




Figure 22. Turn-On Response (TPS22925Bx)




Figure 23. Turn-On Response (TPS22925Bx)




Figure 24. Turn-On Response (TPS22925Cx)




Figure 25. Turn-On Response (TPS22925Cx)




Figure 26. Turn-On Response (TPS22925Cx)

### Typical Characteristics (continued)

$C_{IN} = 1 \mu\text{F}$ ,  $C_L = 0.1 \mu\text{F}$ ,  $R_L = 10 \Omega$ ,  $T_A = 25^\circ\text{C}$




Figure 27. Turn-Off Response (TPS22925xx)




Figure 28. Turn-Off Response (TPS22925xx)





Figure 29. Turn-Off Response (TPS22925xx)

## 8 Detailed Description

### 8.1 Overview

The TPS22925 is a single channel, 3-A load switch in a WCSP-6 package. This device implements an N-channel MOSFET with a controlled rise time for applications that need to limit inrush current. The device is also designed to have low leakage current during off state. This prevents downstream circuits from pulling high standby current from the supply. The TPS22925 provides reverse current blocking when the power switch is disabled. Integrated control logic, driver, and output discharge FET eliminates the need for additional external components, which reduces solution size and bill of material (BOM) count.

### 8.2 Functional Block Diagram



### 8.3 Feature Description

#### 8.3.1 ON and OFF Control

The ON pin controls the state of the switch. Asserting the ON pin high enables the switch. The ON pin is compatible with GPIOs of 1.5 V and above.

#### 8.3.2 Quick Output Discharge (QOD) (TPS22925B and TPS22925C only)

When the switch is disabled, a discharge path is enabled between the output and ground with a typical resistance of 150  $\Omega$ . The resistance pulls down the output and prevents it from floating when the device is disabled.

## Feature Description (continued)


### 8.3.3 Reverse Current Blocking

The reverse current blocking feature prevents current flow from the VOUT pin to the VIN pin when the TPS22925 devices are disabled. This feature is particularly useful when the output of the device needs to be driven by another voltage source after TPS22925 is disabled (for example in a power multiplexer application). In order for this feature to work, the TPS22925 must be disabled and either of the following conditions must be met:

- $V_{IN} \geq 0.65\text{ V}$  or
- $V_{OUT} \geq 0.65\text{ V}$

Figure 30 describes the ideal behavior of reverse current blocking circuit in TPS22925 devices where

- $I_{VIN}$  is the current through the VIN pin
- $V_{SRC}$  is the input voltage applied to the device
- $V_{FORCE}$  is the external voltage source forced at the VOUT pin
- $I_{OUT}$  is the output load current



**Figure 30. Reverse Current Blocking**

After the device is disabled via the ON pin and VOUT is forced to an external voltage ( $V_{FORCE}$ ), less than  $6\ \mu\text{A}$  of current flows from the VOUT pin to the VIN pin. This limitation prevents any extra current loading on the voltage source supplying the  $V_{FORCE}$  voltage.

## 8.4 Device Functional Modes

Table 1 shows the function table for the TPS22925xx devices.

**Table 1. Function Table**

ON	VIN to VOUT	OUTPUT DISCHARGE <sup>(1)</sup>
L	OFF	ENABLED
H	ON	DISABLED

(1) This feature is in the TPS22925B and TPS22925C only (not in the TPS22925BN and TPS22925CN).

## 9 Application and Implementation

### NOTE

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

### 9.1 Application Information

The TPS22925 device is a 9-mΩ, single-channel load switch with a controlled slew rate. This design example describes a device containing an N-channel MOSFET that operates at an input voltage range of 3.6 V and supports a maximum continuous current of 3 A. The device provides reverse current blocking when disabled allowing for power supply protection and power multiplexing capabilities.

#### 9.1.1 VIN to VOUT Voltage Drop

The VIN pin to VOUT pin voltage drop in the device is determined by the  $R_{ON}$  of the device and the load current. The on-resistance of the device depends upon the VIN condition of the device. Refer to the on-resistance specification in the *Electrical Characteristics* table. After the on-resistance of the device is determined based upon the input voltage conditions, use [Equation 1](#) to calculate the VIN-to-VOUT voltage drop.

$$\Delta V = I_L \times R_{ON}$$

where

- $\Delta V$  is the voltage drop from the VIN pin to the VOUT pin
- $I_L$  is the load current
- $R_{ON}$  is the on-resistance of the device for a specific input voltage
- Choose an appropriate  $I_L$  so that the maximum current ( $I_{MAX}$ ) specification of the device is not violated (1)

#### 9.1.2 Input Capacitor ( $C_{IN}$ )

To limit the voltage drop on the input supply caused by transient inrush currents when the switch turns on into a discharged load capacitor, place a capacitor between VIN and GND close to the pins. A 1-μF ceramic capacitor,  $C_{IN}$ , is usually sufficient. Higher values of  $C_{IN}$  can be used to further reduce the voltage drop.

#### 9.1.3 Load Capacitor ( $C_L$ )

A  $C_{IN}$  to  $C_L$  ratio of 10-to-1 is recommended for minimizing the input voltage dip caused by inrush currents during startup.



## Application Information (continued)

### 9.1.4 Standby Power Reduction

Any end equipment that is being powered from the battery has a need to reduce current consumption in order to maintain the battery charge for a longer time. TPS22925 devices help to accomplish this reduction by turning off the supply to the modules that are in standby state and hence significantly reducing the leakage current overhead of the standby modules.




Figure 31. Standby Power Reduction

### 9.1.5 Power Multiplexing

Figure 32 shows a power multiplexing application using two TPS22925xN devices. Use the non-QOD version in order to maintain the output voltage. Configure the GPIO control from the microprocessor unit as break-before-make (BBM).




Figure 32. Power Multiplexing with Two TPS22925xN Devices

## Application Information (continued)

### 9.1.6 Thermal Considerations

Restrict the maximum junction temperature lower than 125°C. Use Equation 2 to calculate the maximum allowable dissipation,  $P_{D(max)}$  for a given output load current and ambient temperature.

$$P_{D(max)} = \frac{T_{J(max)} - T_A}{R_{\theta JA}}$$

where

- $P_{D(max)}$  is the maximum allowable power dissipation
- $T_{J(max)}$  is the maximum allowable junction temperature
- $T_A$  is the ambient temperature of the device
- $R_{\theta JA}$  is the junction-to-air thermal impedance (2)

#### NOTE

The  $R_{\theta JA}$  parameter is highly dependent upon board layout. (See the [Thermal Information](#) table)

## 9.2 Typical Application




Figure 33. Typical Application Schematic

### 9.2.1 Design Requirements

For this design example, use the following as the input parameters.

Table 2. Design Parameters

DESIGN PARAMETER	EXAMPLE VALUE
$V_{IN}$	3.6 V
$C_L$	1 $\mu$ F
Maximum Acceptable Inrush Current	40 mA

### 9.2.2 Detailed Design Procedure

#### 9.2.2.1 Managing Inrush Current

When the switch is enabled, the  $V_{IN}$  capacitors must be charged up from 0 V to  $V_{IN}$ . This charge arrives in the form of inrush current. Calculate the inrush current using Equation 3.

$$I_{INRUSH} = C_L \times \frac{dv}{dt}$$

where


- $I_{INRUSH}$  is the inrush current
- $C_L$  is the load capacitance
- $dv/dt$  is the output slew rate (3)

TPS22925Bx and TPS22925Cx have different controlled rise time. TPS22925Bx has shorter rise time than TPS22925Cx. In the application where fast rise time is required and higher inrush current can be tolerated, consider using the TPS22925Bx. For an application that requires a longer rise time and lower inrush current, consider using the TPS22925Cx. Calculate the maximum acceptable slew rate using the design requirements and Equation 4.

$$\frac{dv}{dt} = \frac{I_{\text{INRUSH}}}{C_L} = \frac{40 \text{ mA}}{1.0 \mu\text{F}} = 40 \text{ V/ms} \tag{4}$$

The TPS22925Bx has a typical rise time of 97 μs at 3.6 V. This results in a slew rate of 29.7 V/ms which meets the above design requirements. The TPS22925Cx has a typical rise time of 810 μs at 3.6 V. This results in a slew rate of 3.6 V/ms which also meets the above design requirements. Base on inrush current requirement, either devices can be used.

**9.2.3 Application Curve**



**10 Power Supply Recommendations**


This family of devices is designed to operate with a VIN range of 0.65 V to 3.6 V. This supply must be well regulated and placed as close to the device terminal as possible with the recommended 1 μF bypass capacitor. If the supply is located more than a few inches from the device terminals, additional bulk capacitance may be required in addition to the ceramic bypass capacitors. If additional bulk capacitance is required, an electrolytic, tantalum, or ceramic capacitor of 10 μF may be sufficient.

## 11 Layout

### 11.1 Layout Guidelines

For best performance, all traces should be as short as possible. To be most effective, the input and load capacitors should be placed close to the device to minimize the effects that parasitic trace inductances may have on operation. Using wide traces for VIN, VOUT, and GND helps minimize the parasitic electrical effects.

### 11.2 Layout Example



**Figure 35. TPS22925xx Layout Example**

## 12 器件和文档支持

### 12.1 社区资源

The following links connect to TI community resources. Linked contents are provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

**TI E2E™ Online Community** *TI's Engineer-to-Engineer (E2E) Community*. Created to foster collaboration among engineers. At [e2e.ti.com](http://e2e.ti.com), you can ask questions, share knowledge, explore ideas and help solve problems with fellow engineers.

**Design Support** *TI's Design Support* Quickly find helpful E2E forums along with design support tools and contact information for technical support.

### 12.2 商标

E2E is a trademark of Texas Instruments.  
All other trademarks are the property of their respective owners.

### 12.3 静电放电警告



这些装置包含有限的内置 ESD 保护。存储或装卸时，应将导线一起截短或将装置放置于导电泡棉中，以防止 MOS 门极遭受静电损伤。

### 12.4 Glossary

[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

## 13 机械、封装和可订购信息

以下页中包括机械、封装和可订购信息。这些信息是针对指定器件可提供的最新数据。这些数据会在无通知且不对本文档进行修订的情况下发生改变。要获得这份数据表的浏览器版本，请查阅左侧导航栏。

## 重要声明

德州仪器(TI)及其下属子公司有权根据 JESD46 最新标准,对所提供的产品和服务进行更正、修改、增强、改进或其它更改,并有权根据 JESD48 最新标准中止提供任何产品和服务。客户在下订单前应获取最新的相关信息,并验证这些信息是否完整且是最新的。所有产品的销售都遵循在订单确认时所提供的TI 销售条款与条件。

TI 保证其所销售的组件的性能符合产品销售时 TI 半导体产品销售条件与条款的适用规范。仅在 TI 保证的范围内,且 TI 认为有必要时才会使用测试或其它质量控制技术。除非适用法律做出了硬性规定,否则没有必要对每种组件的所有参数进行测试。

TI 对应用帮助或客户产品设计不承担任何义务。客户应对其使用 TI 组件的产品和应用自行负责。为尽量减小与客户产品和应用相关的风险,客户应提供充分的设计与操作安全措施。

TI 不对任何 TI 专利权、版权、屏蔽作品权或其它与使用了 TI 组件或服务的组合设备、机器或流程相关的 TI 知识产权中授予的直接或隐含权限作出任何保证或解释。TI 所发布的与第三方产品或服务有关的信息,不能构成从 TI 获得使用这些产品或服务的许可、授权、或认可。使用此类信息可能需要获得第三方的专利权或其它知识产权方面的许可,或是 TI 的专利权或其它知识产权方面的许可。

对于 TI 的产品手册或数据表中 TI 信息的重要部分,仅在没有对内容进行任何篡改且带有相关授权、条件、限制和声明的情况下才允许进行复制。TI 对此类篡改过的文件不承担任何责任或义务。复制第三方的信息可能需要服从额外的限制条件。

在转售 TI 组件或服务时,如果对该组件或服务参数的陈述与 TI 标明的参数相比存在差异或虚假成分,则会失去相关 TI 组件或服务的所有明示或暗示授权,且这是不正当的、欺诈性商业行为。TI 对任何此类虚假陈述均不承担任何责任或义务。

客户认可并同意,尽管任何应用相关信息或支持仍可能由 TI 提供,但他们将独立负责满足与其产品及其在应用中使用的 TI 产品相关的所有法律、法规和安全相关要求。客户声明并同意,他们具备制定与实施安全措施所需的全部专业技术和知识,可预见故障的危险后果、监测故障及其后果、降低有可能造成人身伤害的故障的发生机率并采取适当的补救措施。客户将全额赔偿因在此类安全关键应用中使用任何 TI 组件而对 TI 及其代理造成的任何损失。

在某些场合中,为了推进安全相关应用有可能对 TI 组件进行特别的促销。TI 的目标是利用此类组件帮助客户设计和创立其特有的可满足适用的功能安全性标准和要求的终端产品解决方案。尽管如此,此类组件仍然服从这些条款。

TI 组件未获得用于 FDA Class III (或类似的生命攸关医疗设备)的授权许可,除非各方授权官员已经达成了专门管控此类使用的特别协议。

只有那些 TI 特别注明属于军用等级或“增强型塑料”的 TI 组件才是设计或专门用于军事/航空应用或环境的。购买者认可并同意,对并非指定面向军事或航空航天用途的 TI 组件进行军事或航空航天方面的应用,其风险由客户单独承担,并且由客户独立负责满足与此类使用相关的所有法律和法规要求。

TI 已明确指定符合 ISO/TS16949 要求的产品,这些产品主要用于汽车。在任何情况下,因使用非指定产品而无法达到 ISO/TS16949 要求, TI 不承担任何责任。

	产品		应用
数字音频	<a href="http://www.ti.com.cn/audio">www.ti.com.cn/audio</a>	通信与电信	<a href="http://www.ti.com.cn/telecom">www.ti.com.cn/telecom</a>
放大器和线性器件	<a href="http://www.ti.com.cn/amplifiers">www.ti.com.cn/amplifiers</a>	计算机及周边	<a href="http://www.ti.com.cn/computer">www.ti.com.cn/computer</a>
数据转换器	<a href="http://www.ti.com.cn/dataconverters">www.ti.com.cn/dataconverters</a>	消费电子	<a href="http://www.ti.com.cn/consumer-apps">www.ti.com.cn/consumer-apps</a>
DLP® 产品	<a href="http://www.dlp.com">www.dlp.com</a>	能源	<a href="http://www.ti.com.cn/energy">www.ti.com.cn/energy</a>
DSP - 数字信号处理器	<a href="http://www.ti.com.cn/dsp">www.ti.com.cn/dsp</a>	工业应用	<a href="http://www.ti.com.cn/industrial">www.ti.com.cn/industrial</a>
时钟和计时器	<a href="http://www.ti.com.cn/clockandtimers">www.ti.com.cn/clockandtimers</a>	医疗电子	<a href="http://www.ti.com.cn/medical">www.ti.com.cn/medical</a>
接口	<a href="http://www.ti.com.cn/interface">www.ti.com.cn/interface</a>	安防应用	<a href="http://www.ti.com.cn/security">www.ti.com.cn/security</a>
逻辑	<a href="http://www.ti.com.cn/logic">www.ti.com.cn/logic</a>	汽车电子	<a href="http://www.ti.com.cn/automotive">www.ti.com.cn/automotive</a>
电源管理	<a href="http://www.ti.com.cn/power">www.ti.com.cn/power</a>	视频和影像	<a href="http://www.ti.com.cn/video">www.ti.com.cn/video</a>
微控制器 (MCU)	<a href="http://www.ti.com.cn/microcontrollers">www.ti.com.cn/microcontrollers</a>		
RFID 系统	<a href="http://www.ti.com.cn/rfidsys">www.ti.com.cn/rfidsys</a>		
OMAP应用处理器	<a href="http://www.ti.com.cn/omap">www.ti.com.cn/omap</a>		
无线连通性	<a href="http://www.ti.com.cn/wirelessconnectivity">www.ti.com.cn/wirelessconnectivity</a>	德州仪器在线技术支持社区	<a href="http://www.deyisupport.com">www.deyisupport.com</a>

邮寄地址: 上海市浦东新区世纪大道1568号, 中建大厦32楼邮政编码: 200122  
Copyright © 2016, 德州仪器半导体技术(上海)有限公司

**PACKAGING INFORMATION**

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead finish/ Ball material (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
TPS22925BNYPHR	ACTIVE	DSBGA	YPH	6	3000	RoHS & Green	SAC396   SNAGCU	Level-1-260C-UNLIM	-40 to 105	12D9	<a href="#">Samples</a>
TPS22925BNYPHT	ACTIVE	DSBGA	YPH	6	250	RoHS & Green	SAC396   SNAGCU	Level-1-260C-UNLIM	-40 to 105	12D9	<a href="#">Samples</a>
TPS22925BYPHR	ACTIVE	DSBGA	YPH	6	3000	RoHS & Green	SAC396   SNAGCU	Level-1-260C-UNLIM	-40 to 105	12A8	<a href="#">Samples</a>
TPS22925BYPHT	ACTIVE	DSBGA	YPH	6	250	RoHS & Green	SAC396   SNAGCU	Level-1-260C-UNLIM	-40 to 105	12A8	<a href="#">Samples</a>
TPS22925CNYPHR	ACTIVE	DSBGA	YPH	6	3000	RoHS & Green	SAC396   SNAGCU	Level-1-260C-UNLIM	-40 to 105	12C9	<a href="#">Samples</a>
TPS22925CNYPHT	ACTIVE	DSBGA	YPH	6	250	RoHS & Green	SAC396   SNAGCU	Level-1-260C-UNLIM	-40 to 105	12C9	<a href="#">Samples</a>
TPS22925CYPHR	ACTIVE	DSBGA	YPH	6	3000	RoHS & Green	SAC396   SNAGCU	Level-1-260C-UNLIM	-40 to 105	12B9	<a href="#">Samples</a>
TPS22925CYPHT	ACTIVE	DSBGA	YPH	6	250	RoHS & Green	SAC396   SNAGCU	Level-1-260C-UNLIM	-40 to 105	12B9	<a href="#">Samples</a>

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSELETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.


<sup>(6)</sup> Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.




YPH0006



# PACKAGE OUTLINE

DSBGA - 0.4 mm max height

DIE SIZE BALL GRID ARRAY



D: Max = 1.393 mm, Min = 1.332 mm  
E: Max = 0.892 mm, Min = 0.832 mm

4223801/A 06/2017

NOTES:

NanoFree is a trademark of Texas Instruments.


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. NanoFree™ package configuration.

# EXAMPLE BOARD LAYOUT


YPH0006

DSBGA - 0.4 mm max height

DIE SIZE BALL GRID ARRAY



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:35X



SOLDER MASK DETAILS  
NOT TO SCALE

4223801/A 06/2017

NOTES: (continued)


- Final dimensions may vary due to manufacturing tolerance considerations and also routing constraints. For more information, see Texas Instruments literature number SNVA009 ([www.ti.com/lit/snva009](http://www.ti.com/lit/snva009)).

# EXAMPLE STENCIL DESIGN

YPH0006

DSBGA - 0.4 mm max height

DIE SIZE BALL GRID ARRAY



SOLDER PASTE EXAMPLE  
BASED ON 0.1 mm THICK STENCIL  
SCALE:40X

4223801/A 06/2017

NOTES: (continued)

5. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release.

## 重要声明和免责声明

TI 均以“原样”提供技术性及其可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证其中不含任何瑕疵，且不做任何明示或暗示的担保，包括但不限于对适销性、适合某特定用途或不侵犯任何第三方知识产权的暗示担保。

所述资源可供专业开发人员应用TI 产品进行设计使用。您将对以下行为独自承担全部责任：(1) 针对您的应用选择合适的TI 产品；(2) 设计、验证并测试您的应用；(3) 确保您的应用满足相应标准以及任何其他安全、安保或其他要求。所述资源如有变更，恕不另行通知。TI 对您使用所述资源的授权仅限于开发资源所涉及TI 产品的相关应用。除此之外不得复制或展示所述资源，也不提供其它TI 或任何第三方的知识产权授权许可。如因使用所述资源而产生任何索赔、赔偿、成本、损失及债务等，TI 对此概不负责，并且您须赔偿由此对TI 及其代表造成的损害。

TI 所提供产品均受TI 的销售条款 (<http://www.ti.com.cn/zh-cn/legal/termsofsale.html>) 以及ti.com.cn 上或随附TI 产品提供的其他可适用条款的约束。TI 提供所述资源并不扩展或以其他方式更改TI 针对TI 产品所发布的可适用的担保范围或担保免责声明。

邮寄地址：上海市浦东新区世纪大道 1568 号中建大厦 32 楼，邮政编码：200122

Copyright © 2020 德州仪器半导体技术（上海）有限公司