

49SSMD



Features

- External dimensions: 11.5 x 4.8 x 4.2mm.
- Frequency range: 3.579545MHz ~ 64MHz.
- Surface mount type crystal units.
- A great number of standard frequencies.
- High frequency pullability and low equivalent series resistance.
- Highly mass production capability.
- Applications: PC, STB, LCDM and Cable Modem.

Electrical Specifications

Item / Type	49S SMD
Frequency Range	3.2 ~ 50 MHz
Frequency Tolerance (at 25 °C)	± 20ppm, or specify
Frequency Stability Over Operating Temperature Range	± 20ppm, or specify
Operating Temperature Range	- 20 ~ +70 °C, or specify
Shunt Capacitance (C0)	7 pF Max.
Drive Level	1 ~ 500 uW (50 uW typical)
Load Capacitance	Series, 9 pF 12 pF 16 pF, 18 pF, 20 pF, 22 pF, or specify
Aging (at 25 °C)	± 3 ppm / year Max.
Storage Temperature Range	- 40 ~ + 85 °C

Equivalent Series Resistance

Item / Type		49S SMD	
3.2 ~ 3.686 MHz	300 Ω Max	20 ~ 30 MHz	40 Ω Max.
3.686 ~ 5 MHz	120 Ω Max	30 ~ 50 MHz	30 Ω Max.
5 ~ 10 MHz	70 Ω Max		
10 ~ 14 MHz	60 Ω Max.		
14 ~ 20 MHz	50 Ω Max.		

Dimensions

