





06H RoHS Compliant



贴片保险丝(抗浪涌型)

SMD Fuse (High Inrush Current Withstand) 32V



测试标准:
Testing Standard:
UL248-1 UL248-14

额定分断能力:
Interrupting Rating:
50 Amperes at 32V DC


工作温度:
Operating Temperature:
-55°C ~ +125°C

材料:
Materials:
Substrate: ceramic/glass cover
Termination: silver over-plated with nickel and tin
Element: silver

焊接方法:
Soldering Method:
Reflow soldering: 260°C, 10s max

包装:
Packaging:
Automaton taped 5000PCS per reel,
150000PCS per carton

Time-Current Characteristics
电流-时间曲线图



电气特性: Electrical Characteristics

额定电流的% % of Ampere Rating	熔断时间 Opening Time
100%	4 hours Min(大于4小时)
200%	1 s ~ 60 s
250%	5 s Max(小于5秒)

目录编号: Catalog No.D:32V.

目录编号 Catalog No.	额定电流 Ampere Rating	额定电压 Voltage Rating	标示 Marking	熔化热能 ² Melting Integral (A ² .S)	认证 Approvals
					● 表示已获认证 ● 表示认证中
06H1100D	1A	32V	H	0.017	●
06H1150D	1.5A	32V	K	0.060	●
06H1200D	2A	32V	N	0.183	●
06H1250D	2.5A	32V	O	0.240	●
06H1300D	3A	32V	P	0.270	●
06H1400D	4A	32V	S	0.936	●
06H1500D	5A	32V	T	1.865	●