

## Surface Mount Schottky Barrier Rectifier

Reverse Voltage - 20 to 200 V    Forward Current - 1.0 A

### FEATURES

- Metal silicon junction, majority carrier conduction
- For surface mounted applications
- Low power loss, high efficiency
- High forward surge current capability
- For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

### MECHANICAL DATA


- Case: SMAF
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 27mg 0. 00086oz

### Absolute Maximum Ratings and Electrical characteristics

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz resistive or inductive load, for capacitive load, derate by 20 %

#### PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode



Parameter	Symbols	SS12F	SS14F	SS16F	SS18F	SS110F	SS112F	SS115F	SS120F	Units					
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	20	40	60	80	100	120	150	200	V					
Maximum RMS voltage	$V_{RMS}$	14	28	42	56	70	84	105	140	V					
Maximum DC Blocking Voltage	$V_{DC}$	20	40	60	80	100	120	150	200	V					
Maximum Average Forward Rectified Current	$I_{F(AV)}$	1.0							A						
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	$I_{FSM}$	40				30				A					
Max Instantaneous Forward Voltage at 1 A	$V_F$	0.55		0.70		0.85		0.90		V					
Maximum DC Reverse Current $T_a = 25^\circ C$ at Rated DC Reverse Voltage $T_a = 100^\circ C$	$I_R$	0.3 10			0.2 5			0.1 2		mA					
Typical Junction Capacitance <sup>1)</sup>	$C_J$	110		80						pF					
Typical Thermal Resistance <sup>2)</sup>	$R_{\thetaJA}$	115							°C/W						
Operating Junction Temperature Range	$T_j$	-55 ~ +125							°C						
Storage Temperature Range	$T_{stg}$	-55 ~ +150							°C						

1) Measured at 1MHz and applied reverse voltage of 4 V D.C.

2) P.C.B. mounted with 0.2 X 0.2" (5 X 5 mm) copper pad areas.

SHIKE MAKE CONSCIOUS PRODUCT

CONSCIOUS PRODUCTS BEGIN WITH CONSCIOUS PEOPLE



# SS12F THRU SS120F

Fig.1 Forward Current Derating Curve




Fig.3 Typical Forward Characteristic




Fig.5 Maximum Non-Repetitive Peak Forward Surge Current




Fig.2 Typical Reverse Characteristics




Fig.4 Typical Junction Capacitance





Fig.6-Typical Transient Thermal Impedance



SHIKE MAKE CONSCIOUS PRODUCT


CONSCIOUS PRODUCTS BEGIN WITH CONSCIOUS PEOPLE



## PACKAGE OUTLINE


Plastic surface mounted package; 2 leads

SMAF



UNIT		A	C	D	E	e	g	H <sub>E</sub>	$\angle$
mm	max	1.1	0.20	3.7	2.7	1.6	1.2	4.9	7°
	min	0.9	0.12	3.3	2.4	1.3	0.8	4.4	
mil	max	43	7.9	146	106	63	47	193	7°
	min	35	4.7	130	94	51	31	173	

### The recommended mounting pad size



SHIKE MAKE CONSCIOUS PRODUCT

CONSCIOUS PRODUCTS BEGIN WITH CONSCIOUS PEOPLE

REV.07

