




# Wirewound Resistors, Commercial Power, Axial Lead, Low Value



## FEATURES

- High power to size ratio
- Low inductance, less than 5 nH
- Ceramic cases are available with circuit board stand-offs (designated with a -3 model ending)
- Superior surge capability
- Extremely low resistance values
- Complete welded construction
- Special inorganic potting compound and ceramic case provide high thermal conductivity in a fireproof package
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



Available



RoHS\*

Available

HALOGEN  
**FREE**

Available

**GREEN**

(5-2008)

Available

STANDARD ELECTRICAL SPECIFICATIONS					
GLOBAL MODEL	HISTORICAL MODEL	POWER RATING $P_{40^{\circ}\text{C}}$ W	RESISTANCE RANGE <sup>(1)</sup> $\Omega$	TOLERANCE $\pm$ %	WEIGHT (typical) g
CPL03	CPL-3	3	0.01 to 0.10	1, 2, 3, 5, 10	3.4
CPL03...3	CPL-3-3	3	0.01 to 0.10	1, 2, 3, 5, 10	3.6
CPL05	CPL-5	5	0.01 to 0.10	1, 2, 3, 5, 10	4.8
CPL05...3	CPL-5-3	5	0.01 to 0.10	1, 2, 3, 5, 10	5.0
CPL07	CPL-7	7	0.01 to 0.10	1, 2, 3, 5, 10	6.8
CPL07...3	CPL-7-3	7	0.01 to 0.10	1, 2, 3, 5, 10	7.0
CPL10	CPL-10	10	0.01 to 0.10	1, 2, 3, 5, 10	9.5
CPL10...3	CPL-10-3	10	0.01 to 0.10	1, 2, 3, 5, 10	9.9
CPL15	CPL-15	15	0.01 to 0.10	1, 2, 3, 5, 10	16.8
CPL15...3	CPL-15-3	15	0.01 to 0.10	1, 2, 3, 5, 10	17.4

**Note**


(1) Resistance is measured 3/8" [9.52 mm] from resistor body

TECHNICAL SPECIFICATIONS		
PARAMETER	UNIT	CPL RESISTOR CHARACTERISTICS
Temperature Coefficient	ppm/°C	$\pm$ 300
Short Time Overload	-	5 x rated power for 5 s
Maximum Working Voltage	V	$(P \times R)^{1/2}$
Operating Temperature Range	°C	-65 to +275
Terminal Strength	lb	10 minimum
Dielectric Withstanding Voltage	$V_{AC}$	1000


GLOBAL PART NUMBER INFORMATION																
Global Part Numbering Example: CPL05R0500J B14 3																
C	P	L	0	5	R	0	5	0	0	J	B	1	4	3		
GLOBAL MODEL		VALUE		TOLERANCE		PACKAGING			SPECIAL							
CPL03 CPL05 CPL07 CPL10 CPL15		R = decimal R1000 = 0.10 $\Omega$		F = $\pm$ 1.0 % G = $\pm$ 2.0 % H = $\pm$ 3.0 % J = $\pm$ 5.0 % K = $\pm$ 10.0 %		E14 = lead (Pb)-free bulk E31 = lead (Pb)-free four layer bulk E01 = lead (Pb)-free skin pack  B14 = tin / lead bulk B31 = tin / lead four layer bulk J01 = tin / lead skin pack			(dash number) (up to 3 digits) from 1 to 999 as applicable							
Historical Part Numbering Example: CPL-5-3 0.05 $\Omega$ 5 % B14																
CPL-5-3		0.05 $\Omega$		5 %		B14										
HISTORICAL MODEL		RESISTANCE VALUE		TOLERANCE CODE		PACKAGING										

**DIMENSIONS** in inches [millimeters]

CPLxx



CPLxx...3



GLOBAL MODEL	DIMENSIONS in inches [millimeters]				
	A <sup>(1)</sup> ± 0.031 [0.794]	B ± 0.031 [0.794]	C ± 0.031 [0.794]	D ± 0.031 [0.794]	E ± 0.001 [0.025]
CPL03	0.875 [22.22]	0.313 [7.94]	0.313 [7.94]	-	0.036 [0.914]
CPL03...3	0.875 [22.22]	0.313 [7.94]	0.313 [7.94]	0.375 [9.52]	0.036 [0.914]
CPL05	0.875 [22.22]	0.375 [9.52]	0.344 [8.73]	-	0.036 [0.914]
CPL05...3	0.875 [22.22]	0.375 [9.52]	0.344 [8.73]	0.406 [10.32]	0.036 [0.914]
CPL07	1.391 [35.32]	0.375 [9.52]	0.344 [8.73]	-	0.036 [0.914]
CPL07...3	1.391 [35.32]	0.375 [9.52]	0.344 [8.73]	0.469 [11.91]	0.036 [0.914]
CPL10	1.875 [47.62]	0.375 [9.52]	0.344 [8.73]	-	0.036 [0.914]
CPL10...3	1.875 [47.62]	0.375 [9.52]	0.344 [8.73]	0.469 [11.91]	0.036 [0.914]
CPL15	1.875 [47.62]	0.500 [12.70]	0.500 [12.70]	-	0.036 [0.914]
CPL15...3	1.875 [47.62]	0.500 [12.70]	0.500 [12.70]	0.625 [15.87]	0.036 [0.914]

**Note**

<sup>(1)</sup> Potting compound may extend outside of ceramic case up to 0.060 [1.52] maximum per side


**MATERIAL SPECIFICATIONS**

**Element:** self-supporting copper-nickel alloy or nickel-chrome alloy, depending on resistance range

**Body:** steatite ceramic case with inorganic potting compound

**Terminals:** tinned copper

**Part Marking:** Dale, model, wattage, value, tolerance, date code

**DERATING**

PERFORMANCE		
TEST	CONDITIONS OF TEST	TEST LIMITS (EIA RS-344)
Thermal Shock	-55 °C to +275 °C, 5 cycles, 30 min dwell time	± (5.0 % + 0.05 Ω) ΔR
Short Time Overload	5 x rated power for 5 s	± (4.0 % + 0.05 Ω) ΔR
Dielectric Withstanding Voltage	1000 V <sub>RMS</sub> for 1 min	± (2.0 % + 0.05 Ω) ΔR
Low Temperature Operation	-65 °C, full rated working voltage for 45 min	± (3.0 % + 0.05 Ω) ΔR
Bias Humidity	75 °C, 90 % to 100 % RH, 240 h	± (5.0 % + 0.05 Ω) ΔR
Load Life	1000 h at rated power, +40 °C, 1.5 h "ON", 0.5 h "OFF"	± (5.0 % + 0.05 Ω) ΔR
Terminal Strength	5 s to 10 s 10 pound pull test, torsion test - 3 alternating directions, 360° each	± (1.0 % + 0.05 Ω) ΔR
Resistance to Solder Heat	Terminal immersed 3.5 s in molten solder at 1/8" to 3/16" from body	± (1.0 % + 0.05 Ω) ΔR



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.