三菱J3/ES/JE系列伺服电缆线

X300

三菱J3/ES/JEシリーズ用サーボケーブル

Servo cable for Mitsubishi J3/ES/JE series

省空间 | 伺服线 | 耐油耐热 | 柔软 | 电缆配线

非在库品

Items in the library of non -

询问胜蓝 0755-8886 0059 | 当日出货

特点 Features

* 电缆外护套由低粘性高耐磨损材料制成；
* 具有高抗弯曲强度及高柔韧性；
* 耐油和冷却剂，耐刻痕；
* 适用于一般布线场所及拖链。

* ケーブルのカバーは低粘り高耐摩耗材料でつくりられます：
* 高い曲げ強度と高柔軟性；
* 耐油和冷却剂，耐刻痕，冷却剂と油に強い、耐きず：
* 普通の配線場所およびローラーチェーンに適用.

* Cable oversheath is made of low tack and high wear-resistance material;
* With high flexural strength and high flexibility;
* With oil and refrigerant resistance function, uneasy to leave scratch;
* Applicable to general wiring situation and towing transmission places.

注意事项 note

- 请根据下表，选择伺服马达的线束。
- 请不要随意变更线束内部品。
- Please according to the table below to choose the wiring harness of the servo motor.
- Please don't change the wiring harness internal component at will.

订货范例 Order

型号 Model	全长 Length (mm)
X300-1	1000

注意：全长最短长度为1000mm，如需要缩加长度以1000mm递增。

Notice：the shortest length is 1000mm, such as thened to increase to 1000mm for increasing unit.

注意：以上为标准型号。如需使用拖链线材，请在型号后加“T”,详情请咨询相关销售人员。

Notice：The above is standard cable model. f you want to usethe chain wire, Please sign "T" after the model.Please contact sales for more details.

端口对应列表 Port corresponding list

型号 Model	对应功率 Corresponding power	驱动器 Drive	对应马达(W) Corresponding motor	原厂型号 Original model
X300-1 X300-1T	100～600W	J3，J4 E，JE	HF-MP HG-MR HF-KP HG-KR HF-KE HG-KN HF-KN (13/23/43)	MR-PWS1CBL()-A1-L
X300-1H X300-1HT	750W	J3，J4 E，JE	HF-MP HG-KE HF-KR HG-KN HF-KP HG-KR HF-MR (73) HF-SE(52)	MR-PWS1CBL()-A1-L
X300-2/2T	100～750W	J3，J4 E，JE	HF-MP HG-KN HF-KP HG-KR HF-KE HG-MR HF-KW HF-KN (13/23/43/73)	B:MR-J3ENCBL()-L
X300-3				S:MR-BKS1CBL()-A1-L
X300-4	600～1000W	J3，J4 E，JE	HF-SP (51/52/81/102) HG-SR(51/52/81/102) HF-SN(52/102) HF-SE52JWI-S100 HF-SE102JWI-10	插头：MR-PWCNS4
X300-4H	2000W	J3，J4 E，JE	HF-SP(152) HF-SN(152) HG-SR(152) HF-SE152JWI-S100	
X300-5	2000～3000W	J3，J4 E，JE	HF-SP(121/201/202/352) HF-SN(202 302) HG-SR(121/201/202/301/352)	插头：MR-PWCNS5
X300-5H	5000W	J3，J4	HF-SP(502) HG-SR(502)	
X300-6	600～5000W	J3，J4 JE	HF-SP (51/52/81/102/121/152 /201/202/352/502) HG-SR(51/52/81/102/121/152 /202/201/301/352) HF-SN HG-KN HG-SN (52/102/152/202/302)	MR-J3ENSCBL()-L
X300-7	750～2000W	E	HF-SE()JWI-S100 (52/102/152/202) HG-JR701M(4) HG-JR37K1M(4) HG-JR45K1M4HG JR55K1M4HG-JR601(4) HG-JR37K1(4))	/
X300-8	600～5000W	J3，J4 E，JE	HF-SP (51/52/102/121/152/201 /202/352/502) HF-SN (52 102 152 202) HG-SR HG-SN (51/52/81/102/121/152/ 201/202/301)	插头：MR-BKCNS1

外形图 Outline

型号 Model	功能 Functions	缆线规格 Cable specification	外形图 Dimensions	电路图 Wiring Diagram
X300-1 X300-1T	伺服动力线 Servo drive cable	AWG20	全长 Length 120mm CN1 JN4FT04SJ1-R (插头针: JN4FT-Z) CN2	X300-1/1H CN1 1 2 3 4 E U V W CN2
X300-1H X300-1HT	伺服动力线 Servo drive cable	AWG18		
X300-2 X300-2T	伺服编码器线 Servo encoder cable	AWG24	全长 Length CN1 1674320-1 (插头针: 1674335-4) CN2	X300-2 CN1 3 6 5 4 2 9 1 7 8 1 2 3 4 9 金属牌 CN2
X300-3	伺服刹车线 Servo brake cable	AWG22	全长 Length 120mm CN1 JN4FT02SJ1-R (插头针: JN4FT-Z) CN2	X300-3 CN1 1 2 B1 B2 CN2
X300-4	伺服动力线 Servo drive cable	AWG17	全长 Length 120mm CN1 X300-4-4H: D/MS3108B18-10S X300-5-5H: D/MS3106B22-22S CN2	X300-4/4H/5/5H CN1 A B C D U V W E CN2
X300-4H	伺服动力线 Servo drive cable	AWG13		
X300-5	伺服动力线 Servo drive cable	AWG13		
X300-5H	伺服动力线 Servo drive cable	AWG10		
X300-6	伺服编码器线 Servo encoder cable	AWG24	全长 Length CN1 X300-6: CM10-SP10S-M X300-7: D/MS3106B20-29S CN2	X300-6 CN1 8 S 1 2 4 10 1 2 3 4 9 金属牌 CN2
X300-7	伺服编码器线 Servo encoder cable	AWG24		X300-7 CN1 S R C D F N 1 2 3 4 9 金属牌 CN2
X300-8	伺服刹车线 Servo brake cable	AWG17	全长 Length 120mm CN1 CM10-SP2S-S CN2	X300-8 CN1 1 2 B2 CN2