SIEMENS

Data sheet US2:52SA2BBB

design of the product Enclosure number of command points 1 delivery state as a kit No Actuator design of the actuating element selector switch plastic type of unlocking device rotate-to-unlatch mechanism number of switching positions 3 Front ring product component front ring standard metal of the front ring metal of the front ring metal of the front ring metal color of the front ring holder Metal General technical data product component • light source No degree of pollution 1 protection class IP operating frequency maximum 600 1/h Ambient conditions anbient temperature • during storage 40 +85 °C		Selector swich, metal Spring return from left Short lever position, B Cam 3 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)
number of command points delivery state as a kit No Actuator design of the actuating element material of the actuating element yep of unlocking device number of switching positions Front ring product component front ring design of the front ring material of the front ring color of the front ring material of the holder General technical data product component • light source degree of pollution protection class IP operating frequency maximum Amblent conditions ambient temperature e during speration e during storage until selection witch discovered by the comment of the conditions election of the conditions and the conditions and the conditions and	design of the product	
delivery state as a kit Actuator design of the actuating element material of the actuating element type of unlocking device number of switching positions routing product component front ring getsign of the front ring material of the holder General technical data product component elight source No degree of pollution protection class IP operating frequency maximum Ambient conditions ambient temperature e during operation e during storage Installation/ mounting/ dimensions	Enclosure	
Actuator design of the actuating element selector switch material of the actuating element plastic type of unlocking device rotate-to-unlatch mechanism number of switching positions Front ring product component front ring yes design of the front ring standard material of the front ring metal color of the front ring chrome Holder material of the holder General technical data product component	number of command points	1
design of the actuating element material of the actuating element type of unlocking device number of switching positions rotate-to-unlatch mechanism number of switching positions rotate-to-unlatch mechanism number of switching positions rotate-to-unlatch mechanism 3 Front ring Product component front ring yes design of the front ring standard material of the front ring metal color of the front ring chrome Holder material of the holder Metal General technical data product component ight source legree of pollution 1 protection class IP operating frequency maximum Ambient conditions ambient temperature during operation during storage -35 +70 °C -40 +85 °C	delivery state as a kit	No
material of the actuating element type of unlocking device number of switching positions 3 Front ring product component front ring design of the front ring material of the front ring color of the front ring material of the front ring color of the front ring material of the holder material of the holder Metal General technical data product component	Actuator	
type of unlocking device rotate-to-unlatch mechanism number of switching positions 3 Front ring product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring chrome Holder material of the holder Metal General technical data product component	design of the actuating element	selector switch
number of switching positions Front ring product component front ring	material of the actuating element	plastic
product component front ring design of the front ring material of the front ring metal color of the front ring metal color of the front ring metal color of the front ring Metal General technical data product component	type of unlocking device	rotate-to-unlatch mechanism
product component front ring design of the front ring material of the front ring color of the front ring material of the holder material of the holder Metal General technical data product component • light source degree of pollution protection class IP operating frequency maximum Ambient conditions ambient temperature • during operation • during storage -40 +85 °C Installation/ mounting/ dimensions	number of switching positions	3
design of the front ring material of the front ring metal color of the front ring chrome Holder material of the holder Metal General technical data product component	Front ring	
material of the front ring chrome Holder material of the holder Metal General technical data product component • light source degree of pollution protection class IP operating frequency maximum Ambient conditions ambient temperature • during operation • during storage during storage Installation/ mounting/ dimensions	product component front ring	Yes
color of the front ring Holder material of the holder General technical data product component	design of the front ring	standard
material of the holder Metal General technical data product component Ight source degree of pollution protection class IP IP66 operating frequency maximum Ambient conditions ambient temperature Iduring operation Iduring storage Jeneral Metal No No No No 1 P66 600 1/h Arbient conditions ambient temperature Iduring operation Jeneral Metal Arbient conditions Arbient conditions ambient temperature Iduring operation Jeneral Metal Arbient conditions Arbient conditions Arbient conditions	material of the front ring	metal
material of the holder General technical data product component • light source No degree of pollution protection class IP operating frequency maximum Ambient conditions ambient temperature • during operation • during storage dimensions IMERICAL Metall Metal Metal Metal No No 1 1 1 1 1 1 1 1 1 1 1 1 1	color of the front ring	chrome
product component • light source No degree of pollution protection class IP operating frequency maximum Ambient conditions ambient temperature • during operation • during storage Installation/ mounting/ dimensions	Holder	
product component Ight source degree of pollution protection class IP operating frequency maximum Ambient conditions ambient temperature during operation during storage during storage Installation/ mounting/ dimensions	material of the holder	Metal
● light source degree of pollution protection class IP IP66 operating frequency maximum Ambient conditions ambient temperature ● during operation ● during storage during storage Installation/ mounting/ dimensions	General technical data	
degree of pollution protection class IP IP66 operating frequency maximum 600 1/h Ambient conditions ambient temperature • during operation • during storage -40 +85 °C Installation/ mounting/ dimensions	product component	
protection class IP operating frequency maximum 600 1/h Ambient conditions ambient temperature • during operation • during storage -40 +85 °C Installation/ mounting/ dimensions	• light source	No
operating frequency maximum Ambient conditions ambient temperature • during operation • during storage -35 +70 °C -40 +85 °C Installation/ mounting/ dimensions	degree of pollution	1
Ambient conditions ambient temperature • during operation • during storage • during storage -40 +85 °C	protection class IP	IP66
ambient temperature	operating frequency maximum	600 1/h
 during operation during storage 40 +85 °C Installation/ mounting/ dimensions	Ambient conditions	
◆ during storage	ambient temperature	
Installation/ mounting/ dimensions	 during operation 	-35 +70 °C
	during storage	-40 +85 °C
shape of the installation opening round	Installation/ mounting/ dimensions	
	shape of the installation opening	round
Certificates/ approvals	Certificates/ approvals	
Further information	Further information	

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SA2BBB

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SA2BBB

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52SA2BBB

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SA2BBB&lang=en

5/31/2021 last modified: