SIEMENS

Data sheet US2:52SX2GAB



Metal NEMA 4X, selector switch Maintained, short lever position, G Cam 3 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)

Figure similar

design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
design of the actuating element	selector switch
material of the actuating element	plastic
type of unlocking device	rotate-to-unlatch mechanism
number of switching positions	3
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	black
Holder	
material of the holder	Metal
	Metal
material of the holder	Metal
material of the holder General technical data	Metal No
material of the holder General technical data product component	
material of the holder General technical data product component • light source	No
material of the holder General technical data product component • light source degree of pollution	No 1
material of the holder General technical data product component • light source degree of pollution protection class IP	No 1 IP66
material of the holder General technical data product component • light source degree of pollution protection class IP operating frequency maximum	No 1 IP66
material of the holder General technical data product component • light source degree of pollution protection class IP operating frequency maximum Ambient conditions	No 1 IP66
material of the holder General technical data product component • light source degree of pollution protection class IP operating frequency maximum Ambient conditions ambient temperature	No 1 IP66 600 1/h
material of the holder General technical data product component • light source degree of pollution protection class IP operating frequency maximum Ambient conditions ambient temperature • during operation	No 1 IP66 600 1/h
material of the holder General technical data product component • light source degree of pollution protection class IP operating frequency maximum Ambient conditions ambient temperature • during operation • during storage Installation/ mounting/ dimensions shape of the installation opening	No 1 IP66 600 1/h
material of the holder General technical data product component • light source degree of pollution protection class IP operating frequency maximum Ambient conditions ambient temperature • during operation • during storage Installation/ mounting/ dimensions	No 1 IP66 600 1/h -35 +70 °C -40 +85 °C

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SX2GAB

Cax online generator

Service&Support (Manuals, Certificates, Characteristics, FAQ: https://support.industry.siemens.com/cs/ww/en/ps/US2:52SX2GAE	s,)	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SX2GAB⟨=en		
last modified:	5/31/2021 🗗	