

### Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of PTGL14AR3R3M3B71B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=PTGL14AR3R3M3B71B0

## PTGL14AR3R3M3B71B0











## Appearance & Shape







### **Features**

- 1. Best suited to meet the requirements for power supplies and motor protection. Error-free operations are assured by rush current.
- 2. Circuit is protected until current is turned off.
- 3. Restores the original low resistance value automatically once the overload is removed.
- 4. Non-contact design leads to long life and no noise. Durable and strong against mechanical vibration and shock because it is a solid element.



## **Applications**

Limited Usage	Consumer Grade
---------------	----------------



## **Packaging Information**

Packaging	Specifications	Standard Packing Quantity
В0	Bulk(Bag)	300

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date.  $Please\ download\ the\ latest\ data sheet\ of\ PTGL14AR3R3M3B71B0\ from\ the\ official\ website\ of\ Muratangle and the statest and the stat$ Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=PTGL14AR3R3M3B71B0

# PTGL14AR3R3M3B71B0



# **Specifications**

Max. Voltage	56V
Hold Current(25°C)	490mA
Measure Condition of Hold Current	(at +25°C)
Hold Current (2)	380mA
Measure Condition of Hold Current (2)	(at +60°C)
Trip Current(25°C)	830mA
Measure Condition of Trip Current	(at +25°C)
Trip Current(2)	980mA
Measure Condition of Trip Current(2)	(at -10°C)
Max. Current	2.5A
Resistance (25°C)	3.3Ω
Resistance Value Tolerance (at 25°C)	±20%
Curie Point(typ.)	120°C
Power Consumption(typ)	2.4W
Operating Temperature Range	-10°C to 60°C
D: Outer Dimension	14.5mm
Thickness	4mm
F: Lead Space	7.5mm
d: Lead Diameter	0.6mm
Shape	Lead
Mass	1.25g
MSL	N

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




### Note: This datasheet may be out of date. Please download the latest datasheet of PTGL14AR3R3M3B71B0 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-us/products/productdetail?partno=PTGL14AR3R3M3B71B0

# PTGL14AR3R3M3B71B0




### **Product Data**





### Resistance-Temperature Charac.



### Operating Time (Typical Curve)

### Protective Threshold Current Range

3 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata:

PTGL14AR3R3M3B71B0