


Product Search Data Sheet

PTGLESARR15M1B51B0

discontinued RoHS REACH

Appearance & Shape





ed±0.05

(in mm)

Note: This datasheet may be out of date. Please download the latest datasheet of PTGLESARR15M1B51B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=PTGLESARR15M1B51B0



1. Best suited to meet the requirements for power supply and motor protection. Error-free operation is assured by rush current.

Circuit is protected until current is turned off.
Restores the original low resistance value automatically once

the overload is removed.

4. Non-contact design leads to long life and no noise. Durable and strong against mechanical vibration and shock because it is a solid element.

5. Lead (Pb) is not contained in the terminations.

Applications

Automotive Usage	Infotainment	
Limited Usage	Automotive Grade	

Packaging Information

	Specifications	Standard
Packaging		Packing
		Quantity
B0	Bulk(Bag)	300

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date. Please download the latest datasheet of PTGLESARR15M1B51B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/pr



Specifications

Max. Voltage	16V
Hold Current(25°C)	1545mA
Measure Condition of Hold Current	(at +25°C)
Hold Current (2)	820mA
Measure Condition of Hold Current (2)	(at +85℃)
Trip Current(25°C)	2855mA
Measure Condition of Trip Current	(at +25℃)
Trip Current(2)	3561mA
Measure Condition of Trip Current(2)	(at -30℃)
Max. Current	10A
Resistance (25°C)	0.15Ω
Resistance Value Tolerance (at 25°C)	±20%
Curie Point(typ.)	120°C
Power Consumption(typ)	2.3W
Operating Temperature Range	-30°C to 85°C
D: Outer Dimension	13.5mm
Thickness	3.5mm
H: Height	18.5mm
F: Lead Space	5mm
d: Lead Diameter	0.6mm
Shape	Lead
Mass	0.69g
MSL	Ν

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.







PTGLESARR15M1B51B0

Note: This datasheet may be out of date. Please download the latest datasheet of PTGLESARR15M1B51B0 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-sg/products/productdetail?partno=PTGLESARR15M1B51B0







Resistance-Temperature Charac.



Operating Time (Typical Curve)

Protective Threshold Current Range

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Murata: PTGLESARR15M1B51B0